

Weicon GmbH

Revision date: 20.08.2010

Revision no.:

1,10

Aluminum Paint A-100

7619-0250

1. Identification of the substance/preparation and of the company/undertaking**Identification of the substance or preparation**

Aluminum Paint A-100

Further trade names

150020

Use of the substance/preparation

Technical material

Coating component

Company/undertaking identification**Manufacturer**

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

WEICON Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3

Telephone: 519 896 5252

Telefax: 519 896 5254

e-mail: info@weicon.ca

Emergency telephone number: 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

2. Hazards identification**Classification**

Indications of danger : Harmful

R-phrases:

Flammable.

Harmful by inhalation and in contact with skin.

Irritating to skin.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking.

3. Composition/information on ingredients**Chemical characterization (Mixture)**

Paint

Hazardous components

CAS-No.	Chemical name	Quantity
1330-20-7	xylene	25 - 50 %
7429-90-5	aluminium powder (stabilised)	10 - 25 %
64742-95-6	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	10 - 25 %
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha	2.5 - 10 %
123-86-4	n-butyl acetate	2.5 - 10 %

4. First aid measures

General information

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off with soap and water.

In case of irritation consult a physician.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids.

If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting.

Seek medical treatment immediately.

Advice to doctor

Attention. Beware, danger of aspiration.

The following symptoms may occur:

Unconsciousness

Anaesthetic state

Headache

Nausea

Confusion

Dizziness

5. Fire-fighting measures

Suitable extinguishing media

Dry powder

Carbon dioxide

Sand

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide and carbon dioxide.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Additional information

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

6. Accidental release measures

Personal precautions

In case of vapour formation use respirator.

Keep away sources of ignition.

Ensure adequate ventilation.

Use personal protective clothing.

Environmental precautions

Do not discharge into the drains or bodies of water.

Methods for cleaning up/taking up

Take up residues with suitable absorbent materials.

Shovel into suitable container for disposal.

Weicon GmbH

Revision date: 20.08.2010

Revision no.:

1,10

Aluminum Paint A-100

7619-0250

7. Handling and storage

Handling

Advice on safe handling

Keep container tightly closed.

Avoid contact with skin, eyes and clothing.

Use only in well-ventilated areas.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pay attention to anti-explosion rules.

Take measures against electrostatic charging.

Storage

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Protect from direct solar radiation.

Keep in closed original container.

Storageclass (VCI):

3 A

8. Exposure controls/personal protection

Exposure limit values

Exposure limits (ACGIH)

CAS No.	Substance	ppm	mg/m ³	F/ml	Category	Origin
123-86-4	Butyl acetate	150	713		TWA (8 h)	TLV
		200	950		STEL (15 min)	TLV
		-	-		Peak	TLV
1330-20-7	Xylene	100	434		TWA (8 h)	TLV
		150	651		STEL (15 min)	TLV
		-	-		Peak	TLV

Occupational exposure controls

Provide appropriate exhaust ventilation at machinery and at places where dust or smoke can be generated.

Protective and hygiene measures

At work do not eat, drink and smoke.

Wash hands and skin before breaks and after work.

When using, do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

ANSI Z49.1 Safety in Welding, Cutting and allied processes.

Respiratory protection

Use suitable breathing apparatus if there is inadequate ventilation.

Hand protection

PVC gloves

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Eye protection

Safety goggles with side protection

Skin protection

Protective clothing

Weicon GmbH

Revision date: 20.08.2010

Revision no.:

1,10

Aluminum Paint A-100

7619-0250

9. Physical and chemical properties

General information

Physical state: Liquid
 Colour: Silver-coloured
 Odour: Solvent-like

Important health, safety and environmental information

	Test method
pH-Value:	n.a.

Changes in the physical state

Boiling point:	137 °C
Flash point:	30 °C

Explosive properties

"The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated."

Lower explosion limits:	0,6 vol. %
Upper explosion limits:	7,5 vol. %
Vapour pressure: (at 20 °C)	5 hPa
Density:	0,95 g/cm ³
Water solubility:	Insoluble
Viscosity / kinematic:	60 mm ² /s 4 DIN 53211

Other information

Ignition temperature:	240 °C
-----------------------	--------

10. Stability and reactivity

Conditions to avoid

Keep away from heat and sources of ignition.

No hazardous reactions known.

Materials to avoid

Oxidizing agents.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Additional information

No decomposition if used as directed.

11. Toxicological information

Acute toxicity

LD50/oral/rat: >5000 mg/kg rat

LD50/dermal/rabbit: >3000 mg/kg

Information refers to main component.

Corrosive and irritant effects

Skin irritation : Non-irritant

Eye irritation: Non-irritant

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Sensitising effects

Skin sensitization, remark : Non-sensitizing

Empirical data on effects on humans

Inhalation of vapours in high concentration can cause narcotic effects.

Further information

Weicon GmbH

Revision date: 20.08.2010

Revision no.:

1,10

Aluminum Paint A-100

7619-0250

Vapours may cause drowsiness and dizziness. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

12. Ecological information

Ecotoxicity

No data available.

Further information

Do not discharge product unmonitored into the environment.

Product is not allowed to discharge into the ground water or aquatic environment.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

13. Disposal considerations

Advice on disposal

Where possible recycling is preferred to disposal.

Product rests: send for disposal, e.g. special waste incineration.

14. Transport information

Canadian TDG

Proper shipping name

PAINT

UN/ID number: UN1263

Hazard classes: 3

Packing group: III

Hazard label: 3

Land transport (ADR/RID)

UN number: 1263

ADR/RID class: 3

Classification Code: F1

Warning plate

Hazard-no.: 33

Hazard label: 3



ADR/RID packing group: III

Limited quantity: LQ4

Description of the goods

Paint

Other applicable information (land transport)

Special provision: 640D

Tunnel restriction code: D/E

Marine transport

UN number: 1263

IMDG code: 3

Marine pollutant: -

Hazard label: 3



IMDG packing group: III

EmS: F-E, S-E

Weicon GmbH

Revision date: 20.08.2010

Revision no.:

1,10

Aluminum Paint A-100

7619-0250

Limited quantity: 5 L

Description of the goods

PAINT

Air transport

UN/ID number: 1263

ICAO/IATA-DGR: 3

Hazard label: 3



ICAO packing group: III

Limited quantity Passenger: 1 L

IATA-packing instructions - Passenger: 309

IATA-max. quantity - Passenger: 60 L

IATA-packing instructions - Cargo: 310

IATA-max. quantity - Cargo: 220 L

Description of the goods

PAINT

15. Regulatory information**Canadian regulations****DSL/NDSL inventory status**

All of the components are listed on the DSL Inventory.

National Pollutant Release Inventory (NPRI)

Xylene, CAS No. 1330-20-7 (max. 50%)

WHMIS classification

WHMIS: B2 & D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

16. Other information**Other data**

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Literature:

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)