

Weicon GmbH

Revision date: 28.12.2009

Revision no.:

1,00

Metal-Fluid Spray

7619-0107

1. Identification of the substance/preparation and of the company/undertaking**Identification of the substance or preparation**

Metal-Fluid Spray

Further trade names

11580

Use of the substance/preparation

Technical aerosol. / Cleaner

Company/undertaking identification**Manufacturer**

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

WEICON Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3

Telephone: 519 896 5252

Telefax: 519 896 5254

e-mail: info@weicon.ca

Emergency telephone number: 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

2. Hazards identification**Classification**

Indications of danger : Extremely flammable, Irritant, Dangerous for the environment

R-phrases:

Heating may cause an explosion.

Extremely flammable.

Vapours may cause drowsiness and dizziness.

3. Composition/information on ingredients**Chemical characterization (Mixture)**

Mixtures of hydrocarbons with propellant propane/butane

Hazardous components

CAS-No.	Chemical name	Quantity
61641-74-5	Propan/Butan	40 - 45 %

4. First aid measures**General information**

Remove contaminated soaked clothing immediately.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

Weicon GmbH

Revision date: 28.12.2009

Revision no.:

1,00

Metal-Fluid Spray

7619-0107

After contact with skin

In case of contact with skin wash off with water.

Consult a doctor if skin irritation persists.

After contact with eyes

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting.

Summon a doctor immediately.

Advice to doctor

The following symptoms may occur:

Unconsciousness

Delirious state

Anaesthetic state

Headache

Confusion

Dizziness

5. Fire-fighting measures

Suitable extinguishing media

Foam

Dry powder

Carbon dioxide

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide and carbon dioxide.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Additional information

Heating will cause pressure rise with risk of bursting.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. Accidental release measures

Personal precautions

Keep away sources of ignition.

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Use personal protective clothing.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Methods for cleaning up/taking up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

7. Handling and storage

Handling

Weicon GmbH

Revision date: 28.12.2009

Revision no.:

1,00

Metal-Fluid Spray

7619-0107

Advice on safe handling

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Do not spray on a naked flame or any other incandescent material.

Heating will cause pressure rise with risk of bursting.

Further information on handling

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Storage**Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place.

Storage temperature may not exceed 50°C (=122°F).

Advice on storage compatibility

Incompatible with oxidizing agents.

Storageclass (VCI):

2 B

8. Exposure controls/personal protection**Exposure limit values****Additional advice on limit values**

Aliphatic hydrocarbon gases (propane/butane/Alkane C1-C4) have workplace limits of 1000 ppm (TWA-ACGIH).

Protective and hygiene measures

Ensure adequate ventilation, especially in confined areas.

Wash hands before breaks and immediately after handling the product.

At work do not eat, drink, smoke or take drugs.

Take off immediately all contaminated clothing.

Avoid contact with eyes, skin or mucous membrane.

Respiratory protection

Do not inhale gases/vapours/aerosols.

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type AX).

Hand protection

Protective gloves resistant to chemicals made of nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril 735> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Safety goggles with side protection

Skin protectionProtective overalls

9. Physical and chemical properties**General information**

Physical state:

Aerosol

Colour:

Colourless

Odour:

Characteristic

Weicon GmbH

Revision date: 28.12.2009

Revision no.:

1,00

Metal-Fluid Spray

7619-0107

Important health, safety and environmental information

Test method

Changes in the physical state

Flash point: <0 °C

Explosive properties

"The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated."

Lower explosion limits: 0,6 vol. %

Upper explosion limits:

Vapour pressure: 3500 hPa
(at 20 °C)

Density (at 20 °C): n.d.

Water solubility: Miscible
(at 20 °C)**Other information**

Ignition temperature: >250 °C

10. Stability and reactivity**Conditions to avoid**

Fire or intense heat may cause violent rupture of packages.

Keep away from heat and sources of ignition.

Formation of explosive gas/air mixtures.

Materials to avoid

Strong oxidizing agents

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Additional information

No decomposition if stored and applied as directed.

11. Toxicological information**Acute toxicity**

No toxicological data available.

Harmful by inhalation.

Inhalation causes narcotic effect/intoxication.

Empirical data on effects on humans

Harmful by inhalation.

Vapours may cause drowsiness and dizziness.

12. Ecological information**Further information**

Do not discharge product unmonitored into the environment.

Product is not allowed to be discharged into aquatic environment.

Product does not contain any organic bound halogens which could lead to AOX-values.

13. Disposal considerations**Advice on disposal**

Remove in accordance with local official regulations.

Where possible recycling is preferred to disposal.

If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging

Offer empty spray cans to an established disposal company.

Weicon GmbH

Revision date: 28.12.2009

Revision no.:

1,00

Metal-Fluid Spray

7619-0107

14. Transport information**Canadian TDG****Proper shipping name**

AEROSOLS

UN/ID number: 1950

Hazard classes: 2.1

Packing group: -

Hazard label: 2.1

Land transport (ADR/RID)

UN number: 1950

ADR/RID class: 2

Warning plate

Hazard-no.: -

Hazard label: 2.1



ADR/RID packing group: -

Description of the goods

AEROSOLS

Other applicable information (land transport)

LQ 2: combination packaging: 1 l / 30 kg (total gross mass); trays: 1 l / 20 kg (total gross mass).

Additional label with symbol "fish and tree" according to subsection 5.2.1.8.3. ADR for single packagings and inner packagings with > 5 kg or 5 L, transition period ends 31.12.2010.

Marine transport

UN number: 1950

IMDG code: 2

Marine pollutant: No

Hazard label: 2.1



IMDG packing group: -

EmS: F-D; S-U

Description of the goods

AEROSOLS

Other applicable information (marine transport)

Limited quantities (chapter 3.4): combination packaging: 1 l / 30 kg (total gross mass); trays: 1 l / 20 kg (total gross mass)

Air transport

UN/ID number: 1950

ICAO/IATA-DGR: 2.1

Hazard label: 2.1



ICAO packing group: -

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

Weicon GmbH

Revision date: 28.12.2009

Revision no.:

1,00

Metal-Fluid Spray

7619-0107

IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

Description of the goods
AEROSOLS FLAMMABLE

15. Regulatory information**Canadian regulations****DSL/NDSL inventory status**

All of the components are listed on the DSL Inventory.

WHMIS classification

WHMIS: A, B5, D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

16. Other information**Other data**

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)