

Weicon GmbH

Revision date: 06.11.2009

Revision no.:

1,00

Plastic-Metal Ceramic BL Slow Hardener

7619-0037

1. Identification of the substance/preparation and of the company/undertaking**Identification of the substance or preparation**

Plastic-Metal Ceramic BL Slow Hardener

Further trade names

10400-3

Use of the substance/preparation

Hardener

Company/undertaking identification**Manufacturer**

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

WEICON Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3

Telephone: 519 896 5252

Telefax: 519 896 5254

e-mail: info@weicon.ca

Emergency telephone number: 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

2. Hazards identification**Classification**

Indications of danger : Corrosive, Harmful

R-phrases:

Harmful by inhalation, in contact with skin and if swallowed.

Causes burns.

May cause sensitization by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. Composition/information on ingredients**Chemical characterization (Mixture)**

Hardener for a 2-component epoxy adhesive

Hazardous components

CAS-No.	Chemical name	Quantity
100-51-6	benzyl alcohol	35 - 47 %
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	30 - 42 %
25620-58-0	Trimethylhexane-1,6-diamine	>1 - 7 %

Further Information

Aliphatic and cyclo-aliphatic polyamine.

4. First aid measures

General information

Remove contaminated soaked clothing immediately.

Consult a doctor if skin irritation persists.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Summon a doctor immediately.

After ingestion

Administer activated charcoal.

Do not induce vomiting.

If swallowed by mistake drink plenty of water and seek medical treatment.

Advice to doctor

In the event of pulmonary irritation treat initially with dexamethasone metered-dose aerosol.

5. Fire-fighting measures

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Additional information

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

6. Accidental release measures

Personal precautions

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

Methods for cleaning up/taking up

Take up with absorbent material.

Shovel into suitable container for disposal.

Additional information

Keep away sources of ignition.

7. Handling and storage

Handling

Advice on safe handling

Avoid contact with the skin and the eyes. Do not breathe vapours.

Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Further information on handling

Avoid formation of aerosols.

Open and handle container with care.

Storage

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Protect from heat and direct solar radiation.

Recommended storage temperature: room temperature.

Advice on storage compatibility

Incompatible with strong acids and bases.

Keep away from sources of ignition.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

Do not store together with food.

Storageclass (VCI): _____ 8 _____

8. Exposure controls/personal protection

Exposure limit values

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale gases/vapours/aerosols.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

Respiratory protection

Use suitable breathing apparatus if there is inadequate ventilation.

Hand protection

Protective gloves resistant to chemicals made of butyl, Minimum coat thickness 0,7 mm, Permeation

resistance (wear duration) approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Tightly fitting goggles

Skin protection

Light protective clothing

Safety Shoes

Weicon GmbH

Revision date: 06.11.2009

Revision no.:

1,00

Plastic-Metal Ceramic BL Slow Hardener

7619-0037

9. Physical and chemical properties

General information

Physical state: Liquid
 Colour: Light yellow
 Odour: Hardly noticeable

Important health, safety and environmental information

	Test method
pH-Value (at 20 °C):	approx. 11 1:1 in water
Changes in the physical state	
Melting point:	>200 °C
Boiling point:	>200 °C
Flash point:	108 °C DIN 51758
Lower explosion limits:	n.d.
Vapour pressure: (at 20 °C)	approx. 0.06 hPa
Density (at 25 °C):	1,0 g/cm ³
Water solubility: (at 20 °C)	Partially soluble
Viscosity / dynamic: (at 25 °C)	30 - 70 mPa·s

Other information

Ignition temperature: n.d.

10. Stability and reactivity

Conditions to avoid

No decomposition if stored and applied as directed.

Materials to avoid

Reactions with strong acids and alkalis.

Reactions with strong oxidizing agents.

Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

11. Toxicological information

Acute toxicity

LD50/oral = 1990 mg/kg Rat

Corrosive and irritant effects

Skin irritation = Corrosive Rabbit

Eye irritation = Corrosive Rabbit eye

Sensitizing effects

Sensitization skin (guinea pig): Sensitizing

May cause sensitization by skin contact.

Empirical data on effects on humans

Harmful: danger of serious damage to health by prolonged exposure if swallowed.

12. Ecological information

Further information

Do not discharge product unmonitored into the environment.

Product is not allowed to be discharged into aquatic environment.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Weicon GmbH

Revision date: 06.11.2009

Revision no.:

1,00

Plastic-Metal Ceramic BL Slow Hardener

7619-0037

13. Disposal considerations**Advice on disposal**

Remove in accordance with local official regulations.

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Empty containers may be recycled. Otherwise dispose of in accordance with applicable regulations.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

14. Transport information**Canadian TDG****Proper shipping name**

Isophoronediamine, Solution

UN/ID number: UN2289

Hazard classes: 8

Packing group: III

Hazard label: 8

Land transport (ADR/RID)

UN number: 2289

ADR/RID class: 8

Warning plate

Hazard-no.: 80

Hazard label: 8



ADR/RID packing group: III

Description of the goods

Isophoronediamine, Solution

Marine transport

UN number: 2289

IMDG code: 8

IMDG packing group: III

Description of the goods

ISOPHORONEDIAMINE, Solution

Air transport

UN/ID number: 2289

ICAO/IATA-DGR: 8

Hazard label: 8



ICAO packing group: III

Description of the goods

ISOPHORONEDIAMINE, Solution

15. Regulatory information

Weicon GmbH

Revision date: 06.11.2009

Revision no.:

1,00

Plastic-Metal Ceramic BL Slow Hardener

7619-0037

Canadian regulations

DSL/NDSL inventory status

All of the components are listed on the DSL Inventory.

WHMIS classification

WHMIS: D2B & E

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

16. Other information

Other data

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)