

Weicon GmbH

Revision date: 13.10.2011

Revision no.:

1,00

Pneuma Lub

7619-0277

**1. Identification of the substance/mixture and of the company/undertaking****Identification of the substance or mixture**

Pneuma Lub

**Further trade names**

S11250-P

**Use of the substance/mixture**

Technical aerosol.

**Company/undertaking identification****Manufacturer**

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

**Supplier**

WEICON Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3

Telephone: 519 896 5252

Telefax: 519 896 5254

e-mail: info@weicon.ca

Emergency telephone number: 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

**2. Hazards identification****Classification**

Indications of danger : Extremely flammable, Irritant, Dangerous for the environment

R-phrases:

Heating may cause an explosion.

Extremely flammable.

Vapours may cause drowsiness and dizziness.

**3. Composition/information on ingredients****Chemical characterization ( Mixture )**

Mixtures of hydrocarbons with propellant propane/butane

**Hazardous components**

CAS No.	Chemical name	Quantity
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified	25 - 50 %
61641-74-5	Propan/Butan	12 - 35 %
8008-20-6	Kerosine (petroleum), Straight run kerosine	10 - 25 %

**4. First aid measures****General information**

Remove contaminated soaked clothing immediately.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours.

Weicon GmbH

Revision date: 13.10.2011

Revision no.:

1,00

Pneuma Lub

7619-0277

---

In the event of symptoms refer for medical treatment.

**After contact with skin**

Wash off with soap and plenty of water.  
Consult a doctor if skin irritation persists.

**After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
If eye irritation persists, consult a specialist.

**After ingestion**

Do not induce vomiting.  
Summon a doctor immediately.

**Advice to doctor**

The following symptoms may occur:  
Anaesthetic state  
Headache

---

**5. Fire-fighting measures**

**Suitable extinguishing media**

Foam  
Dry powder  
Carbon dioxide

**Extinguishing media which must not be used for safety reasons**

Full water jet

**Special exposure hazards arising from substance or mixture itself, combustion products, resulting gases**

Fire may produce:  
Carbon monoxide and carbon dioxide.

**Special protective equipment for fire-fighters**

Use breathing apparatus with independent air supply.

**Additional information**

Heating will cause pressure rise with risk of bursting.  
Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

**6. Accidental release measures**

**Personal precautions**

Keep away sources of ignition.  
In case of vapour formation use respirator.  
Use only explosion-proof equipment.  
Ensure adequate ventilation.  
Use personal protective clothing.

**Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.  
Do not discharge into the subsoil/soil.

**Methods for cleaning up/taking up**

Take up with absorbent material.  
Shovel into suitable container for disposal.

---

**7. Handling and storage**

**Handling**

**Advice on safe handling**

Ensure adequate ventilation.  
Avoid contact with skin, eyes and clothing.

Weicon GmbH

Revision date: 13.10.2011

Revision no.:

1,00

Pneuma Lub

7619-0277

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Do not spray on a naked flame or any other incandescent material.

Heating will cause pressure rise with risk of bursting.

**Further information on handling**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

**Storage****Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place.

Storage temperature may not exceed 50°C (=122°F).

**Advice on storage compatibility**

Incompatible with oxidizing agents.

**Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

**8. Exposure controls/personal protection****Exposure limit values****Exposure limits (ACGIH)**

CAS No.	Chemical name	ppm	mg/m <sup>3</sup>	F/ml	Category	Origin
8008-20-6	Kerosene	-	200 P		TWA (8 h)	TLV
		-	-		STEL (15 min)	TLV
		-	-		Peak	TLV

**Additional advice on limit values**

Aliphatic hydrocarbon gases (propane/butane/Alkane C1-C4) have workplace limits of 1000 ppm (TWA-ACGIH).

**Protective and hygiene measures**

Ensure adequate ventilation, especially in confined areas.

Wash hands before breaks and immediately after handling the product.

At work do not eat, drink, smoke or take drugs.

Take off immediately all contaminated clothing.

Avoid contact with eyes, skin or mucous membrane.

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type AX).

**Hand protection**

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Eye protection**

Safety goggles with side protection

**Skin protection**

Protective clothing

**9. Physical and chemical properties****General information**

Physical state:

Aerosol

Colour:

Yellowish

Weicon GmbH

Revision date: 13.10.2011

Revision no.:

1,00

Pneuma Lub

7619-0277

Odour: Solvent-like

**Important health, safety and environmental information**

Test method

**Changes in the physical state**

Boiling point: -44 °C

Flash point: &lt; 0 °C

**Flammability** >210**Explosive properties**

"The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated."

Lower explosion limits: 0,5 vol. %

Upper explosion limits: 8,5 vol. %

Vapour pressure: 2100 hPa  
(at 20 °C)Density (at 20 °C): 0,75 g/cm<sup>3</sup>Water solubility: Insoluble  
(at 20 °C)**Solvent content**

35.9%

**Other information**

Auto-ignition temperature

Solid: 29.1%

**10. Stability and reactivity****Conditions to avoid**Fire or intense heat may cause violent rupture of packages.  
Keep away from heat and sources of ignition.**Materials to avoid**Strong oxidizing agents  
Formation of explosive gas/air mixtures.**Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

**Further information**

No decomposition if stored and applied as directed.

**11. Toxicological information****Acute toxicity**

Description of possible hazards to health effects is based on experience and/or toxicological characteristics of several components.

Harmful by inhalation.

Vapours may cause drowsiness and dizziness.

**Irritation and corrosivity**

Skin irritation: Non-irritant

Eye irritation : Non-irritant

**Sensitizing effects**

Sensitization skin : Non-sensitizing

**Empirical data on effects on humans**

Harmful by inhalation.

Inhalation of vapours in high concentration can cause narcotic effects.

**12. Ecological information**

Weicon GmbH

Revision date: 13.10.2011

Revision no.:

1,00

Pneuma Lub

7619-0277

**Further information**

Do not discharge product unmonitored into the environment.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**13. Disposal considerations****Advice on disposal**

Remove in accordance with local official regulations.

Where possible recycling is preferred to disposal.

If recycling is not practicable, dispose of in compliance with local regulations.

**Contaminated packaging**

Offer empty spray cans to an established disposal company.

**14. Transport information****Canadian TDG****Proper shipping name**

AEROSOLS

UN/ID number: 1950

Hazard classes: 2.1

Packing group: -

Hazard label: 2.1

**Land transport (ADR/RID)**

UN number: UN1950

ADR/RID class: 2

Classification Code: 5F

Warning plate

Hazard label: 2.1



Limited quantity: 1 L / 30 kg

Tunnel restriction code: D

**Description of the goods**

AEROSOLS

**Marine transport**

UN number: UN1950

IMDG code: 2

IMDG packing group: -

EmS: F-D, S-U

Limited quantity: 1 l / 30 kg

**Description of the goods**

AEROSOLS

**Air transport**

UN/ID number: UN1950

ICAO/IATA-DGR: 2.1

Hazard label: 2.1



Limited quantity Passenger: Y203 / 30 kg G

IATA-packing instructions - Passenger: 203

Weicon GmbH

Revision date: 13.10.2011

Revision no.:

1,00

Pneuma Lub

7619-0277

---

IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**Description of the goods**AEROSOLS, flammable

---

**15. Regulatory information****Canadian regulations****DSL/NDSL inventory status**

All of the components are listed on the DSL Inventory.

**WHMIS classification**

WHMIS: A, B5, A2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

---

**16. Other information****Further Information**

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*