

Weicon GmbH

Revision date: 27.11.2009

Revision no.:

1,00

Spray Chrome-Argent

7619-0074

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

Spray Chrome-Argent

Further trade names

11103

Use of the substance/preparation

Technical aerosol.

Company/undertaking identification

Manufacturer

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

WEICON Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3

Telephone: 519 896 5252

Telefax: 519 896 5254

e-mail: info@weicon.ca

Emergency telephone number: 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

2. Hazards identification

Classification

Indications of danger : Extremely flammable, Irritant, Dangerous for the environment

R-phrases:

Heating may cause an explosion.

Extremely flammable.

Irritating to eyes.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

3. Composition/information on ingredients

Chemical characterization (Mixture)

Mixtures of hydrocarbons with propellant propane/butane

Weicon GmbH

Revision date: 27.11.2009

Revision no.:

1,00

Spray Chrome-Argent

7619-0074

Hazardous components

CAS-No.	Chemical name	Quantity
67-64-1	acetone; propan-2-one; propanone	10 - 25 %
106-97-8	butane	10 - 25 %
123-86-4	n-butyl acetate	2.5 - 10 %
1330-20-7	xylene	2.5 - 10 %
64742-95-6	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	2.5 - 10 %
78-93-3	butanone; ethyl methyl ketone	2.5 - 10 %
7429-90-5	aluminium powder (stabilised)	<=2.5 %

4. First aid measures

General information

Remove contaminated soaked clothing immediately.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting.

Summon a doctor immediately.

5. Fire-fighting measures

Suitable extinguishing media

Dry powder

Carbon dioxide

Sand

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide and carbon dioxide.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Vapours are heavier than air and spread along ground.

Additional information

Heating will cause pressure rise with risk of bursting.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. Accidental release measures

Personal precautions

Keep away sources of ignition.

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Weicon GmbH

Revision date: 27.11.2009

Revision no.:

1,00

Spray Chrome-Argent

7619-0074

Ensure adequate ventilation.

Use personal protective clothing.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

Methods for cleaning up/taking up

Take up with absorbent material.

After taking up the material dispose according to regulation.

7. Handling and storage**Handling****Advice on safe handling**

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Do not spray on a naked flame or any other incandescent material.

Heating will cause pressure rise with risk of bursting.

Further information on handling

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Storage**Requirements for storage rooms and vessels**

Keep in closed original container.

Keep containers tightly closed in a cool, well-ventilated place.

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Advice on storage compatibility

Incompatible with oxidizing agents.

Do not store with combustible materials.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

Storageclass (VCI):

2 B

8. Exposure controls/personal protection**Exposure limit values****Exposure limits (ACGIH)**

CAS No.	Substance	ppm	mg/m ³	F/ml	Category	Origin
106-97-8	Butane	1000			TWA (8 h)	TLV
		-	-		STEL (15 min)	TLV
		-	-		Peak	TLV
78-93-3	Methyl ethyl ketone (MEK)	200	590		TWA (8 h)	TLV
		300	885		STEL (15 min)	TLV
		-	-		Peak	TLV

Additional advice on limit values

Aliphatic hydrocarbon gases (propane/butane/Alkane C1-C4) have workplace limits of 1000 ppm (TWA-ACGIH).

Protective and hygiene measures

Ensure adequate ventilation, especially in confined areas.

Wash hands before breaks and immediately after handling the product.

Weicon GmbH

Revision date: 27.11.2009

Revision no.:

1,00

Spray Chrome-Argent

7619-0074

At work do not eat, drink, smoke or take drugs.
Take off immediately all contaminated clothing.
Avoid contact with eyes, skin or mucous membrane.

Respiratory protection

Do not inhale gases/vapours/aerosols.

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type AX).

Hand protection

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Butyl latex, 0,7 mm, 480 min., 60 min., i.e. protective glove made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Safety goggles with side protection

Skin protection

Protective clothing

9. Physical and chemical properties**General information**

Physical state:	Aerosol
Colour:	Silver-grey
Odour:	Solvent-like

Important health, safety and environmental information

Test method

Changes in the physical state

Boiling point:	-44 °C
Flash point:	-97 °C

Explosive properties

"The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated."

Lower explosion limits:	1,5 vol. %
Upper explosion limits:	13 vol. %
Vapour pressure: (at 20 °C)	8300 hPa
Density (at 20 °C):	n.d.
Water solubility: (at 20 °C)	Immiscible

Other information

Ignition temperature:	365 °C
-----------------------	--------

10. Stability and reactivity**Conditions to avoid**

Fire or intense heat may cause violent rupture of packages.
Keep away from heat and sources of ignition.
Formation of explosive gas/air mixtures.

Materials to avoid

Strong oxidizing agents

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Weicon GmbH

Revision date: 27.11.2009

Revision no.:

1,00

Spray Chrome-Argent

7619-0074

Additional information

No decomposition if stored and applied as directed.

11. Toxicological information**Acute toxicity**

Description of possible hazards to health effects is based on experience and/or toxicological characteristics of several components.

Harmful by inhalation.

Corrosive and irritant effects

Skin irritation: Non-irritant

Eye irritation : Non-irritant

Sensitizing effects

Sensitization skin : Non-sensitizing

Empirical data on effects on humans

Harmful by inhalation.

Vapours may cause drowsiness and dizziness.

Repeated exposure may cause skin dryness or cracking.

12. Ecological information**Further information**

Do not discharge product unmonitored into the environment.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal considerations**Advice on disposal**

Remove in accordance with local official regulations.

Where possible recycling is preferred to disposal.

If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging

Offer empty spray cans to an established disposal company.

14. Transport information**Canadian TDG****Proper shipping name**

AEROSOLS

UN/ID number: 1950

Hazard classes: 2.1

Packing group: -

Hazard label: 2.1

Land transport (ADR/RID)

UN number: 1950

ADR/RID class: 2

Warning plate

Hazard-no.: -

Hazard label: 2.1



ADR/RID packing group: -

Description of the goods

AEROSOLS

Weicon GmbH

Revision date: 27.11.2009

Revision no.:

1,00

Spray Chrome-Argent

7619-0074

Other applicable information (land transport)

LQ 2: combination packaging: 1 l / 30 kg (total gross mass); trays: 1 l / 20 kg (total gross mass).

Additional label with symbol "fish and tree" according to subsection 5.2.1.8.3. ADR for single packagings and inner packagings with > 5 kg or 5 L, transition period ends 31.12.2010.

Marine transport

UN number:	1950
IMDG code:	2
Marine pollutant:	No
Hazard label:	2.1



IMDG packing group:	-
EmS:	F-D; S-U

Description of the goods

AEROSOLS

Other applicable information (marine transport)

Limited quantities (chapter 3.4): combination packaging: 1 l / 30 kg (total gross mass); trays: 1 l / 20 kg (total gross mass)

Air transport

UN/ID number:	1950
ICAO/IATA-DGR:	2.1
Hazard label:	2.1



ICAO packing group:	-
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

Description of the goods

AEROSOLS FLAMMABLE

15. Regulatory information**Canadian regulations****DSL/NDSL inventory status**

All of the components are listed on the DSL Inventory.

WHMIS classification

WHMIS: A, B5, D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

16. Other information**Other data**

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

Safety Data Sheet according to WHMIS



Weicon GmbH

Revision date: 27.11.2009

Revision no.:

1,00

Spray Chrome-Argent

7619-0074

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)