

Weicon GmbH

Revision date: 01.11.2009

Revision no.:

1,00

Plastic-Metal SF Resin

7619-0033

## **1. Product and Company Identification**

### **Commercial product name**

Plastic-Metal SF Resin

### **Further trade names**

10250-2

### **Chemical characterization ( Mixture )**

Resin for a two-component epoxy adhesive.

### **Company/undertaking identification**

#### **Manufacturer**

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

## **2. Hazards Identification**

### **Route(s) of Entry**

Skin and eye contact, inhalation and ingestion.

### **Signs and Symptoms of Exposure**

CAUTION !

Irritating to eyes and skin.

May cause sensitization by skin contact.

OSHA Hazard Communication: This material is considered hazardous by the OSHA Hazard Communication Standard 29CFR 1910.1200.

Carcinogenicity (NTP): Not listed

Carcinogenicity (IARC): Not listed

Carcinogenicity (OSHA): Not listed

## **3. Composition/Information on Ingredients**

### **Hazardous components**

| CAS No.    | Components   | Quantity |
|------------|--|----------|
| 25068-38-6 | epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin) | 4 - 10 % |
| 14807-96-6 | Talc   | 4 - 10 % |
| 9003-36-5  | Epoxidharz   | 1 - 7 %  |
| 16096-31-4 | 1,6-bis(2,3-epoxypropoxy)hexane  | 1 - 7 %  |

## **4. First Aid Measures**

### **General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

### **After inhalation**

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

Weicon GmbH

Revision date: 01.11.2009

Revision no.:

1,00

Plastic-Metal SF Resin

7619-0033

---

**After contact with skin**

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

**After contact with eyes**

Rinse eyes immediately with large amounts of water for several minutes, especially under the eyelids.

Seek medical treatment by eye specialist.

**After ingestion**

Do not induce vomiting.

Refer to medical treatment.

If swallowed by mistake drink plenty of water and seek medical treatment.

---

**5. Fire Fighting Measures**

**Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

**Unsuitable extinguishing media**

Full water jet

**Special hazards arising from the chemical**

Fire may produce:

Carbon monoxide (CO)

Carbon dioxide

**Protective equipment and precautions for firefighters**

Use breathing apparatus with independent air supply.

**Additional information**

Collect contaminated firefighting water separately, must not be discharged into the drains.

---

**6. Accidental Release Measures**

**Personal precautions**

Remove persons to safety.

Ensure adequate ventilation.

Keep away sources of ignition.

**Environmental precautions**

Clean contaminated surface thoroughly.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

**Methods for cleaning up/taking up**

Take up with absorbent material.

Shovel into suitable container for disposal.

**Additional information**

After taking up the material dispose according to regulation.

---

**7. Handling and Storage**

**Handling**

**Advice on safe handling**

Use only in thoroughly ventilated areas.

Avoid formation of aerosols.

Avoid contact with skin, eyes and clothing.

When using, do not eat, drink or smoke.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

**Storage**

**Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.

Weicon GmbH

Revision date: 01.11.2009

Revision no.:

1,00

Plastic-Metal SF Resin

7619-0033

**Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

Storage temperature between 2°C to 40°C.

**8. Exposure Controls/Personal Protection****Exposure limit values****Exposure limits**

| CAS No.    | Components                                    | ppm | mg/m <sup>3</sup> | fib/cc | Category  | Origin |
|------------|---|-----|-------------------|--------|-----------|--------|
| 14807-96-6 | Talc (containing no asbestos) respirable dust | 706 | mp/m <sup>3</sup> | -      | TWA (8 h) | PEL    |

**Occupational exposure controls**

Ensure adequate ventilation, especially in confined areas.

Do not inhale gases/vapours/aerosols.

**Protective and hygiene measures**

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

**Respiratory protection**

Use suitable breathing apparatus if there is inadequate ventilation.

**Hand protection**

Protective glove (rubber or nitrile)

Protective gloves resistant to chemicals made off natural-rubber latex, Minimum coat thickness 0.6 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove &lt;Lapren 706&gt; made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Eye protection**

Tightly fitting goggles

**Skin protection**

Long sleeved clothing.

**9. Physical and Chemical Properties****Appearance**

Form: Pasty  
 Color: Black  
 Odor: Hardly noticeable

**Important health, safety and environmental information**

pH-Value (at 20 °C): approx. 7 Test method 1:1 in water

**Changes in the physical state**

Flash point: > 200 °C Pensky-Martens CC EN 22719

Vapour pressure: <0,002 hPa  
 (at 20 °C)

Density (at 25 °C): 3.28 g/cm<sup>3</sup>

Water solubility: More or less insoluble  
 (at 20 °C)

Weicon GmbH

Revision date: 01.11.2009

Revision no.:

1,00

Plastic-Metal SF Resin

7619-0033

Viscosity / dynamic:  
(at 50 °C)

190000 - 200000 mPa·s

---

## 10. Stability and Reactivity

### Stability

Stable

### Conditions to avoid

Keep away from heat and sources of ignition.

No decomposition below 200°C.

### Materials to avoid

Reactions with strong acids and alkalis.

Reactions with strong oxidizing agents.

### Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Toxic gases/vapours

### Possibility of Hazardous Reactions

Will not occur

### Additional information

No decomposition if stored and applied as directed.

---

## 11. Toxicological Information

### Acute toxicity

LD50/oral : = &gt;2000 mg/kg Rat

### Corrosive and irritant effects

Skin irritation = Irritant Rabbit

Eye irritation = Irritant Rabbit eye

### Sensitizing effects

Sensitization skin (guinea pig): Sensitizing

---

## 12. Ecological Information

### Further information

Do not discharge product unmonitored into the environment.

Product is not allowed to be discharged into aquatic environment.

---

## 13. Disposal Considerations

### Advice on disposal

Remove in accordance with local official regulations.

Where possible recycling is preferred to disposal.

If recycling is not practicable, dispose of in compliance with local regulations.

Empty containers may be recycled. Otherwise dispose of in accordance with applicable regulations.

### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

---

## 14. Transport Information

### US DOT 49 CFR 172.101

#### Proper shipping name

Not regulated.

#### Land transport (ADR/RID)

#### Description of the goods

No hazardous material as defined by the transport regulations.

Weicon GmbH

Revision date: 01.11.2009

Revision no.:

1,00

Plastic-Metal SF Resin

7619-0033

**Other applicable information**

No hazardous material as defined by the transport regulations.

**15. Regulatory Information****U.S. Regulations****National Inventory TSCA**

All of the components are listed on the TSCA inventory.

**SARA**

To the best of our knowledge this product contains no toxic chemicals subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 372.

**16. Other Information****Hazardous Materials Information Label (HMIS)**

|                  |   |
|------------------|---|
| Health:          | 1 |
| Flammability:    | 1 |
| Physical Hazard: | 0 |

**NFPA Hazard Ratings**

|                |   |
|----------------|---|
| Health:        | 1 |
| Flammability:  | 1 |
| Reactivity:    | 0 |
| Unique Hazard: |   |

**Other data**

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*