

Weicon GmbH

Revision date: 06.10.2011

Revision no.:

1,00

Pneuma-Lub Spray

7691-0276

1. Product and Company Identification

Commercial product name

Pneuma-Lub Spray

Further trade names

11260

Chemical characterization (Mixture)

Mixtures of hydrocarbons with propellant propane/butane

Company/undertaking identification

Manufacturer

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

2. Hazards Identification

Route(s) of Entry

Skin and eye contact, inhalation and ingestion.

Signs and Symptoms of Exposure

DANGER!

Extremely flammable.

Contents under pressure.

OSHA Hazard Communication: This material is considered hazardous by the OSHA Hazard Communication Standard 29CFR 1910.1200.

Carcinogenicity (NTP): Not listed

Carcinogenicity (IARC): Not listed

Carcinogenicity (OSHA): Not listed

3. Composition/Information on Ingredients

Hazardous components

CAS No.	Components	Quantity
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified	25 - 50 %
61641-74-5	Propan/Butan	12 - 35 %
8008-20-6	Kerosine (petroleum), Straight run kerosine	10 - 25 %

4. First Aid Measures

General information

Remove contaminated soaked clothing immediately.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

Weicon GmbH

Revision date: 06.10.2011

Revision no.:

1,00

Pneuma-Lub Spray

7691-0276

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting.

Summon a doctor immediately.

Advice to physician

The following symptoms may occur:

Anaesthetic state

Headache

5. Fire Fighting Measures

Suitable extinguishing media

Foam

Dry powder

Carbon dioxide

Unsuitable extinguishing media

Full water jet

Special hazards arising from the chemical

Fire may produce:

Carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters

Use breathing apparatus with independent air supply.

Additional information

Heating will cause pressure rise with risk of bursting.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. Accidental Release Measures

Personal precautions

Keep away sources of ignition.

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Use personal protective clothing.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

Methods for cleaning up/taking up

Take up with absorbent material.

Shovel into suitable container for disposal.

7. Handling and Storage

Handling

Advice on safe handling

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Do not spray on a naked flame or any other incandescent material.

Heating will cause pressure rise with risk of bursting.

Weicon GmbH

Revision date: 06.10.2011

Revision no.:

1,00

Pneuma-Lub Spray

7691-0276

Further information on handling

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Storage**Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place.

Storage temperature may not exceed 50°C (=122°F).

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

8. Exposure Controls/Personal Protection**Exposure limit values****Exposure limits**

CAS No.	Components	ppm	mg/m ³	fib/cc	Category	Origin
8008-20-6	Kerosine (petroleum), Straight run kerosine				TWA (8 h)	
	Kerosene	100	-		TWA (8 h)	REL

Additional advice on limit values

Aliphatic hydrocarbon gases (propane/butane/Alkane C1-C4) have workplace limits of 1000 ppm (TWA-ACGIH).

Protective and hygiene measures

Ensure adequate ventilation, especially in confined areas.

Wash hands before breaks and immediately after handling the product.

At work do not eat, drink, smoke or take drugs.

Take off immediately all contaminated clothing.

Avoid contact with eyes, skin or mucous membrane.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type AX).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Safety goggles with side protection

Skin protection

Protective clothing

9. Physical and Chemical Properties**Appearance**

Form: Aerosol
 Color: Yellowish
 Odor: Solvent-like

Important health, safety and environmental information

Test method

Changes in the physical state

Boiling point: -44 °C

Weicon GmbH

Revision date: 06.10.2011

Revision no.:

1,00

Pneuma-Lub Spray

7691-0276

Flash point: < 0 °C
Flammability >210

Explosive properties

"The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated."

Lower explosion limits: 0,5 vol. %

Upper explosion limits: 8,5 vol. %

Vapour pressure: 2100 hPa
(at 20 °C)Density (at 20 °C): 0,75 g/cm³Water solubility: Insoluble
(at 20 °C)**Solvent content**

35.9%

Other information

Autoignition temperature

Solid: 29.1%

10. Stability and Reactivity**Stability**

Stable

Conditions to avoid

Fire or intense heat may cause violent rupture of packages.

Keep away from heat and sources of ignition.

Materials to avoid

Strong oxidizing agents

Formation of explosive gas/air mixtures.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Possibility of Hazardous Reactions

Will not occur

Further information

No decomposition if stored and applied as directed.

11. Toxicological Information**Acute toxicity**

Description of possible hazards to health effects is based on experience and/or toxicological characteristics of several components.

Harmful by inhalation.

Vapours may cause drowsiness and dizziness.

Irritation and corrosivity

Skin irritation: Non-irritant

Eye irritation : Non-irritant

Sensitizing effects

Sensitization skin : Non-sensitizing

Empirical data on effects on humans

Harmful by inhalation.

Inhalation of vapours in high concentration can cause narcotic effects.

12. Ecological Information**Further information**

Do not discharge product unmonitored into the environment.

Weicon GmbH

Revision date: 06.10.2011

Revision no.:

1,00

Pneuma-Lub Spray

7691-0276

 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal considerations**Advice on disposal**

Remove in accordance with local official regulations.

Where possible recycling is preferred to disposal.

If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging

Offer empty spray cans to an established disposal company.

14. Transport Information**US DOT 49 CFR 172.101****Proper shipping name**

AEROSOLS

ID Number: 1950

Hazard Class or Division: 2.1

Packing group: -

Label: 2.1

**Marine transport**

UN number: 1950

IMDG code: 2

Marine pollutant: No

Hazard label: 2.1



IMDG packing group: -

EmS: F-D; S-U

Description of the goods

AEROSOLS

Other applicable information

Limited quantities (chapter 3.4): combination packaging: 1 l / 30 kg (total gross mass); trays: 1 l / 20 kg (total gross mass)

Air transport

UN/ID number: 1950

ICAO/IATA-DGR: 2.1

Hazard label: 2.1



ICAO packing group: -

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

Description of the goods

AEROSOLS FLAMMABLE

Weicon GmbH

Revision date: 06.10.2011

Revision no.:

1,00

Pneuma-Lub Spray

7691-0276

15. Regulatory Information

U.S. Regulations

National Inventory TSCA

All of the components are listed on the TSCA inventory.

SARA

To the best of our knowledge this product contains no toxic chemicals subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 372.

State Regulations

This product contains max VOC: 59% (445 g/L)

16. Other Information

Hazardous Materials Information Label (HMIS)

Health: 1

Flammability: 4

Physical Hazard: 0

NFPA Hazard Ratings

Health: 1

Flammability: 4

Reactivity: 0

Unique Hazard:



Other data

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)