





Plast-o-Seal®

**Permanently plastic universal sealant
Solvent free with no unpleasant odour
enables immediate assembly**

- for sealing the smooth treated flanges of machine, gearbox and motor casing flanges
- to improve the performance of both old and new gaskets made from paper, cork, felt etc.
- solvent free – odourless
- remains permanently plastic, before and after assembly
- easy joint dismantling
- economical in use
- very good resistance to most fuels, mineral oils, water, air, coolant mixtures based on methanol and glycol, antifreezes, kerosene, fluorocarbon refrigerants etc.
- max. gap filling capability up to 0,10 mm (without a gasket)
- non-sag can be applied to vertical surfaces
- temperature resistant from -50°C (-58°F) to +200°C (+392°F) briefly up to +250°C (+482°F)
- compensates for manufacturing defects such as scoring and scratches enabling accurate assembly
- allows accurate assembly and construction with low tolerances
- no need to overtighten fixings during assembly
- non corrosive
- neither contains any substances that disturb lacquer wettings (e.g. silicone)
- fluorescent blue colour



Technical Data:

Temperature resistance:	from -50°C (-58°F) to +200°C (+392°F) briefly up to +250°C (+482°F)
Chemical base:	polyester resin
Viscosity:	950.000 up to 1.650.000 mPa·s (pasty)
Colour:	blue (fluorescent)
Gap filling:	max 0,10 mm without gasket
Working temperature:	from +5°C (+41°F) up to +35°C (+95°F)
Specific weight:	1,12 g/cm ³
Shelf life:	24 months at room temperature (approx. +20°C) (+68°F)

Packaging:	90 g	Tube	Art.-No.: 30000090
	120 g	Brush-top can	Art.-No.: 30000120
	300 g	Cartridge	Art.-No.: 30000300

The specifications and recommendations given in this brochure must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.

Jebel Ali Ind Area 3
P.O. Box 118 216
Dubai · U.A.E

Phone +971 4 880 25 05
Fax +971 4 880 25 09
Mobile +971 50 545 99 83
www.weicon.ae
info@weicon.ae

WEICON Inc.

20 Steckle Place · Unit 20
Kitchener · Ontario N2E 2C3
Canada

Phone +1 519 896 5252
Fax +1 519 896 5254
Cell +1 519 590 5168
www.weicon.ca
info@weicon.ca

Distributed by: