



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 17/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 25/Jul/2017

WEICONLOCK AN 305-42

Material number 305420

Page:

1 of 9

1. Product and company identification

Product identifier

Trade name: WEICONLOCK AN 305-42

Relevant identified uses of the substance or mixture and uses advised against

General use: One-component adhesive and sealing agent, anaerobic curing.
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: WEICON Inc.
Street/POB-No.: 20 Steckle Place, Unit 20
Postal Code, city: Kitchener, Ontario N2E 2C3, CA
WWW: www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254
Dept. responsible for information:
Product-Safety-Department
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

Emergency phone number

EMERGENCY CONTACT – Canada (24h): Tel: ++1 866 928 0789 (Toll free)

Transport:

TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: ++1 866 928 0789 (Toll free)

2. Hazards identification

Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: liquid
Form: viscous
Color: brownish
Odor: weak
Classification: Specific Target Organ Toxicity (Single Exposure) 3;
Hazard symbols:



Signal word: **Warning**
Hazard statements: **May cause respiratory irritation.**

Precautionary statements: **Keep out of reach of children.**
Avoid breathing dust/fume/gas/mist/vapors/spray.
Do not get in eyes, on skin, or on clothing.
Use only outdoors or in a well-ventilated area.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICONLOCK AN 305-42

Material number 305420

Revision date: 17/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 25/Jul/2017

Page: 2 of 9

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

Special danger of slipping by leaking/spilling product.

In case of prolonged or frequent exposure skin and eye irritation may occur.

see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterisation: Anaerobic sealants and adhesives

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 81-07-2	1,2-Benzisothiazol-3(2H)-one 1,1-dioxide	1 - 5 %	not applicable
CAS 67762-90-7	Siloxanes and Silicones, di-Methyl, reaction products with silica	1 - 5 %	not applicable
CAS 107-21-1	Ethylene glycol	< 1 %	Acute Toxicity 4 (oral).
CAS 80-15-9	Cumene hydroperoxide	< 1 %	Organic Peroxide E. Acute Toxicity 4 (oral). Acute Toxicity 4 (dermal). Acute Toxicity 3 (inhalative). Skin Corrosion 1B. Specific Target Organ Toxicity (Repeated Exposure) 2. Aquatic toxicity - chronic 2.

4. First aid measures

General information: Take off immediately all contaminated clothing and wash it before reuse.

In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical attention.

Following skin contact: Immediately clean with water and soap followed by thorough rinsing. Change contaminated clothing. Do not peel solidified product off the skin. Seek medical attention.

After eye contact: Keep eye wide open. Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Do not attempt to pull apart bonded eyelid. Subsequently seek the immediate attention of an ophthalmologist.

After swallowing: Never give anything by mouth to an unconscious person. Do not induce vomiting. Give water to drink in small sips. Seek medical attention.

Most important symptoms and effects, both acute and delayed

May cause respiratory irritation. In case of prolonged or frequent exposure skin and eye irritation may occur.

Information to physician

Treat symptomatically.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICONLOCK AN 305-42

Material number 305420

Revision date: 17/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 25/Jul/2017

Page: 3 of 9

5. Fire fighting measures

Flash point/flash point range:

> 100 °C

Auto-ignition temperature: not determined

Suitable extinguishing media:

Water fog, extinguishing powder, alcohol resistant foam, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

Specific hazards arising from the chemical

May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: Carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

You have to dispose of contaminated extinguishing water according to the regulations of the authorities.

6. Accidental release measures

Personal precautions:

Avoid contact with skin, eyes, and clothing.

Do not breathe vapor or spray. Do not breathe dust. Provide adequate ventilation.

Wear appropriate protective equipment. Take off immediately all contaminated or soaked clothing.

Keep away from sources of ignition.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.

Methods for clean-up:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal.

Additional information:

Special danger of slipping by leaking/spilling product.

7. Handling and storage

Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed.

Do not breathe vapor or spray. Avoid contact with skin, eyes, and clothing.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Take off immediately all contaminated clothing and wash it before reuse.

Wear appropriate protective equipment. When handling large quantities, supply emergency spray.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking.

Storage

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.

Keep container dry. Keep only in the original container.

Protect from heat and direct sunlight. storage temperature: < 30 °C.

Store containers in upright position.

Hints on joint storage:

Do not store together with: Strong oxidizing agents, strong reducing agents, strong acids, strong alkalis.

Keep away from food, drink and animal feedingstuffs.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICONLOCK AN 305-42

Material number 305420

Revision date: 17/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 25/Jul/2017

Page: 4 of 9

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
107-21-1	Ethylene glycol	Canada, Alberta: OEL Ceiling	100 mg/m ³
		Canada, BC: OEL Ceiling	100 mg/m ³ Aerosol
		Canada, BC: OEL Ceiling	50 mg/m ³ vapor
		Canada, BC: OEL STEL	20 mg/m ³ particles
		Canada, BC: OEL TWA	10 mg/m ³ particles
		Canada, Québec: Plafond	127 mg/m ³ ; 50 ppm
		USA: ACGIH: STEL	10 mg/m ³ (inhalable fraction Aerosol)
		USA: ACGIH: STEL	50 ppm (vapor)
		USA: ACGIH: TWA	25 ppm (vapor)

Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection Wear suitable protective clothing.
Protective gloves according to OSHA Standard - 29 CFR: 1910.138.
Glove material: Fluororubber (Viton) - Layer thickness: 0.7 mm
Breakthrough time: >480 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.

General hygiene considerations:
Do not breathe vapor or spray. Avoid contact with skin, eyes, and clothing.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Take off immediately all contaminated clothing and wash it before reuse.
When handling large quantities, supply emergency spray.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Form: viscous Color: brownish
Odor:	weak
Odor threshold:	not determined
pH value:	not determined
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	not determined
Flash point/flash point range:	> 100 °C
Evaporation rate:	not determined



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 17/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 25/Jul/2017

WEICONLOCK AN 305-42

Material number 305420

Page: 5 of 9

Flammability:	No data available
Explosion limits:	LEL (Lower Explosion Limit): not determined UEL (Upper Explosive Limit): not determined
Vapor pressure:	not determined
Vapor density:	not determined
Density:	1.1 g/mL
Solubility:	organic solvents: soluble
Water solubility:	at 20 °C: insoluble
Partition coefficient: n-octanol/water:	not determined
Auto-ignition temperature:	not determined
Thermal decomposition:	No data available
Viscosity, dynamic:	approx. 530 mPa*s
Oxidizing characteristics:	not oxidising
Ignition temperature:	not determined

10. Stability and reactivity

Reactivity:	Refer to subsection "Possibility of hazardous reactions".
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Reacts with: Strong oxidizing agents, strong reducing agents, strong acids, strong alkalis, metals and metal salts.
Conditions to avoid:	Keep away from heat sources, sparks and open flames. Protect against direct sunlight.
Incompatible materials:	Strong oxidizing agents, strong reducing agents, strong acids, strong alkalis, metals, metal salts.
Hazardous decomposition products:	Toxic gases/vapours, carbon monoxide and carbon dioxide.
Thermal decomposition:	No data available



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICONLOCK AN 305-42

Material number 305420

Revision date: 17/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 25/Jul/2017

Page: 6 of 9

11. Toxicological information

Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
Acute toxicity (oral): Based on available data, the classification criteria are not met.
ATEmix (calculated): > 5000 mg/kg.
Acute toxicity (dermal): Based on available data, the classification criteria are not met.
ATEmix (calculated): > 5000 mg/kg.
Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
ATEmix (calculated): > 20 mg/L. (vapor)
Skin corrosion/irritation: Lack of data.
Minor irritation effect - does not require labeling.
Eye damage/irritation: Based on available data, the classification criteria are not met.
Minor irritation effect - does not require labeling.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Based on available data, the classification criteria are not met.
May cause sensitisation especially in sensitive humans.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) 3 = May cause respiratory irritation.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

Other information: For carcinogenic effects:
Information about 1,2-Benzisothiazol-3(2H)-one 1,1-dioxide:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed

12. Ecological information

Ecotoxicity

Further details: No data available

Mobility in soil

No data available

Persistence and degradability

Further details: No data available

Additional ecological information

Volatile organic compounds (VOC):

approx. 5 % by weight = 44.5 g/L

General information: Do not allow to enter into ground-water, surface water or drains.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICONLOCK AN 305-42

Material number 305420

Revision date: 17/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 25/Jul/2017

Page: 7 of 9

13. Disposal considerations

Product

Recommendation: Dispose of waste according to applicable legislation.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.
Non-contaminated packages may be recycled.

14. Transport information

USA: Department of Transportation (DOT)

Proper shipping name: Not restricted

Canada: Transportation of Dangerous Goods (TDG)

Shipping name: Not restricted

Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant: no

Air transport (IATA)

Proper shipping name: Not restricted

Further information

No dangerous good in sense of these transport regulations.

15. Regulatory information

National regulations - Canada

No data available



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICONLOCK AN 305-42

Material number 305420

Revision date: 17/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 25/Jul/2017

Page: 8 of 9

National regulations - U.S. Federal Regulations

1,2-Benzisothiazol-3(2H)-one
1,1-dioxide:

TSCA Inventory: listed
TSCA HPVC: not listed
Carcinogen Status:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed
Other Environmental Laws:
CERCLA: RQ 100 lbs.
RCRA Hazardous Wastes: Code U202
SARA Title III Section 313, Toxic Release: Conc. 0.1% /
Threshold Standard

Siloxanes and Silicones, di-Methyl,
reaction products with silica:

TSCA Inventory: listed; UVCB; EPA flags XU
TSCA HPVC: not listed

Ethylene glycol:

TSCA Inventory: listed; EPA flags T
TSCA HPVC: not listed
Clean Air Act:
Hazardous Air Pollutants: Code XO
SOCMI Chemical: yes
Other Environmental Laws:
CERCLA: RQ 5000 lbs.
SARA Title III Section 313, Toxic Release: Conc. 1.0% /
Threshold Standard
NIOSH Recommendations:
Occupational Health Guideline: 0272

Cumene hydroperoxide:

TSCA Inventory: listed
TSCA HPVC: not listed
Clean Air Act:
SOCMI Chemical: yes
Other Environmental Laws:
CERCLA: RQ 10 lbs.
RCRA Hazardous Wastes: Code U096
SARA Title III Section 313, Toxic Release: Conc. 1.0% /
Threshold Standard
OSHA Process Safety Management: Threshold 5000 lbs.

National regulations - U.S. State Regulations


California Proposition 65: Not listed.

16. Other information

Text for labeling:

Contains 1 - 5 % 1,2-Benzisothiazol-3(2H)-one 1,1-dioxide, 1 - 5 % Siloxanes and Silicones, di-Methyl, reaction products with silica, < 1 % Ethylene glycol, < 1 % Cumene hydroperoxide. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:

Health: 1 (Slight)
Fire: 1 (Slight)
Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 1 (Slight)
Flammability: 1 (Slight)
Physical Hazard: 0 (Minimal)
Personal Protection: X = Consult your supervisor

Date of first version:

17/Jul/2017

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICONLOCK AN 305-42

Material number 305420

Revision date: 17/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 25/Jul/2017

Page: 9 of 9

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.