



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 31/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 1/Aug/2017

WEICON UW Resin

Material number 104401

Page: 1 of 9

1. Product and company identification

Product identifier

Trade name: WEICON UW Resin

Relevant identified uses of the substance or mixture and uses advised against

General use: Two-component epoxy resins, resin component.
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: WEICON Inc.
Street/POB-No.: 20 Steckle Place, Unit 20
Postal Code, city: Kitchener, Ontario N2E 2C3, CA
WWW: www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254
Dept. responsible for information:
Product-Safety-Department
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

Emergency phone number

EMERGENCY CONTACT – Canada (24h): Tel: ++1 866 928 0789 (Toll free)

Transport:

TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: ++1 866 928 0789 (Toll free)

2. Hazards identification

Emergency overview

Appearance: Form: pasty
Color: green
Odor: characteristic
Classification: Acute Toxicity 4 (dermal); Acute Toxicity 4 (inhalative); Skin Irritation 2;
Eye Irritation 2A; Sensitization - skin 1; Aquatic toxicity - chronic 2;

Hazard symbols:



Signal word:

Warning

Hazard statements: Harmful in contact with skin.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful if inhaled.
Toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICON UW Resin

Material number 104401

Revision date: 31/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 1/Aug/2017

Page: 2 of 9

Precautionary statements: Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash hands and face thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection.
IF ON SKIN: Wash with plenty of water/soap.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a POISON CENTER/doctor if you feel unwell.
Specific measures (see 'First aid' on this label).
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Wash contaminated clothing before reuse.
Collect spillage.
Dispose of contents/container to hazardous or special waste collection point.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterisation: Formulated bisphenol A-epoxy resin

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 25068-38-6	Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700)	20 - 35 %	Skin Irritation 2. Eye Irritation 2A. Sensitization - skin 1. Aquatic toxicity - chronic 2.
CAS 2425-79-8	1,4-bis(2,3-Epoxypropoxy)butane	3 - 5 %	Acute Toxicity 4 (dermal). Acute Toxicity 4 (inhalative). Skin Irritation 2. Eye Irritation 2A. Sensitization - skin 1. Aquatic toxicity - chronic 3.

Additional information: Information about Talcum:
The maximum workplace exposure limits are, where necessary, listed in section 8.

4. First aid measures

General information: First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse.

In case of inhalation: Move victim to fresh air; if necessary, provide artificial respiration or oxygen. Keep airway open.
Seek medical aid in case of troubles.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICON UW Resin

Material number 104401

Revision date: 31/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 1/Aug/2017

Page: 3 of 9

- Following skin contact: After contact with skin, wash immediately with soap and plenty of water. Take off immediately all contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.
- After swallowing: Do not induce vomiting.
Rinse mouth immediately and drink plenty of water.
Never give anything by mouth to an unconscious person.
Immediately get medical attention.

Most important symptoms and effects, both acute and delayed

Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Dizziness. Abdominal pain. vomiting.

Information to physician

Symptoms of poisoning can only emerge after several hours; medical supervision is therefore essential for at least 48 hours.
Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:

not applicable

Auto-ignition temperature: No data available

Suitable extinguishing media:

Foam, water fog, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet.

Specific hazards arising from the chemical

May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: hydrogen chloride, halogenated compounds, metallic oxides, methanol, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Cool endangered containers with water jetspray.

Do not allow fire water to penetrate into surface or ground water.

Do not inhale explosion and combustion gases.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. Accidental release measures

Personal precautions:

Provide adequate ventilation, and local exhaust as needed. Avoid contact with skin, eyes, and clothing. Do not breathe dust/fume/gas/mist/vapors/spray. Wear respiratory protection when in the presence of vapor, dust, and aerosols.

Wear appropriate protective equipment. Take off immediately all contaminated clothing and wash it before reuse.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.

Methods for clean-up:

Soak up with absorbent materials such as sand, siliceous earth, acid- or universal binder. Store in special closed containers and dispose of according to ordinance.

Dispose of in accordance with the regulations. If necessary notify appropriate authorities.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICON UW Resin

Material number 104401

Revision date: 31/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 1/Aug/2017

Page: 4 of 9

7. Handling and storage

Handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Avoid the formation of aerosol/vapors.

Avoid contact with skin and eyes.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear appropriate protective equipment.

When using do not eat, drink or smoke. Wash hands thoroughly after handling.

Take off immediately all contaminated clothing and wash it before reuse.

Work place should be equipped with a shower and an eye rinsing apparatus.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking.

Usual measures for fire prevention.

Storage

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place. Keep container dry.

Protect from heat and direct sunlight. storage temperature: 5 °C up to 25 °C. Handle and open container with care. Store only in original container.

Hints on joint storage:

Keep away from food, drink and animal feedingstuffs.

Do not store together with acids/alkalies and oxidation agents.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

Type	Limit value
Canada, Alberta: OEL 15 min	10 mg/m ³ Oil mist mineral
Canada, Alberta: OEL 8 hour	5 mg/m ³ Oil mist mineral
Canada, BC: OEL TWA	0.2 mg/m ³ Oil mist mineral
Canada, BC: OEL TWA	1 mg/m ³ Oil mist mineral, (mineral, severely refined)
Canada, Ontario: OEL TWA	5 mg/m ³ Oil mist mineral
Canada, Québec: VECD	10 mg/m ³ Oil mist mineral
Canada, Québec: VEMP	5 mg/m ³ Oil mist mineral
USA: NIOSH: STEL	10 mg/m ³ Oil mist mineral
USA: NIOSH: TWA	5 mg/m ³ Oil mist mineral
USA: OSHA: TWA	5 mg/m ³ Oil mist mineral

Engineering controls

Provide adequate ventilation, and local exhaust as needed.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010

Skin protection: Wear suitable protective clothing.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICON UW Resin

Material number 104401

Revision date: 31/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 1/Aug/2017

Page: 5 of 9

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material: natural rubber.

Layer thickness: ≥ 0.6 mm

Breakthrough time: > 60 min

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. When vapors form, use respiratory protection.

The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.

If higher concentrations occur: Wear self-contained breathing apparatus.

General hygiene considerations:

Avoid contact with skin and eyes.

Take off immediately all contaminated clothing and wash it before reuse.

When using do not eat or drink.

Wash hands before breaks and immediately after handling the product.

Work place should be equipped with a shower and an eye rinsing apparatus.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Form: pasty Color: green
Odor:	characteristic
Odor threshold:	No data available
pH value:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	not applicable
Evaporation rate:	No data available
Flammability:	No data available
Explosion limits:	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Density:	1.44 g/cm ³
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	Information about Reaction product with Bisphenol A-epichlorhydrin epoxy resin (molecular weight = 700) 2.64 - 3.78 log P(o/w) Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.
Auto-ignition temperature:	No data available
Thermal decomposition:	No data available
Viscosity, dynamic:	not applicable
Viscosity, kinematic:	not applicable

10. Stability and reactivity

Reactivity:	Refer to subsection "Possibility of hazardous reactions".
Chemical stability:	Stable under recommended storage conditions.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICON UW Resin

Material number 104401

Revision date: 31/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 1/Aug/2017

Page: 6 of 9

Possibility of hazardous reactions

Reactions with acids, alkalis and oxidizing agents

Conditions to avoid:

Keep away from heat sources, sparks and open flames.
Protect against direct sunlight.
Protect from moisture contamination.

Incompatible materials:

Oxidizing agents, acids, alkalis.

Hazardous decomposition products:

Toxic gases/vapours.
Hydrogen chloride, halogenated compounds, metallic oxides, methanol.

Thermal decomposition:

No data available

11. Toxicological information

Toxicological tests

Toxicological effects:

The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Acute Toxicity 4 (dermal) = Harmful in contact with skin.

ATEmix (calculated): 1000 mg/kg < ATE <= 2000 mg/kg.

Acute toxicity (inhalative): Acute Toxicity 4 (inhalative) = Harmful if inhaled.

ATEmix (calculated): 10 mg/mL < ATE <= 20 mg/L. (vapors)

Skin corrosion/irritation: Skin Irritation 2 = Causes skin irritation.

Eye damage/irritation: Eye Irritation 2A = Causes serious eye irritation.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Sensitization - skin 1 = May cause an allergic skin reaction.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

Other information:

Information about Reaction product with Bisphenol A-epichlorhydrin epoxy resin (molecular weight = 700):

LD50, oral, Rat (OECD 401): > 2000 mg/kg

LD50, dermal, Rabbit (OECD 402): > 2000 mg/kg

LC0, inhalative, Rat (OECD 420): 0,00001 ppm

Information about 1,4-bis(2,3-Epoxypropoxy)butane

LD50, dermal, Rabbit (OECD 402): 1130 mg/kg

General remarks

Handle in accordance with good industrial hygiene and safety practice.

Further hazardous properties cannot be excluded.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

WEICON UW Resin

Material number 104401

Revision date: 31/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 1/Aug/2017

Page: 7 of 9

12. Ecological information

Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.
Information about Reaction product with Bisphenol A-epichlorhydrin epoxy resin (molecular weight = 700):
Algae toxicity:
EC50 *Desmodesmus subspicatus* (green algae): 9.4 mg/L/72h (EPA CFR).
Daphnia toxicity:
EC50 *Daphnia magna* (Big water flea): 1.7 mg/L/48h (OECD 202).
Fish toxicity:
LC50 *Oncorhynchus mykiss*: 1.2 mg/L/96h (OECD 203).
Bacterial toxicity:
IC50 Bacteria, Activated sludge: >100 mg/L/3 h.

Mobility in soil

No data available

Persistence and degradability

Further details: Information about Reaction product with Bisphenol A-epichlorhydrin epoxy resin (molecular weight = 700):
Biodegradation: 5%/28d (OECD 301 F).

Additional ecological information

AOX reference: The product contains organically bound halogen. Thus it may add to the AOX value.
Volatile organic compounds (VOC):
0 % by weight
General information: Do not allow to enter into ground-water, surface water or drains.

13. Disposal considerations

Product

Recommendation: Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 31/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 1/Aug/2017

WEICON UW Resin

Material number 104401

Page: 8 of 9

14. Transport information

USA: Department of Transportation (DOT)

Identification number: UN3082
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700))
Hazard class or Division: 9
Packing Group: III
Labels: 9
Symbols: G
Special provisions: 8, 146, 173, 335, IB3, T4, TP1, TP29
Packaging – Exceptions: 155
Packaging – Non-bulk: 203
Packaging – Bulk: 241
Quantity limitations – Passenger aircraft / rail: No limit
Quantity limitations – Cargo only: No limit
Vessel stowage – Location: A



Canada: Transportation of Dangerous Goods (TDG)

UN Number: UN3082
Shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700))
TDG class: 9
Packing group: III
Special provisions: 16, 99
Explosive limit and limited quantity index: 5 L

Sea transport (IMDG)

UN number: UN 3082
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700))
Class or division, Subsidiary risk: Class 9, Subrisk-III
Packing Group: III
EmS: F-A, S-F
Special provisions: 274, 335, 969
Limited quantities: 5 L
Excepted quantities: E1
Contaminated packaging - Instructions: P001, LP01
Contaminated packaging - Provisions: PP1
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T4
Tank instructions - Provisions: TP2, TP29
Stowage and handling: Category A.
Properties and observations: -
Marine pollutant: yes
Segregation group: none



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 31/Jul/2017

Version: 1

Language: en-CA,US

Date of print: 1/Aug/2017

WEICON UW Resin

Material number 104401

Page: 9 of 9

Air transport (IATA)

UN/ID number: UN 3082
 Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 (Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700))
 Class or division, Subsidiary risk: Class 9
 Packing Group: III
 Hazard label: Miscellaneous
 Excepted Quantity Code: E1
 Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y964 - Max. Net Qty/Pkg. 30 kg G
 Passenger and Cargo Aircraft: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
 Cargo Aircraft only: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
 Special provisions: A97 A158 A197
 Emergency Response Guide-Code (ERG): 9L

15. Regulatory information

National regulations - Canada

No data available


National regulations - U.S. Federal Regulations

Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700): TSCA Inventory: listed; EPA flags XU
 TSCA HPVC: not listed
 1,4-bis(2,3-Epoxypropoxy)butane: TSCA Inventory: listed; EPA flags T
 TSCA HPVC: not listed
 TSCA: listed

16. Other information

Text for labeling: Contains 20 - 35 % Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700), 3 - 5 % 1,4-bis(2,3-Epoxypropoxy)butane. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:

Health: 2 (Moderate)
 Fire: 0 (Minimal)
 Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 2 (Moderate)
 Flammability: 0 (Minimal)
 Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

Date of first version: 31/Jul/2017

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

HEALTH	2
FLAMMABILITY	0
PHYSICAL HAZARD	0
	X

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.