



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 10/Mar/2017

Version: 1

Language: en-CA,US

Date of print: 10/Apr/2017

## Easy-Mix HT 180 Hardener

Material number 106542

Page: 1 of 9

### 1. Product and company identification

#### Product identifier

Trade name: Easy-Mix HT 180 Hardener

#### Relevant identified uses of the substance or mixture and uses advised against

General use: Hardener for 2 component adhesive (epoxy resin).  
Reserved for industrial and professional use.

#### Details of the supplier of the safety data sheet

Company name: WEICON Inc.  
Street/POB-No.: 20 Steckle Place, Unit 20  
Postal Code, city: Kitchener, Ontario N2E 2C3, CA  
WWW: www.weicon.ca  
E-mail: info@weicon.ca  
Telephone: +1-519-896-5252  
Telefax: +1-519-896-5254  
Dept. responsible for information:  
Product-Safety-Department  
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

#### Emergency phone number

**EMERGENCY CONTACT – Canada (24h): Tel: ++1 866 928 0789 (Toll free)**

**Transport:**

**TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: ++1 866 928 0789 (Toll free)**

### 2. Hazards identification

#### Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: liquid  
Form: viscous  
Color: black  
Odor: characteristic  
Classification: Skin Irritation 2; Eye Irritation 2A; Sensitization - skin 1; Aquatic toxicity - chronic 2;

Hazard symbols:



Signal word:

**Warning**

Hazard statements:

Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Easy-Mix HT 180 Hardener

Material number 106542

Revision date: 10/Mar/2017

Version: 1

Language: en-CA,US

Date of print: 10/Apr/2017

Page:

2 of 9

Precautionary statements: Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wash hands and face thoroughly after handling.  
Contaminated work clothing should not be allowed out of the workplace.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection.  
IF ON SKIN: Wash with plenty of water/soap.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Specific treatment (see 'First aid' on this label).  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Take off contaminated clothing.  
Take off contaminated clothing and wash it before reuse.  
Collect spillage.  
Dispose of contents/container to hazardous or special waste collection point.

### Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

### Hazards not otherwise classified

see section 11: Toxicological information

## 3. Composition / Information on ingredients

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 25068-38-6	Reaction product: Bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <=700)	50 - 60 %	Skin Irritation 2. Eye Irritation 2A. Sensitization - skin 1. Aquatic toxicity - chronic 2.
CAS 14228-73-0	1,4-bis[(2,3- epoxypropoxy)methyl] cyclohexane	10 - 15 %	Skin Irritation 2. Eye Irritation 2A. Sensitization - skin 1. Aquatic toxicity - chronic 3.
CAS 2530-83-8	[3-(2,3-Epoxypropoxy) propyl]-trimethoxysilane	1 - 2.5 %	Eye Damage 1. Aquatic toxicity - chronic 3.

Additional information: Contains Silica, vitreous. The maximum workplace exposure limits are, where necessary, listed in section 8.

## 4. First aid measures

General information: First aider: Pay attention to self-protection!  
If medical advice is needed, have product container or label at hand. Take off immediately all contaminated clothing.

In case of inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention.

Following skin contact: Immediately clean with water and soap followed by thorough rinsing. In case of skin reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.  
Subsequently consult an ophthalmologist.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 10/Mar/2017  
Version: 1  
Language: en-CA,US  
Date of print: 10/Apr/2017

## Easy-Mix HT 180 Hardener

Material number 106542

Page: 3 of 9

After swallowing: Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

### Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Vomiting.

### Information to physician

Treat symptomatically.

## 5. Fire fighting measures

Flash point/flash point range:

> 99 °C (c.c.)

Auto-ignition temperature: not self-igniting

Suitable extinguishing media:

Water fog, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet, halones.

### Specific hazards arising from the chemical

May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: Silicon dioxide, methanol, aromatic hydrocarbons, formaldehyde, carbon monoxide and carbon dioxide

Protective equipment and precautions for firefighters:

Use a breathing apparatus independent of the ambient air (isolated apparatus) and a full protection outfit (suit) against chemicals.

Additional information:

Cool exposed containers with water spray.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow water used to extinguish fire to enter drains, ground or waterways.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

## 6. Accidental release measures

Personal precautions:

Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with the substance.

Wear respiratory protection when in the presence of vapor, dust, and aerosols.

If possible, eliminate leakage. Provide adequate ventilation.

Wear appropriate protective equipment. Keep unprotected people away.

Take off contaminated clothing and wash it before reuse.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains.

If necessary notify appropriate authorities.

Methods for clean-up:

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Beware of reignition. Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 10/Mar/2017

Version: 1

Language: en-CA,US

Date of print: 10/Apr/2017

## Easy-Mix HT 180 Hardener

Material number 106542

Page:

4 of 9

## 7. Handling and storage

### Handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.  
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off immediately all contaminated clothing and wash it before reuse. When handling large quantities, supply emergency spray.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking.

### Storage

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.  
Protect from humidity and water. Keep only in the original container.  
Protect from heat and direct sunlight.  
Store containers in upright position.

Hints on joint storage:

Keep away from food, drink and animal feedingstuffs.

Do not store together with: acids, alkalis, oxidizing agents.

Further details:

When handling larger quantities, take precautionary measures against electrostatic charging.

## 8. Exposure controls / personal protection

### Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

See also information in chapter 7, section storage.

### Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010

Skin protection: Wear suitable protective clothing.

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material: Nitrile rubber

Breakthrough time: 60 min

Layer thickness: 0.4

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

General hygiene considerations:

Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

When handling large quantities, supply emergency spray.

### Environmental exposure controls

Do not allow to enter into ground-water, surface water or drains.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Easy-Mix HT 180 Hardener

Material number 106542

Revision date: 10/Mar/2017

Version: 1

Language: en-CA,US

Date of print: 10/Apr/2017

Page: 5 of 9

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Form: viscous Color: black
Odor:	characteristic
Odor threshold:	not determined
pH value:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	> 150 °C
Flash point/flash point range:	> 99 °C (c.c.)
Evaporation rate:	No data available
Flammability:	not applicable
Explosion limits:	LEL (Lower Explosion Limit): not determined UEL (Upper Explosive Limit): not determined
Vapor pressure:	at 20 °C: ≤ 0.1 hPa
Vapor density:	No data available
Density:	at 20 °C: 1.089 g/mL
Water solubility:	immiscible
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	not self-igniting
Thermal decomposition:	No decomposition when used properly.
Viscosity, kinematic:	at 40 °C: ≥ 10000 mm <sup>2</sup> /s
Explosive properties:	Product is not explosive.
Ignition temperature:	not determined

## 10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Reactions with acids, alkalis, oxidizing agents. Reacts with amines.
Conditions to avoid:	Keep away from heat sources, sparks and open flames. Protect against direct sunlight. Protect from humidity and water.
Incompatible materials:	Acids, alkalis, oxidizing agents, fluorine, peroxides, amines.
Hazardous decomposition products:	Toxic gases/vapours. Formaldehyde, methanol, aromatic hydrocarbons, carbon monoxide and carbon dioxide.
Thermal decomposition:	No decomposition when used properly.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Easy-Mix HT 180 Hardener

Material number 106542

Revision date: 10/Mar/2017

Version: 1

Language: en-CA,US

Date of print: 10/Apr/2017

Page: 6 of 9

## 11. Toxicological information

### Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.  
Acute toxicity (oral): Lack of data.  
Acute toxicity (dermal): Lack of data.  
Acute toxicity (inhalative): Lack of data.  
Skin corrosion/irritation: Skin Irritation 2 = Causes skin irritation.  
Eye damage/irritation: Eye Irritation 2A = Causes serious eye irritation.  
Sensitisation to the respiratory tract: Lack of data.  
Skin sensitisation: Sensitization - skin 1 = May cause an allergic skin reaction.  
Germ cell mutagenicity/Genotoxicity: Lack of data.  
Carcinogenicity: Lack of data.  
Reproductive toxicity: Lack of data.  
Effects on or via lactation: Lack of data.  
Specific target organ toxicity (single exposure): Lack of data.  
Specific target organ toxicity (repeated exposure): Lack of data.  
Aspiration hazard: Lack of data.

Other information: Information about Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ ):  
Acute oral toxicity: LD50, Rat: > 2000 mg/kg (OECD 401)  
Acute dermal toxicity: LD50, Rabbit: > 2000 mg/kg (OECD 402)

### General remarks

Further hazardous properties cannot be excluded.

## 12. Ecological information

### Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.  
Information about Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ ):  
Algae toxicity:  
IC50 Pseudokirchneriella subcapitata (green algae): 4.2 mg/L/96h  
Daphnia toxicity:  
EC50 Daphnia magna (Big water flea): 2.8 mg/L/48h (OECD 202)  
NOEC Daphnia magna (Big water flea): 0.3 mg/L/21d (OECD 211)  
Fish toxicity:  
LC50 Oncorhynchus mykiss 2.7 mg/L/96h

Further details: Biodegradability  
Information about Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ ): 5 %/28d (OECD 301 F). Poorly biodegradable.

### Mobility in soil

No data available

### Persistence and degradability

Further details: No data available



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Easy-Mix HT 180 Hardener

Material number 106542

Revision date: 10/Mar/2017  
Version: 1  
Language: en-CA,US  
Date of print: 10/Apr/2017

Page: 7 of 9

### Additional ecological information

General information: Do not allow to enter into ground-water, surface water or drains.

## 13. Disposal considerations

### Product

Recommendation: Dispose of waste according to applicable legislation.  
Do not dispose of with household waste.  
Dispose of as hazardous waste.

### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.  
Handle contaminated packages in the same way as the substance itself.

## 14. Transport information

### USA: Department of Transportation (DOT)

Identification number: UN3082  
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700))  
Hazard class or Division: 9  
Packing Group: III  
Labels: 9  
Symbols: G  
Special provisions: 8, 146, 173, 335, IB3, T4, TP1, TP29  
Packaging – Exceptions: 155  
Packaging – Non-bulk: 203  
Packaging – Bulk: 241  
Quantity limitations – Passenger aircraft / rail: No limit  
Quantity limitations – Cargo only: No limit  
Vessel stowage – Location: A



### Canada: Transportation of Dangerous Goods (TDG)

UN Number: UN3082  
Shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700))  
TDG class: 9  
Packing group: III  
Special provisions: 16, 99  
Explosive limit and limited quantity index: 5 L



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 10/Mar/2017

Version: 1

Language: en-CA,US

Date of print: 10/Apr/2017

## Easy-Mix HT 180 Hardener

Material number 106542

Page:

8 of 9

### Sea transport (IMDG)

UN number: UN 3082  
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700))  
Class or division, Subsidiary risk: Class 9, Subrisk-  
Packing Group: III  
EmS: F-A, S-F  
Special provisions: 274, 335, 969  
Limited quantities: 5 L  
Excepted quantities: E1  
Contaminated packaging - Instructions: P001, LP01  
Contaminated packaging - Provisions: PP1  
IBC - Instructions: IBC03  
IBC - Provisions: -  
Tank instructions - IMO: -  
Tank instructions - UN: T4  
Tank instructions - Provisions: TP2, TP29  
Stowage and handling: Category A.  
Properties and observations: -  
Marine pollutant: yes  
Segregation group: none

### Air transport (IATA)

UN/ID number: UN 3082  
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700))  
Class or division, Subsidiary risk: Class 9  
Packing Group: III  
Hazard label: Miscellaneous  
Excepted Quantity Code: E1  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y964 - Max. Net Qty/Pkg. 30 kg G  
Passenger and Cargo Aircraft: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L  
Cargo Aircraft only: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L  
Special provisions: A97 A158 A197  
Emergency Response Guide-Code (ERG): 9L

## 15. Regulatory information

### National regulations - Canada

No data available

### National regulations - U.S. Federal Regulations

Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700):

TSCA Inventory: listed; EPA flags XU  
TSCA HPVC: not listed

[3-(2,3-Epoxypropoxy)propyl]-trimethoxysilane:

TSCA Inventory: listed; EPA flags T  
TSCA HPVC: not listed





# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 10/Mar/2017

Version: 1

Language: en-CA,US

Date of print: 10/Apr/2017

## Easy-Mix HT 180 Hardener

Material number 106542

Page: 9 of 9

### 16. Other information

Text for labeling:

Contains 50 - 60 % Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ ), 10 - 15 %  
1,4-bis[(2,3-epoxypropoxy)methyl]cyclohexane, 1 - 2.5 %  
[3-(2,3-Epoxypropoxy)propyl]-trimethoxysilane. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:

Health: 2 (Moderate)

Fire: 1 (Slight)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 2 (Moderate)

Flammability: 1 (Slight)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Date of first version:

10/Mar/2017

#### Department issuing data sheet

Contact person:

see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.