



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017
Version: 5
Language: en-CA,US
Date of print: 10/Jan/2017

W44T Turbo-Power-Spray

Material number 112510

Page: 1 of 10

1. Product and company identification

Product identifier

Trade name: W44T Turbo-Power-Spray

Relevant identified uses of the substance or mixture and uses advised against

General use: Technical aerosol.
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: WEICON Inc.
Street/POB-No.: 20 Steckle Place, Unit 20
Postal Code, city: Kitchener, Ontario N2E 2C3, CA
WWW: www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254
Dept. responsible for information:
Product-Safety-Department
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

Emergency phone number

EMERGENCY CONTACT – Canada (24h): Tel: ++1 866 928 0789 (Toll free)

**Transport:
TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: ++1 866 928 0789 (Toll free)**

2. Hazards identification

Emergency overview

Appearance: Form: Aerosol
Color: amber
Odor: characteristic
Classification: Flammable Aerosol 1; Compressed Gas;
Specific Target Organ Toxicity (Single Exposure) 3;

Hazard symbols:



Signal word:

Danger

Hazard statements:

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
May cause drowsiness or dizziness.

Precautionary statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid breathing vapors/spray.
Use only outdoors or in a well-ventilated area.
Call a POISON CENTER/doctor if you feel unwell.
Store locked up.
Protect from sunlight. Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container to hazardous or special waste collection point.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

W44T Turbo-Power-Spray

Material number 112510

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 2 of 10

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

Potentially explosive mixtures may form if adequate ventilation is not provided. Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may have a narcotic effect.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterisation: Preparation of active ingredients with propellant

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	25 - 50 %	Flammable Liquid 3. Specific Target Organ Toxicity (Single Exposure) 3. Aspiration Toxicity 1.
CAS 64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	10 - 25 %	not applicable
CAS 95-63-6	1,2,4-Trimethylbenzene	0.1 - 1 %	Flammable Liquid 3. Acute Toxicity 4 (inhalative). Skin Irritation 2. Eye Irritation 2A. Specific Target Organ Toxicity (Single Exposure) 3. Aquatic toxicity - chronic 2.
CAS 106-97-8	Butane	10 - 25 %	Flammable Gas 1. Compressed Gas.
CAS 74-98-6	Propane	2.5 - 10 %	Flammable Gas 1. Compressed Gas.

4. First aid measures

General information:	Take off immediately all contaminated clothing and wash it before reuse.
In case of inhalation:	Provide fresh air. Seek medical treatment in case of troubles.
Following skin contact:	After contact with skin, wash immediately with soap and plenty of water. Consult a doctor if skin irritation persists.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.
After swallowing:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Immediately get medical attention.

Most important symptoms and effects, both acute and delayed

Lengthy or repeated contact may cause skin irritation.
May cause drowsiness or dizziness.

Information to physician

Treat symptomatically.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017
Version: 5
Language: en-CA,US
Date of print: 10/Jan/2017

W44T Turbo-Power-Spray

Material number 112510

Page: 3 of 10

5. Fire fighting measures

Flash point/flash point range:

-97 °C

Auto-ignition temperature: not self-igniting

Suitable extinguishing media:

Alcohol resistant foam, extinguishing powder, water mist, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

full water jet

Specific hazards arising from the chemical

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

May form dangerous gases and vapours in case of fire.

Carbon monoxide and carbon dioxide.

Potentially explosive vapor/air mixtures may form.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Heating will lead to pressure increase: Danger of bursting and explosion. Cool exposed containers with water spray.

Move undamaged containers from immediate hazard area if it can be done safely.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

6. Accidental release measures

Personal precautions:

Provide adequate ventilation. Do not breathe gas/vapor/spray. Avoid contact with the substance.

Eliminate all ignition sources if safe to do so. Wear appropriate protective equipment.

Keep unprotected people away.

Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains.

In case of release, notify competent authorities. Danger of explosion!

Methods for clean-up:

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Beware of reignition. Thoroughly clean surrounding area.

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

7. Handling and storage

Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed. Provide room air exhaust at ground level.

Do not breathe gas/vapor/spray. Avoid contact with skin and eyes.

Wear appropriate protective equipment. Take off immediately all contaminated clothing and wash it before reuse.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

W44T Turbo-Power-Spray

Material number 112510

Page:

4 of 10

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.

Storage

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Store containers in upright position. Explosion protection required.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Hints on joint storage:

Do not store together with combustible or self-igniting materials or any highly flammable solids.
Keep away from food, drink and animal feedingstuffs.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
95-63-6	1,2,4-Trimethylbenzene	Canada, Alberta: OEL 8 hour	123 mg/m ³ ; 25 ppm
		Canada, BC: OEL TWA	25 ppm
		Canada, Québec: VEMP	123 mg/m ³ ; 25 ppm
		USA: ACGIH: TWA	123 mg/m ³ ; 25 ppm
		USA: NIOSH: TWA	125 mg/m ³ ; 25 ppm
106-97-8	Butane	Canada, Alberta: OEL 8 hour	1000 ppm
		Canada, BC: OEL STEL	750 ppm
		Canada, BC: OEL TWA	600 ppm
		Canada, Ontario: OEL TWA	800 ppm
		Canada, Québec: VEMP	1900 mg/m ³ ; 800 ppm
		USA: ACGIH: TWA	2370 mg/m ³ ; 1000 ppm
		USA: NIOSH: TWA	1900 mg/m ³ ; 800 ppm
74-98-6	Propane	Canada, Alberta: OEL 8 hour	1000 ppm
		Canada, Québec: VEMP	1800 mg/m ³ ; 1000 ppm
		USA: NIOSH: TWA	1800 mg/m ³ ; 1000 ppm
		USA: OSHA: TWA	1800 mg/m ³ ; 1000 ppm

Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Use only explosion-proof equipment.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection

Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection

Flame retardant, antistatic and chemical resistant protective clothing.

Protective gloves according to OSHA Standard - 29 CFR: 1910.138 (Solvent resistant protective gloves).

Glove material: Nitrile rubber

Layer thickness: >=0.5 mm

Breakthrough time: >480 min

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

W44T Turbo-Power-Spray

Material number 112510

Page:

5 of 10

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.

The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

General hygiene considerations:

Use only non-sparking tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Do not breathe gas/vapor/spray. Avoid contact with skin and eyes.

Take off contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Form: Aerosol Color: amber
Odor:	characteristic
Odor threshold:	not determined
pH value:	not determined
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	-44 °C
Flash point/flash point range:	-97 °C
Evaporation rate:	not determined
Flammability:	Extremely flammable aerosol.
Explosion limits:	LEL (Lower Explosion Limit): 0.60 Vol-% UEL (Upper Explosive Limit): 10.90 Vol-%
Vapor pressure:	at 20 °C: 2100 hPa
Vapor density:	not determined
Density:	at 20 °C: 0.715 g/cm ³
Solubility:	not determined
Water solubility:	slightly miscible
Partition coefficient: n-octanol/water:	not determined
Auto-ignition temperature:	not self-igniting
Thermal decomposition:	No decomposition when used properly.
Viscosity, dynamic:	not determined
Viscosity, kinematic:	not determined
Explosive properties:	Product is not explosive. Potentially explosive vapor/air mixtures may form.
Ignition temperature:	270 °C
Solvent content:	67.1 %
Solid content:	7.5 %

10. Stability and reactivity

Reactivity: Extremely flammable aerosol.
Vapors may form explosive mixtures with air.

Chemical stability: Stable under recommended storage conditions.

Possibility of hazardous reactions

Contains gas under pressure; may explode if heated.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

W44T Turbo-Power-Spray

Material number 112510

Page: 6 of 10

- Conditions to avoid: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- Incompatible materials: Do not store together with combustible or self-igniting materials or any highly flammable solids.
- Hazardous decomposition products: May form dangerous gases and vapours in case of fire.
Carbon monoxide and carbon dioxide
- Thermal decomposition: No decomposition when used properly.

11. Toxicological information

Toxicological tests

- Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
- Acute toxicity (oral): Based on available data, the classification criteria are not met.
ATEmix (calculated): > 5000 mg/kg
- Acute toxicity (dermal): Based on available data, the classification criteria are not met.
ATEmix (calculated): > 5000 mg/kg
- Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
ATEmix (calculated): > 5 mg/L
- Skin corrosion/irritation: Lack of data.
- Eye damage/irritation: Lack of data.
- Sensitisation to the respiratory tract: Lack of data.
- Skin sensitisation: Lack of data.
- Germ cell mutagenicity/Genotoxicity: Lack of data.
- Carcinogenicity: Lack of data.
- Reproductive toxicity: Lack of data.
- Effects on or via lactation: Lack of data.
- Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) 3 = May cause drowsiness or dizziness.
- Specific target organ toxicity (repeated exposure): Lack of data.
- Aspiration hazard: Based on available data, the classification criteria are not met.
- Other information: Information about Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:
LD50, Rat, oral: > 5000 mg/kg
LD50, Rabbit, dermal: > 5000 mg/kg
LC50, Rat, inhalative: 4.951 mg/L/4h
Further hazardous properties cannot be excluded.

General remarks

Handle in accordance with good industrial hygiene and safety practice.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

W44T Turbo-Power-Spray

Material number 112510

Page:

7 of 10

12. Ecological information

Ecotoxicity

Aquatic toxicity: Information about Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:
Algae toxicity:
EC50 Pseudokirchneriella subcapitata (green algae): > 1000 mg/L/72h
Daphnia toxicity:
EC50 Daphnia magna (Big water flea): 1000 mg/L/48 h.
Fish toxicity:
LC50 Oncorhynchus mykiss: > 1000 mg/L/96h

Mobility in soil

No data available

Persistence and degradability

Further details: No data available

Additional ecological information

Volatile organic compounds (VOC):

67.11 % by weight = 480 g/L

General information: Do not allow to enter undiluted resp. in large quantities into surface water or into drains.

13. Disposal considerations

Product

Recommendation: Do not pierce or burn, even after use.
Special waste. Dispose of waste according to applicable legislation.
Do not dispose of with household waste.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle empty containers with care.
Incineration may cause explosion. Empty carefully and completely, if possible.

14. Transport information

USA: Department of Transportation (DOT)

Identification number: UN1950
Proper shipping name: UN 1950, AEROSOLS
Hazard class or Division: 2.1
Labels: 2.1
Special provisions: N82
Packaging – Exceptions: 306
Packaging – Non-bulk: None
Packaging – Bulk: None
Quantity limitations – Passenger aircraft / rail: 75 kg
Quantity limitations – Cargo only: 150 kg
Vessel stowage – Location: A
Vessel stowage – Other: 25, 87, 126





SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

W44T Turbo-Power-Spray

Material number 112510

Page: 8 of 10

Canada: Transportation of Dangerous Goods (TDG)

UN Number: UN1950
Shipping name: UN 1950, AEROSOLS
TDG class: 2.1
Special provisions: 80, 107
Explosive limit and limited quantity index: 1 L
Passenger carrying road or rail index: 75 L

Sea transport (IMDG)

UN number: UN 1950
Proper shipping name: UN 1950, AEROSOLS
Class or division, Subsidiary risk: Class 2.1, Subrisk-
Packing Group: -
EmS: F-D, S-U
Special provisions: 63, 190, 277, 327, 344, 381,959
Limited quantities: 1000 mL
Excepted quantities: E0
Contaminated packaging - Instructions: P207, LP200
Contaminated packaging - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Marine pollutant: no
Segregation group: none

Air transport (IATA)

UN/ID number: UN 1950
Proper shipping name: UN 1950, AEROSOLS, flammable
Class or division, Subsidiary risk: Class 2.1
Hazard label: Flamm. gas
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special provisions: A145 A167 A802
Emergency Response Guide-Code (ERG): 10L

15. Regulatory information

National regulations - Canada

No data available



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

W44T Turbo-Power-Spray

Material number 112510

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 9 of 10

National regulations - U.S. Federal Regulations

Hydrocarbons, C9-C11, n-alkanes,
isoalkanes, cyclics, <2% aromatics:

TSCA Inventory: listed; UVCB
TSCA HPVC: not listed

Distillates (petroleum), solvent-dewaxed
heavy paraffinic:

TSCA Inventory: listed; UVCB
TSCA HPVC: not listed

1,2,4-Trimethylbenzene:

TSCA Inventory: listed
TSCA HPVC: not listed

Other Environmental Laws:

SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold
Standard

NIOSH Recommendations:

Occupational Health Guideline: 0638

Butane:

TSCA Inventory: listed
TSCA HPVC: not listed

Clean Air Act:

Accidental Release Prevention: Threshold 10000 lbs. / Basis for
listing = f

NIOSH Recommendations:

Occupational Health Guideline: 0068*

Propane:

TSCA Inventory: listed
TSCA HPVC: not listed

Clean Air Act:

Accidental Release Prevention: Threshold 10000 lbs. / Basis for
listing = f

NIOSH Recommendations:

Occupational Health Guideline: 0524



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

W44T Turbo-Power-Spray

Material number 112510

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 10 of 10

National regulations - U.S. State Regulations

1,2,4-Trimethylbenzene: California Proposition 65 code: not listed
 Delaware Air Quality Management List:
 DRQ: 100 - RQ State: State requirement differs from Federal
 Maine Hazardous Air Pollutants:
 Me 2005: HAP - Hap Rpt: 1000
 Massachusetts Haz. Substance codes: F7 F9
 New Jersey RTK Hazardous Substance:
 DOT: 1263 - Sub No.: 2716 - TPQ: -
 Pennsylvania Haz. Substance code: E

Butane: Delaware Air Quality Management List:
 DRQ: F 1000** - RQ State: State requirements differs from Federal
 Massachusetts Haz. Substance codes: 4,5,6
 Minnesota Haz. Substance:
 Codes: A - Ratings: - - Status: Title III
 New Jersey RTK Hazardous Substance:
 DOT: 1011 - Sub No.: 0273 - TPQ: -
 Pennsylvania Haz. Substance code: -
 Washington Air Contaminant:
 TWA: 800 ppm - 1900 mg

Propane: California Proposition 65 code: -
 Delaware Air Quality Management List:
 DRQ: F 1000** - RQ State: State requirements differs from Federal
 Massachusetts Haz. Substance codes: 2,4,5,6
 Minnesota Haz. Substance:
 Codes: AP - Ratings: - - Status: Title III
 New Jersey RTK Hazardous Substance:
 DOT: 1978 - Sub No.: 1594 - TPQ: -
 Pennsylvania Haz. Substance code: -
 Washington Air Contaminant:
 TWA: 1000 ppm - 1800 mg

16. Other information

Text for labeling: Contains 25 - 50 % Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, 10 - 25 % Distillates (petroleum), solvent-dewaxed heavy paraffinic, 0.1 - 1 % 1,2,4-Trimethylbenzene, 10 - 25 % Butane, 2.5 - 10 % Propane. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:
 Health: 2 (Moderate)
 Fire: 4 (Severe)
 Reactivity: 0 (Minimal)

HMIS Version III Rating:
 Health: 2 (Moderate)
 Flammability: 4 (Severe)
 Physical Hazard: 0 (Minimal)
 Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	0
	X

Reason of change: ADR/RID 2017, IMDG 2017

Date of first version: 25/Nov/2015

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.