



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: May/24/2018

Version: 4

Language: en-US

Date of print: May/24/2018

AT-44-Multi-Oil

Material number 152500

Page:

1 of 11

1. Product and company identification

Product identifier

Trade name: AT-44-Multi-Oil

Relevant identified uses of the substance or mixture and uses advised against

General use: Active ingredients, liquid.
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: WEICON Inc.
Street/POB-No.: 20 Steckle Place, Unit 20
Postal Code, city: Kitchener, Ontario N2E 2C3, CA
WWW: www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254
Dept. responsible for information:
Product-Safety-Department
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

Emergency phone number

EMERGENCY CONTACT – USA (24h): Tel: +1 202 464 2554

Transport:

TRANSPORT EMERGENCY CONTACT - USA (24h): Tel: +1 202 464 2554

2. Hazards identification

Emergency overview

Appearance: Physical state at 68 °F and 101.3 kPa: liquid
Color: varying
Odor: characteristic
Classification: Flammable Liquid - Category 3; Specific Target Organ Toxicity (Single Exposure) - Category 3; Aspiration Toxicity - Category 1;

Hazard symbols:



Signal word:

Danger

Hazard statements:

Flammable liquid and vapor.
May be fatal if swallowed and enters airways.
May cause drowsiness or dizziness.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: May/24/2018

Version: 4

Language: en-US

Date of print: May/24/2018

AT-44-Multi-Oil

Material number 152500

Page:

2 of 11

Precautionary statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/or shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.
Do NOT induce vomiting.
In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

Special danger of slipping by leaking/spilling product. Repeated exposure may cause skin dryness or cracking. Potentially explosive mixtures may form if adequate ventilation is not provided.

Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may have a narcotic effect.

see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterization: Mixture of hydrocarbons, additives and solvents



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: May/24/2018

Version: 4

Language: en-US

Date of print: May/24/2018

AT-44-Multi-Oil

Material number 152500

Page:

3 of 11

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	25 - 50 %	Aspiration Toxicity - Category 1.
CAS 64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	10 - 25 %	Flammable Liquid - Category 3. Specific Target Organ Toxicity (Single Exposure) - Category 3. Aspiration Toxicity - Category 1.
CAS 95-63-6	1,2,4-Trimethylbenzene	0.1 - 1 %	Flammable Liquid - Category 3. Acute Toxicity - inhalative - Category 4. Skin Irritation - Category 2. Eye Irritation - Category 2A. Specific Target Organ Toxicity (Single Exposure) - Category 3. Aquatic toxicity - chronic - Category 2.

4. First aid measures

- In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing. Keep airway open. If breathing becomes irregular or ceases, apply rescue breathing or artificial respiration immediately, where required supply oxygen. Consult physician immediately.
- Following skin contact: Immediately clean with water and soap followed by thorough rinsing. Take off contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Keep eye wide open. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.
- After swallowing: Rinse mouth with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Aspiration hazard: in case of swallowing or vomiting danger of penetration into the lungs. Seek medical aid in case of troubles.

Most important symptoms/effects, acute and delayed

May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may have a narcotic effect.

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:

96.8 °F

Auto-ignition temperature: No data available

Suitable extinguishing media:

Water spray jet, alcohol resistant foam, dry chemical powder, carbon dioxide.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: May/24/2018

Version: 4

Language: en-US

Date of print: May/24/2018

AT-44-Multi-Oil

Material number 152500

Page:

4 of 11

Extinguishing media which must not be used for safety reasons:

Full water jet

Specific hazards arising from the chemical

Flammable liquid and vapor. May form dangerous gases and vapours in case of fire. In case of fire may be liberated: Carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Heating will lead to pressure increase: Danger of bursting and explosion. Cool exposed containers with water spray.

Move undamaged containers from immediate hazard area if it can be done safely.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

6. Accidental release measures

Personal precautions:

Avoid contact with skin, eyes, and clothing.

Do not breathe fume/gas/mist/vapors/spray. Eliminate all ignition sources if safe to do so.

Provide adequate ventilation.

Wear appropriate protective equipment. Keep unprotected people away. Take off contaminated clothing and wash it before reuse.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains. Danger of explosion!

In case of release, notify competent authorities.

Methods for clean-up:

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Beware of reignition. Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

Special danger of slipping by leaking/spilling product.

7. Handling and storage

Handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.

Wear appropriate protective equipment. Do not breathe fume/gas/mist/vapors/spray.

Avoid contact with skin, eyes, and clothing.

Take off contaminated clothing and wash it before reuse. Guarantee sufficient ventilation

during and after use, in order to prevent vapour accumulation. Avoid the formation of aerosol.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Use only explosion-protected equipment/instruments. Do not weld.

In partially filled containers explosive mixtures may form.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: May/24/2018

Version: 4

Language: en-US

Date of print: May/24/2018

AT-44-Multi-Oil

Material number 152500

Page:

5 of 11

Storage

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place.
Protect from moisture contamination. Protect from frost, heat and sunlight. Keep only in the original container. Explosion protection required.

Hints on joint storage: Do not store together with combustible or self-igniting materials or any highly flammable solids. Keep away from food, drink and animal feedingstuffs.

Further details: Do not allow the product to enter the ground.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
95-63-6	1,2,4-Trimethylbenzene	USA: ACGIH: TWA	123 mg/m ³ ; 25 ppm
		USA: NIOSH: TWA	125 mg/m ³ ; 25 ppm

Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Explosion protection required.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Flame retardant, antistatic and chemical resistant protective clothing.
Protective gloves according to OSHA Standard - 29 CFR: 1910.138.
Glove material: Nitrile rubber
Layer thickness: >0.5 mm
Breakthrough time: >480 min
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

General hygiene considerations:

Use only non-sparking tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Do not breathe vapor or spray. Avoid contact with skin and eyes.

Take off contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance: Physical state at 68 °F and 101.3 kPa: liquid
Color: varying



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: May/24/2018

Version: 4

Language: en-US

Date of print: May/24/2018

AT-44-Multi-Oil

Material number 152500

Page:

6 of 11

Odor:	characteristic
Odor threshold:	not determined
pH value:	not determined
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	323.6 °F
Flash point/flash point range:	96.8 °F
Evaporation rate:	not determined
Flammability:	not applicable
Explosion limits:	LEL (Lower Explosion Limit): 0.50 Vol-% UEL (Upper Explosive Limit): 7.00 Vol-%
Vapor pressure:	at 68 °F: 1 hPa
Vapor density:	No data available
Density:	at 68 °F: 0.89 g/mL
Water solubility:	not/slightly miscible
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Thermal decomposition:	No data available
Viscosity, kinematic:	not determined
Explosive properties:	Product is not explosive. Vapors may form explosive mixtures with air.
Ignition temperature:	> 392 °F
Solvent content:	47 %
Solid content:	9.8 %

10. Stability and reactivity

Reactivity:	Flammable liquid and vapor. Vapors may form explosive mixtures with air.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Heating will lead to pressure increase: Danger of bursting and explosion.
Conditions to avoid:	Keep away from heat sources, sparks and open flames. Protect against direct sunlight.
Incompatible materials:	No data available
Hazardous decomposition products:	May form dangerous gases and vapours in case of fire. In case of fire may be liberated: Carbon monoxide and carbon dioxide.
Thermal decomposition:	No data available



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: May/24/2018

Version: 4

Language: en-US

Date of print: May/24/2018

AT-44-Multi-Oil

Material number 152500

Page:

7 of 11

11. Toxicological information

Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

ATEmix (calculated): ATE > 20 mg/L. (vapor)

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) - Category 3 = May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: Aspiration Toxicity -

Category 1 = May be fatal if swallowed and enters airways.

Other information:

Information about Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Oral LD50 Rat: > 5000 mg/kg bw (OECD 423)

Dermal LD50 Rabbit: > 2000 mg/kg (OECD 402)

Inhalative LC50 Rat: 4951 mg/m³ (OECD 403)

Information about Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Oral LD50 Rat: > 5000 mg/kg bw (OECD 420)

Dermal LD50 Rabbit: > 5000 mg/kg (OECD 402)

Inhalative LC50 Rat: > 5000 mg/m³/8h (OECD 403)



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: May/24/2018

Version: 4

Language: en-US

Date of print: May/24/2018

AT-44-Multi-Oil

Material number 152500

Page:

8 of 11

12. Ecological information

Ecotoxicity

Aquatic toxicity: Information about Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Algae toxicity:

EL50 Pseudokirchneriella subcapitata (green algae): > 1000 mg/L/72h (OECD 201).

Daphnia toxicity:

LL50 Daphnia magna (Big water flea): 1000 mg/L/48h (OECD 202).

Fish toxicity:

LL50 Oncorhynchus mykiss: > 1000 mg/L/96h (OECD 203).

Information about Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Algae toxicity:

EL50 Pseudokirchneriella subcapitata (green algae): > 1000 mg/L/72h (OECD 201).

Daphnia toxicity:

LL50 Daphnia magna (Big water flea): 1000 mg/L/48h (OECD 202).

Fish toxicity:

LL50 Oncorhynchus mykiss: > 1000 mg/L/96h (OECD 203).

Further details:

Biodegradation:

Information about Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:
80% (OECD 301F) Product is biodegradable.

Information about Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2%
aromatics Biodegradation: 68 % (OECD 301F). Product is biodegradable.

Mobility in soil

No data available

Persistence and degradability

Further details:

No data available

Additional ecological information

Volatile organic compounds (VOC):

48.66 % by weight = 433.5 g/L

General information:

Do not allow to enter into ground-water, surface water or drains.

13. Disposal considerations

Product

Recommendation:

Dispose of waste according to applicable legislation.

Contaminated packaging

Recommendation:

Dispose of waste according to applicable legislation.

Non-contaminated packages may be recycled.

Handle empty containers with care. Incineration may cause explosion.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: May/24/2018

Version: 4

Language: en-US

Date of print: May/24/2018

AT-44-Multi-Oil

Material number 152500

Page:

9 of 11

14. Transport information

USA: Department of Transportation (DOT)

Identification number: UN1993
Proper shipping name: UN 1993, UN 1993, flammable liquids, n.o.s.
(Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics), solution
Hazard class or Division: 3
Packing Group: III
Labels: 3
Symbols: G
Special provisions: B1, B52, IB3, T4, TP1, TP29
Packaging – Exceptions: 150
Packaging – Non-bulk: 203
Packaging – Bulk: 242
Quantity limitations – Passenger aircraft / rail: 60 L
Quantity limitations – Cargo only: 220 L
Vessel stowage – Location: A



Sea transport (IMDG)

UN number: UN 1993
Proper shipping name: UN 1993, FLAMMABLE LIQUID, N.O.S.
(Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics), solution
Class or division, Subsidiary risk: Class 3, Subrisk -
Packing Group: III
EmS: F-E, S-E
Special provisions: 223, 274, 955
Limited quantities: 5 L
Excepted quantities: E1
Contaminated packaging - Instructions: P001, LP01
Contaminated packaging - Provisions: -
IBC - Instructions: IBC03
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T4
Tank instructions - Provisions: TP1, TP29
Stowage and handling: Category A.
Properties and observations: -
Marine pollutant: no
Segregation group: none



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: May/24/2018

Version: 4

Language: en-US

Date of print: May/24/2018

AT-44-Multi-Oil

Material number 152500

Page: 10 of 11

Air transport (IATA)

UN/ID number: UN 1993
Proper shipping name: UN 1993, FLAMMABLE LIQUID, N.O.S.
(Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics;
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics),
solution
Class or division, Subsidiary risk: Class 3
Packing Group: III
Hazard label: Flamm. liquid
Excepted Quantity Code: E1
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L
Passenger and Cargo Aircraft: Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L
Cargo Aircraft only: Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L
Special provisions: A3
Emergency Response Guide-Code (ERG): 3L

15. Regulatory information

National regulations - U.S. Federal Regulations

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics: TSCA Inventory: listed; UVCB
TSCA HPVC: not listed
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics: TSCA Inventory: listed; EPA flags P
TSCA HPVC: not listed
1,2,4-Trimethylbenzene: TSCA Inventory: listed
TSCA HPVC: not listed
Other Environmental Laws:
SARA Title III Section 313, Toxic Release:
Conc. 1.0% / Threshold Standard
NIOSH Recommendations:
Occupational Health Guideline: 0638

National regulations - U.S. State Regulations

1,2,4-Trimethylbenzene: California Proposition 65 code: not listed
Delaware Air Quality Management List:
DRQ: 100 - RQ State: State requirement differs from
Federal
Maine Hazardous Air Pollutants:
Me 2005: HAP - Hap Rpt: 1000
Massachusetts Haz. Substance codes: F7 F9
New Jersey RTK Hazardous Substance:
DOT: 1263 - Sub No.: 2716 - TPQ: -
Pennsylvania Haz. Substance code: E

National regulations - Great Britain

Hazchem-Code: •3Y

16. Other information

Text for labeling: Contains 25 - 50 % Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics, 10 - 25 % Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, 0.1 - 1 % 1,2,4-Trimethylbenzene. Safety data sheet available on request.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: May/24/2018
Version: 4
Language: en-US
Date of print: May/24/2018

AT-44-Multi-Oil

Material number 152500

Page: 11 of 11

Hazard rating systems:



NFPA Hazard Rating:

Health: 4 (Severe)

Fire: 3 (Serious)

Reactivity: 1 (Slight)

HMIS Version III Rating:

Health: 4 (Severe)

Flammability: 3 (Serious)

Physical Hazard: 1 (Slight)

Personal Protection: X = Consult your supervisor

HEALTH	4
FLAMMABILITY	3
PHYSICAL HAZARD	1
	X

Reason of change: ADR/RID 2017

Date of first version: Mar/1/2016

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.