



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

## Rust-Schock, Spray

Material number 111510

Page: 1 of 11

### 1. Product and company identification

#### Product identifier

Trade name: Rust-Schock, Spray

#### Relevant identified uses of the substance or mixture and uses advised against

General use: Technical aerosol

#### Details of the supplier of the safety data sheet

Company name: WEICON Inc.

Street/POB-No.: 20 Steckle Place, Unit 20

Postal Code, city: Kitchener, Ontario N2E 2C3, CA

WWW: www.weicon.ca

E-mail: info@weicon.ca

Telephone: +1-519-896-5252

Telefax: +1-519-896-5254

Dept. responsible for information:

Product-Safety-Department

Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

#### Emergency phone number

**EMERGENCY CONTACT – Canada (24h): Tel: ++1 866 928 0789 (Toll free)**

**Transport:**

**TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: ++1 866 928 0789 (Toll free)**

### 2. Hazards identification

#### Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: liquid

Form: Aerosol

Odor: characteristic

Classification: Aerosol 1; Eye Damage 1;

Hazard symbols:



Signal word: **Danger**

Hazard statements: Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye damage.

Precautionary statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Rust-Schock, Spray

Material number 111510

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 2 of 11

### Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

### Hazards not otherwise classified

Exposure to temperatures exceeding 50 °C will increase pressure: resulting in danger of bursting or explosion.

Potentially explosive mixtures may form if adequate ventilation is not provided.

Inhaling can lead to irritations of the respiratory tract and mucous membrane.

Higher doses may have a narcotic effect. Danger of metabolic acidosis.

see section 11: Toxicological information

## 3. Composition / Information on ingredients

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 64-17-5	Ethanol	50 - 70 %	Flammable Liquid 2.
CAS 71-23-8	Propan-1-ol	< 20 %	Flammable Liquid 2. Eye Damage 1. Specific Target Organ Toxicity (Single Exposure) 3.
CAS 106-97-8	n-Butane, pure	10 - 20 %	Flammable Gas 1. Compressed Gas.
CAS 74-98-6	Propane	1 - 10 %	Flammable Gas 1. Compressed Gas.
CAS 75-28-5	Isobutane, pure	1 - 10 %	Flammable Gas 1. Compressed Gas.

## 4. First aid measures

In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical aid in case of troubles.

Following skin contact: Wash with generous amount of water and soap. Take off contaminated clothing. Consult a doctor if skin irritation persists.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.

After swallowing: Do not induce vomiting. Never give anything by mouth to an unconscious person. Seek medical treatment in case of troubles.

### Most important symptoms and effects, both acute and delayed

Causes serious eye damage.

### Information to physician

Treat symptomatically.

## 5. Fire fighting measures

Flash point/flash point range:

-60 °C

Auto-ignition temperature: not self-igniting

Suitable extinguishing media:

Atomized water, alcohol resistant foam, extinguishing powder, carbon dioxide

Extinguishing media which must not be used for safety reasons:

High power water jet



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Rust-Schock, Spray

Material number 111510

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 3 of 11

### Specific hazards arising from the chemical

Extremely flammable aerosol. Vapors form potentially explosive mixtures with air, which are heavier than air. Air-Vapor mixture may travel great distances at floor level and lead to backflash when exposed to an ignition source.

May form dangerous gases and vapours in case of fire. Furthermore, there may develop: Carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing. Do not breathe fumes.

Additional information:

Heating will lead to pressure increase: Danger of bursting and explosion.

Cool endangered containers with water spray and, if possible, remove from danger zone.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

## 6. Accidental release measures

Personal precautions:

Eliminate all ignition sources if safe to do so.

Provide adequate ventilation. Do not breathe vapor or spray.

Wear appropriate protective equipment. Avoid contact with skin and eyes. Change contaminated clothing.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains. In case of release, notify competent authorities.

Methods for clean-up:

Take up with non-flammable, liquid binding material (e.g. sand/earth/diatomaceous earth/vermiculit) and perform disposal according to instructions.

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

## 7. Handling and storage

### Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed.

Use only in well-ventilated areas. Do not breathe vapor or spray.

Wear appropriate protective equipment. Avoid contact with skin and eyes. Change contaminated clothing.

Precautions against fire and explosion:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material.

Use only non-sparking tools. Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

### Storage

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

Keep only in the original container.

Hints on joint storage:

Keep away from food, drink and animal feedingstuffs.

Do not store together with combustible or self-igniting materials or any highly flammable solids.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Rust-Schock, Spray

Material number 111510

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 4 of 11

### 8. Exposure controls / personal protection

#### Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
64-17-5	Ethanol	Canada, Alberta: OEL 8 hour	1880 mg/m <sup>3</sup> ; 1000 ppm
		Canada, BC: OEL STEL	1000 ppm
		Canada, Québec: VEMP	1880 mg/m <sup>3</sup> ; 1000 ppm
		USA: ACGIH: STEL	1000 ppm (A3)
		USA: NIOSH: TWA	1900 mg/m <sup>3</sup> ; 1000 ppm
		USA: OSHA: TWA	1900 mg/m <sup>3</sup> ; 1000 ppm
71-23-8	Propan-1-ol	Canada, Alberta: OEL 15 min	984 mg/m <sup>3</sup> ; 400 ppm
		Canada, Alberta: OEL 8 hour	492 mg/m <sup>3</sup> ; 200 ppm
		Canada, BC: OEL TWA	100 ppm
		Canada, Québec: VECD	614 mg/m <sup>3</sup> ; 250 ppm
		Canada, Québec: VEMP	492 mg/m <sup>3</sup> ; 200 ppm
		USA: ACGIH: TWA	246 mg/m <sup>3</sup> ; 100 ppm
		USA: NIOSH: STEL	625 mg/m <sup>3</sup> ; 250 ppm (May be absorbed through the skin.)
		USA: NIOSH: TWA	500 mg/m <sup>3</sup> ; 200 ppm (May be absorbed through the skin.)
106-97-8	n-Butane, pure	USA: OSHA: TWA	500 mg/m <sup>3</sup> ; 200 ppm
		Canada, Alberta: OEL 8 hour	1000 ppm
		Canada, BC: OEL STEL	750 ppm
		Canada, BC: OEL TWA	600 ppm
		Canada, Ontario: OEL TWA	800 ppm
		Canada, Québec: VEMP	1900 mg/m <sup>3</sup> ; 800 ppm
74-98-6	Propane	USA: ACGIH: TWA	2370 mg/m <sup>3</sup> ; 1000 ppm
		USA: NIOSH: TWA	1900 mg/m <sup>3</sup> ; 800 ppm
		USA: OSHA: TWA	1800 mg/m <sup>3</sup> ; 1000 ppm
		USA: OSHA: TWA	1800 mg/m <sup>3</sup> ; 1000 ppm
75-28-5	Isobutane, pure	Canada, Ontario: OEL TWA	800 ppm
		USA: ACGIH: TWA	2370 mg/m <sup>3</sup> ; 1000 ppm
		USA: NIOSH: TWA	1900 mg/m <sup>3</sup> ; 800 ppm

#### Engineering controls

Provide good ventilation and/or an exhaust system in the work area.

See also information in chapter 7, section storage.

#### Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Wear suitable protective clothing.

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material: Butyl caoutchouc (butyl rubber) - Layer thickness: >= 0.7 mm

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

## Rust-Schock, Spray

Material number 111510

Page:

5 of 11

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.  
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.  
If higher concentrations occur: Wear self-contained breathing apparatus.

General hygiene considerations:

Keep away from heat sources, sparks and open flames.  
Do not breathe vapor or spray. Use only in well-ventilated areas.  
Change contaminated clothing. Avoid contact with skin and eyes.  
When using do not eat, drink or smoke.  
Wash hands before breaks and after work.  
Work place should be equipped with a shower and an eye rinsing apparatus.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Form: Aerosol
Odor:	characteristic
Odor threshold:	No data available
pH value:	not applicable
Melting point/freezing point:	no data available
Initial boiling point and boiling range:	not applicable
Flash point/flash point range:	-60 °C
Evaporation rate:	No data available
Flammability:	Extremely flammable aerosol.
Explosion limits:	LEL (Lower Explosion Limit): 1.50 Vol-% UEL (Upper Explosive Limit): 15.00 Vol-%
Vapor pressure:	at 20 °C: 2700 hPa
Vapor density:	No data available
Density:	at 20 °C: 0.71 g/cm <sup>3</sup>
Water solubility:	miscible
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	not self-igniting
Thermal decomposition:	No data available
Viscosity, dynamic:	no data available
Viscosity, kinematic:	no data available
Explosive properties:	Product is not explosive. Potentially explosive vapor/air mixtures may form.
Ignition temperature:	360 °C

## 10. Stability and reactivity

Reactivity:	Extremely flammable aerosol. Vapors may form explosive mixtures with air.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Container under pressure. Heating will lead to pressure increase: Danger of bursting and explosion.
Conditions to avoid:	Keep away from heat sources, sparks and open flames. Protect from direct exposure to sunlight and temperatures exceeding 50 °C.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Rust-Schock, Spray

Material number 111510

Revision date: 2/Jan/2017  
Version: 3  
Language: en-CA,US  
Date of print: 10/Jan/2017

Page: 6 of 11

Incompatible materials: Do not store together with combustible or self-igniting materials or any highly flammable solids.

Hazardous decomposition products: In case of fire may be liberated: Carbon monoxide and carbon dioxide.

Thermal decomposition: No data available

## 11. Toxicological information

### Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Lack of data.

Eye damage/irritation: Eye Damage 1 = Causes serious eye damage.

Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

### Symptoms

In case of inhalation:  
Inhaling can lead to irritations of the respiratory tract and mucous membrane.  
Higher doses may have a narcotic effect.  
After contact with skin: Information about Ethanol:  
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

## 12. Ecological information

### Ecotoxicity

Further details: No data available

### Mobility in soil

No data available

### Persistence and degradability

Further details: No data available

### Additional ecological information

General information: Do not allow to enter into ground-water, surface water or drains.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

## Rust-Schock, Spray

Material number 111510

Page: 7 of 11

### 13. Disposal considerations

#### Product

Recommendation: Special waste. Do not open with force or incinerate, even when empty.  
Dispose of waste according to applicable legislation.  
Do not dispose of with household waste.

#### Contaminated packaging

Recommendation: Empty carefully and completely, if possible.  
Dispose of waste according to applicable legislation.  
Handle contaminated packages in the same way as the substance itself.  
Non-contaminated packages may be recycled.

### 14. Transport information

#### USA: Department of Transportation (DOT)

Identification number: UN1950  
Proper shipping name: UN 1950, AEROSOLS  
Hazard class or Division: 2.1  
Labels: 2.1  
Special provisions: N82  
Packaging – Exceptions: 306  
Packaging – Non-bulk: None  
Packaging – Bulk: None  
Quantity limitations – Passenger aircraft / rail: 75 kg  
Quantity limitations – Cargo only: 150 kg  
Vessel stowage – Location: A  
Vessel stowage – Other: 25, 87, 126



#### Canada: Transportation of Dangerous Goods (TDG)

UN Number: UN1950  
Shipping name: UN 1950, AEROSOLS  
TDG class: 2.1  
Special provisions: 80, 107  
Explosive limit and limited quantity index: 1 L  
Passenger carrying road or rail index: 75 L



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

## Rust-Schock, Spray

Material number 111510

Page: 8 of 11

### Sea transport (IMDG)

UN number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS  
Class or division, Subsidiary risk: Class 2, Subrisk-, see SP63  
Packing Group: -  
EmS: F-D, S-U  
Special provisions: 63, 190, 277, 327, 344, 381, 959  
Limited quantities: See SP277  
Excepted quantities: E0  
Contaminated packaging - Instructions: P207, LP200  
Contaminated packaging - Provisions: PP87, L2  
IBC - Instructions: -  
IBC - Provisions: -  
Tank instructions - IMO: -  
Tank instructions - UN: -  
Tank instructions - Provisions: -  
Stowage and handling: SW1 SW22  
Segregation: SG69  
Properties and observations: -  
Marine pollutant: no  
Segregation group: none

### Air transport (IATA)

UN/ID number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS, flammable  
Class or division, Subsidiary risk: Class 2.1  
Hazard label: Flamm. gas  
Excepted Quantity Code: E0  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G  
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg  
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg  
Special provisions: A145 A167 A802  
Emergency Response Guide-Code (ERG): 10L

## 15. Regulatory information

### National regulations - Canada

No data available





# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Rust-Schock, Spray

Material number 111510

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 9 of 11

### National regulations - U.S. Federal Regulations

Ethanol:	TSCA Inventory: listed TSCA HPVC: not listed TSCA: listed NIOSH Recommendations: Occupational Health Guideline: 0262
Propan-1-ol:	TSCA Inventory: listed TSCA HPVC: not listed NIOSH Recommendations: Occupational Health Guideline: 0533
n-Butane, pure:	TSCA Inventory: listed TSCA HPVC: not listed Clean Air Act: Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f NIOSH Recommendations: Occupational Health Guideline: 0068*
Propane:	TSCA Inventory: listed TSCA HPVC: not listed Clean Air Act: Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f NIOSH Recommendations: Occupational Health Guideline: 0524
Isobutane, pure:	TSCA Inventory: listed TSCA HPVC: not listed Clean Air Act: Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f NIOSH Recommendations: Occupational Health Guideline: 0350*



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Rust-Schock, Spray

Material number 111510

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 10 of 11

### National regulations - U.S. State Regulations

Ethanol:	California Proposition 65 code: - Idaho Air Pollutant List: Title 585: AAC: 94 - EL: 125 - OEL: 1880 - Title 586: - Massachusetts Haz. Substance codes: 2,4,5,6 *T1* Minnesota Haz. Substance: Codes: AO - Ratings: 7.74 Pennsylvania Haz. Substance code: - Washington Air Contaminant: TWA: 1000 ppm - 1900 mg
Propan-1-ol:	Idaho Air Pollutant List: Title 585: AAC: 25 - EL: 33.3 - OEL: 500 - Title 586: - Massachusetts Haz. Substance codes: 2,4,6 Minnesota Haz. Substance: Codes: AO - Ratings: - Pennsylvania Haz. Substance code: - Washington Air Contaminant: TWA: 200 ppm - 500 mg - STEL: 250 ppm - 625 mg Skin: Protective measures should be taken to prevent or reduce skin absorption.
n-Butane, pure:	Delaware Air Quality Management List: DRQ: F 1000** - RQ State: State requirements differs from Federal Massachusetts Haz. Substance codes: 4,5,6 Minnesota Haz. Substance: Codes: A - Ratings: - - Status: Title III New Jersey RTK Hazardous Substance: DOT: 1011 - Sub No.: 0273 - TPQ: - Pennsylvania Haz. Substance code: - Washington Air Contaminant: TWA: 800 ppm - 1900 mg
Propane:	California Proposition 65 code: - Delaware Air Quality Management List: DRQ: F 1000** - RQ State: State requirements differs from Federal Massachusetts Haz. Substance codes: 2,4,5,6 Minnesota Haz. Substance: Codes: AP - Ratings: - - Status: Title III New Jersey RTK Hazardous Substance: DOT: 1978 - Sub No.: 1594 - TPQ: - Pennsylvania Haz. Substance code: - Washington Air Contaminant: TWA: 1000 ppm - 1800 mg
Isobutane, pure:	California Proposition 65 code: - Delaware Air Quality Management List: DRQ: F 1000** - RQ State: State requirements differs from Federal Massachusetts Haz. Substance codes: 6 New Jersey RTK Hazardous Substance: DOT: 1969 - Sub No.: 1040 - TPQ: - Pennsylvania Haz. Substance code: -

### 16. Other information

Text for labeling: Contains 50 - 70 % Ethanol, < 20 % Propan-1-ol, 10 - 20 % n-Butane, pure, 1 - 10 % Propane, 1 - 10 % Isobutane, pure. Safety data sheet available on request.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

## Rust-Schock, Spray

Material number 111510

Page: 11 of 11

Hazard rating systems:



NFPA Hazard Rating:

Health: 3 (Serious)

Fire: 4 (Severe)

Reactivity: 1 (Slight)

HMIS Version III Rating:

Health: 3 (Serious)

Flammability: 4 (Severe)

Physical Hazard: 1 (Slight)

Personal Protection: X = Consult your supervisor

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	1
	X

Reason of change:

ADR/RID 2017, IMDG 2017

Date of first version:

23/Sep/2015

### Department issuing data sheet

Contact person:

see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.