



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Stainless Steel Care Spray

Material number 115900

Page: 1 of 11

1. Product and company identification

Product identifier

Trade name: Stainless Steel Care Spray

Relevant identified uses of the substance or mixture and uses advised against

General use: Technical aerosol
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: WEICON Inc.
Street/POB-No.: 20 Steckle Place, Unit 20
Postal Code, city: Kitchener, Ontario N2E 2C3, CA
WWW: www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254
Dept. responsible for information:
Product-Safety-Department
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

Emergency phone number

EMERGENCY CONTACT – Canada (24h): Tel: ++1 866 928 0789 (Toll free)

Transport:

TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: ++1 866 928 0789 (Toll free)

2. Hazards identification

Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: liquid
Form: Aerosol
Color: colorless
Odor: solvent-like
Classification: Aerosol 1; Acute Toxicity 4 (oral); Skin Irritation 2; Eye Irritation 2A;
Sensitization - skin 1; Specific Target Organ Toxicity (Single Exposure) 3;
Aquatic toxicity - chronic 2;

Hazard symbols:



Signal word:

Danger

Hazard statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
Harmful if swallowed.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Stainless Steel Care Spray

Material number 115900

Page: 2 of 11

Precautionary statements: Keep out of reach of children.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid breathing vapors/spray.
Wash hands and face thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection.
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF ON SKIN: Wash with plenty of water/soap.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a POISON CENTER/doctor if you feel unwell.
Specific treatment (see 'First aid' on this label).
Rinse mouth.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing.
Collect spillage.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container to hazardous or special waste collection point.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may have a narcotic effect.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterisation: Preparation of active ingredients with propellant



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Stainless Steel Care Spray

Material number 115900

Page:

3 of 11

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	10 - 25 %	Flammable Liquid 3. Specific Target Organ Toxicity (Single Exposure) 3. Aspiration Toxicity 1.
CAS 64-17-5	Ethanol	10 - 25 %	Flammable Liquid 2. Eye Irritation 2A.
CAS 64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	10 - 20 %	Flammable Liquid 2. Skin Irritation 2. Specific Target Organ Toxicity (Single Exposure) 3. Aspiration Toxicity 1. Aquatic toxicity - chronic 2.
CAS 111-76-2	2-Butoxyethanol	10 - 20 %	Acute Toxicity 4 (oral). Acute Toxicity 4 (dermal). Acute Toxicity 4 (inhalative). Skin Irritation 2. Eye Irritation 2A.
CAS 92062-35-6	Mineral oil	< 10 %	Aspiration Toxicity 1.
CAS 5989-27-5	(R)-p-Mentha-1,8-diene	< 1 %	Flammable Liquid 3. Skin Irritation 2. Sensitization - skin 1. Aquatic toxicity - acute 1. Aquatic toxicity - chronic 1.
CAS 74-98-6	Propane	10 - 25 %	Flammable Gas 1. Compressed Gas.
CAS 106-97-8	n-Butane, pure	10 - 25 %	Flammable Gas 1. Compressed Gas.

Additional information: > 30% aliphatic hydrocarbons, < 5% perfumes

4. First aid measures

General information:	First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse.
In case of inhalation:	Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical attention.
Following skin contact:	Immediately clean with water and soap followed by thorough rinsing. Seek medical attention. Take off contaminated clothing and wash it before reuse.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.
After swallowing:	Immediately get medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Harmful if swallowed. May cause drowsiness or dizziness. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Inhalation causes narcotic effects/intoxication. Irritates skin and mucous membranes.

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:

-97 °C

Auto-ignition temperature: not self-igniting



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Stainless Steel Care Spray

Material number 115900

Page: 4 of 11

Suitable extinguishing media:

Alcohol resistant foam, extinguishing powder, carbon dioxide, water mist.

Extinguishing media which must not be used for safety reasons:

full water jet

Specific hazards arising from the chemical

Heating will lead to pressure increase: Danger of bursting and explosion. Cool exposed containers with water spray.

May form dangerous gases and vapours in case of fire.

In case of fire may be liberated: Carbon monoxide and carbon dioxide.

Potentially explosive vapor/air mixtures may form.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

You have to dispose of contaminated extinguishing water according to the regulations of the authorities.

6. Accidental release measures

Personal precautions:

Do not breathe gas/vapor/spray. Avoid contact with the substance. Eliminate all ignition sources if safe to do so. Provide adequate ventilation. Wear appropriate protective equipment. Keep unprotected people away. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects. Take off contaminated clothing and wash it before reuse. Do not spray into eyes or onto the skin.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains. In case of release, notify competent authorities. Danger of explosion!

Methods for clean-up:

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Beware of reignition. Thoroughly clean surrounding area.

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

7. Handling and storage

Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed. Do not breathe gas/vapor/spray. Avoid contact with skin and eyes. Wear appropriate protective equipment. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation. Take off contaminated clothing and wash it before reuse.

Precautions against fire and explosion:

Container under pressure. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Use only explosion-protected equipment/instruments. Do not weld. In partially filled containers explosive mixtures may form. Vapors may form explosive mixtures with air.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017
Version: 3
Language: en-CA,US
Date of print: 10/Jan/2017

Stainless Steel Care Spray

Material number 115900

Page: 5 of 11

Storage

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from heat and direct sunlight.
Store containers in upright position. Explosion protection required. Store locked up.
Keep at temperature not exceeding 50 °C.

Hints on joint storage:

Do not store together with combustible or self-igniting materials or any highly flammable solids. Keep away from food, drink and animal feedingstuffs.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
64-17-5	Ethanol	Canada, Alberta: OEL 8 hour	1880 mg/m ³ ; 1000 ppm
		Canada, BC: OEL STEL	1000 ppm
		Canada, Québec: VEMP	1880 mg/m ³ ; 1000 ppm
		USA: ACGIH: STEL	1000 ppm (A3)
		USA: NIOSH: TWA	1900 mg/m ³ ; 1000 ppm
		USA: OSHA: TWA	1900 mg/m ³ ; 1000 ppm
111-76-2	2- Butoxyethanol	Canada, Alberta: OEL 8 hour	97 mg/m ³ ; 20 ppm
		Canada, BC: OEL TWA	20 ppm
		Canada, Québec: VEMP	97 mg/m ³ ; 20 ppm
		USA: ACGIH: TWA	97 mg/m ³ ; 20 ppm
		USA: NIOSH: TWA	24 mg/m ³ ; 5 ppm (May be absorbed through the skin.)
		USA: OSHA: TWA	240 mg/m ³ ; 50 ppm (May be absorbed through the skin.)
74-98-6	Propane	Canada, Alberta: OEL 8 hour	1000 ppm
		Canada, Québec: VEMP	1800 mg/m ³ ; 1000 ppm
		USA: NIOSH: TWA	1800 mg/m ³ ; 1000 ppm
		USA: OSHA: TWA	1800 mg/m ³ ; 1000 ppm
106-97-8	n-Butane, pure	Canada, Alberta: OEL 8 hour	1000 ppm
		Canada, BC: OEL STEL	750 ppm
		Canada, BC: OEL TWA	600 ppm
		Canada, Ontario: OEL TWA	800 ppm
		Canada, Québec: VEMP	1900 mg/m ³ ; 800 ppm
		USA: ACGIH: TWA	2370 mg/m ³ ; 1000 ppm
USA: NIOSH: TWA	1900 mg/m ³ ; 800 ppm		

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
111-76-2	2-Butoxyethanol	USA: ACGIH-BEI, urine	200 mg/g creatinine	Butoxyacetic acid (BAA)	end of exposure or end of shift

Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Use only explosion-proof equipment.
See also information in chapter 7, section storage.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Stainless Steel Care Spray

Material number 115900

Page:

6 of 11

Personal protection equipment (PPE)

Eye/face protection	Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
Skin protection	Flame retardant, antistatic and chemical resistant protective clothing. Protective gloves according to OSHA Standard - 29 CFR: 1910.138 (Solvent resistant protective gloves). Glove material: Nitrile rubber - Layer thickness: 0.7 mm Breakthrough time: > 480 min. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Respiratory protection:	Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.
General hygiene considerations:	Use only non-sparking tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Do not breathe gas/vapor/spray. Avoid contact with skin and eyes. Take off contaminated clothing and wash it before reuse. When using do not eat, drink or smoke. Wash hands before breaks and after work.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Form: Aerosol Color: colorless
Odor:	solvent-like
Odor threshold:	No data available
pH value:	not determined
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	-44 °C
Flash point/flash point range:	-97 °C
Evaporation rate:	No data available
Flammability:	Extremely flammable aerosol.
Explosion limits:	LEL (Lower Explosion Limit): 0.60 Vol-% UEL (Upper Explosive Limit): 15.00 Vol-%
Vapor pressure:	at 20 °C: 8300 hPa
Vapor density:	No data available
Density:	at 20 °C: 0.693 g/mL
Water solubility:	at 20 °C: slightly miscible
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	not self-igniting
Thermal decomposition:	No data available
Explosive properties:	Product is not explosive. Potentially explosive vapor/air mixtures may form.
Ignition temperature:	200 °C
Solvent content:	95.2 %



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Stainless Steel Care Spray

Material number 115900

Page: 7 of 11

10. Stability and reactivity

Reactivity:	Extremely flammable aerosol. Vapors may form explosive mixtures with air.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Container under pressure. Heating will lead to pressure increase: Danger of bursting and explosion.
Conditions to avoid:	Keep away from heat sources, sparks and open flames. Protect from direct exposure to sunlight and temperatures exceeding 50 °C.
Incompatible materials:	Do not store together with combustible or self-igniting materials or any highly flammable solids.
Hazardous decomposition products:	May form dangerous gases and vapours in case of fire. In case of fire may be liberated: carbon monoxide and carbon dioxide
Thermal decomposition:	No data available

11. Toxicological information

Toxicological tests

Toxicological effects:	The statements are derived from the properties of the single components. No toxicological data is available for the product as such. Acute toxicity (oral): Acute Toxicity 4 (oral) = Harmful if swallowed. ATEmix (calculated): $300 < ATE \leq 2000$ mg/kg. Acute toxicity (dermal): Based on available data, the classification criteria are not met. ATEmix (calculated): $ATE > 2000$ mg/kg. Acute toxicity (inhalative): Lack of data. Skin corrosion/irritation: Skin Irritation 2 = Causes skin irritation. Eye damage/irritation: Eye Irritation 2A = Causes serious eye irritation. Sensitisation to the respiratory tract: Lack of data. Skin sensitisation: Sensitization - skin 1 = May cause an allergic skin reaction. Germ cell mutagenicity/Genotoxicity: Lack of data. Carcinogenicity: Lack of data. Reproductive toxicity: Lack of data. Effects on or via lactation: Lack of data. Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) 3 = May cause drowsiness or dizziness. Specific target organ toxicity (repeated exposure): Lack of data. Aspiration hazard: Based on available data, the classification criteria are not met.
------------------------	--



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Stainless Steel Care Spray

Material number 115900

Page: 8 of 11

Other information: Information about 2-Butoxyethanol:
LD50 Rat, oral: 470 mg/kg (OECD 401)
LD50 Rabbit, dermal: 2000 mg/kg (OECD 402)
LD50 Rat, inhalative: 2.2 (OECD 403)
Information about Naphtha (petroleum), hydrotreated heavy:
LD50 Rat, oral: > 5000 mg/kg.
LD50 Rabbit, dermal: > 2000 mg/kg.
LD50 Rat, inhalative > 5.61 mg/L
For carcinogenic effects:
Information about 2-Butoxyethanol:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed
Information about (R)-p-Mentha-1,8-diene:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed

12. Ecological information

Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.
Information about 2-Butoxyethanol:
Bacterial toxicity:
EC 0 Pseudomonas putida: 700 mg/L/16h.
Daphnia toxicity:
EC50 Daphnia magna (Big water flea): 1698 - 1940 mg/L/24h.
Fish toxicity:
LC50 Lepomis macrochirus (bluegill): 1490 mg/L/96h.

Mobility in soil

No data available

Persistence and degradability

Further details: Information about 2-Butoxyethanol:
Biodegradation: 95 %/28d (OECD 301 E).
Product is readily biodegradable.

Additional ecological information

Volatile organic compounds (VOC):
95.16 % by weight = 659.5 g/L
General information: Do not allow to enter into ground-water, surface water or drains.

13. Disposal considerations

Product

Recommendation: Dispose of waste according to applicable legislation.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle empty containers with care. Incineration may cause explosion. Spray can must be completely empty for proper waste disposal.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Stainless Steel Care Spray

Material number 115900

Page: 9 of 11

14. Transport information

USA: Department of Transportation (DOT)

Identification number: UN1950
Proper shipping name: UN 1950, AEROSOLS
Hazard class or Division: 2.1
Labels: 2.1
Special provisions: N82
Packaging – Exceptions: 306
Packaging – Non-bulk: None
Packaging – Bulk: None
Quantity limitations – Passenger aircraft / rail:
75 kg
Quantity limitations – Cargo only: 150 kg
Vessel stowage – Location: A
Vessel stowage – Other: 25, 87, 126



Canada: Transportation of Dangerous Goods (TDG)

UN Number: UN1950
Shipping name: UN 1950, AEROSOLS
TDG class: 2.1
Special provisions: 80, 107
Explosive limit and limited quantity index: 1 L
Passenger carrying road or rail index: 75 L

Sea transport (IMDG)

UN number: UN 1950
Proper shipping name: UN 1950, AEROSOLS
Class or division, Subsidiary risk: Class 2.1, Subrisk-
Packing Group: -
EmS: F-D, S-U
Special provisions: 63, 190, 277, 327, 344, 381,959
Limited quantities: 1000 mL
Excepted quantities: E0
Contaminated packaging - Instructions: P207, LP200
Contaminated packaging - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Marine pollutant: yes
Segregation group: none

Air transport (IATA)

UN/ID number: UN 1950
Proper shipping name: UN 1950, AEROSOLS, flammable
Class or division, Subsidiary risk: Class 2.1
Hazard label: Flamm. gas
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special provisions: A145 A167 A802
Emergency Response Guide-Code (ERG): 10L



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017
Version: 3
Language: en-CA,US
Date of print: 10/Jan/2017

Stainless Steel Care Spray

Material number 115900

Page: 10 of 11

15. Regulatory information

National regulations - Canada

No data available

National regulations - U.S. Federal Regulations

Hydrocarbons, C9-C11, n-alkanes,
isoalkanes, cyclics, <2% aromatics:

TSCA Inventory: listed; EPA flags P
TSCA HPVC: not listed

Ethanol:

TSCA Inventory: listed
TSCA HPVC: not listed
NIOSH Recommendations:
Occupational Health Guideline: 0262

Hydrocarbons, C6-C7, n-alkanes, isoalkanes,
cyclics, <5% n-hexane:

TSCA Inventory: listed
TSCA HPVC: not listed

2-Butoxyethanol:

TSCA Inventory: listed
TSCA HPVC: not listed
Carcinogen Status:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed

Clean Air Act:

SOCMI Chemical: yes

NIOSH Recommendations:

Occupational Health Guideline: 0070*

(R)-p-Mentha-1,8-diene:

TSCA Inventory: listed
TSCA HPVC: not listed
Carcinogen Status:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed

Other Environmental Laws:

Marine Pollutant: listed as pollutant.

Propane:

TSCA Inventory: listed
TSCA HPVC: not listed
Clean Air Act:
Accidental Release Prevention: Threshold 10000 lbs. /
Basis for listing = f
NIOSH Recommendations:
Occupational Health Guideline: 0524

n-Butane, pure:

TSCA Inventory: listed
TSCA HPVC: not listed
Clean Air Act:
Accidental Release Prevention: Threshold 10000 lbs. /
Basis for listing = f
NIOSH Recommendations:
Occupational Health Guideline: 0068*

National regulations - U.S. State Regulations

California Proposition 65: Not listed.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 3

Language: en-CA,US

Date of print: 10/Jan/2017

Stainless Steel Care Spray

Material number 115900

Page: 11 of 11

16. Other information

Text for labeling:

Contains 10 - 25 % Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, 10 - 25 % Ethanol, 10 - 20 % Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, 10 - 20 % 2-Butoxyethanol, < 10 % Mineral oil, < 1 % (R)-p-Mentha-1,8-diene, 10 - 25 % Propane, 10 - 25 % n-Butane, pure. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:

Health: 3 (Serious)

Fire: 4 (Severe)

Reactivity: 1 (Slight)

HMIS Version III Rating:

Health: 3 (Serious)

Flammability: 4 (Severe)

Physical Hazard: 1 (Slight)

Personal Protection: X = Consult your supervisor

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	1
	X

Reason of change:

ADR/RID 2017, IMDG 2017

Date of first version:

22/Dec/2015

Department issuing data sheet

Contact person:

see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.