



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/6/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

## Crack Testing Agent Penetrant

Material number 116905

Page: 1 of 11

### 1. Product and company identification

#### Product identifier

Trade name: Crack Testing Agent Penetrant

#### Relevant identified uses of the substance or mixture and uses advised against

General use: Technical aerosol, cleaning agent.  
Reserved for industrial and professional use.

#### Details of the supplier of the safety data sheet

Company name: WEICON Inc.  
Street/POB-No.: 20 Steckle Place, Unit 20  
Postal Code, city: Kitchener, Ontario N2E 2C3, CA  
WWW: www.weicon.ca  
E-mail: info@weicon.ca  
Telephone: +1-519-896-5252  
Telefax: +1-519-896-5254  
Dept. responsible for information:  
Product-Safety-Department  
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

#### Emergency phone number

**EMERGENCY CONTACT – USA (24h): Tel: ++1 202 464 2554**

**Transport:**

**TRANSPORT EMERGENCY CONTACT - USA (24h): Tel: ++1 202 464 2554**

### 2. Hazards identification

#### Emergency overview

Appearance: Form: Aerosol  
Color: red  
Odor: characteristic  
Classification: Flammable Aerosol - Category 1; Compressed Gas; Eye Irritation - Category 2A;  
Sensitization - skin - Category 1; Aquatic toxicity - chronic - Category 3;

Hazard symbols:



Signal word:

**Danger**

Hazard statements:

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Harmful to aquatic life with long lasting effects.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/6/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

## Crack Testing Agent Penetrant

Material number 116905

Page: 2 of 11

Precautionary statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wash hands and face thoroughly after handling.  
Contaminated work clothing should not be allowed out of the workplace.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection.  
IF ON SKIN: Wash with plenty of water/soap.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Specific treatment (see ' First aid ' on this label).  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
Protect from sunlight. Store in a well-ventilated place.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container to hazardous or special waste collection point.

### Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

### Hazards not otherwise classified

Potentially explosive mixtures may form if adequate ventilation is not provided.  
Inhaling can lead to irritations of the respiratory tract and mucous membrane.  
Higher doses may lead to a narcotic effect.  
see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterization: Preparation of active ingredients with propellant

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 112-34-5	2-(2-Butoxyethoxy)ethanol	10 - 25 %	Eye Irritation - Category 2A.
CAS 64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	2.5 - 10 %	Aspiration Toxicity - Category 1.
CAS 64742-94-5	Hydrocarbons, C10, aromatics, <1% naphthalene	2.5 - 10 %	Specific Target Organ Toxicity (Single Exposure) - Category 3. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 56358-10-2	N-(2-ethylhexyl)-1-[[3-methyl-4-[(3-methylphenyl)azo]phenyl]azo]naphthalen-2-amine	1 - 2.5 %	Skin Irritation - Category 2. Sensitization - skin - Category 1.
CAS 106-97-8	Butane	10 - 25 %	Flammable Gas - Category 1. Compressed Gas.
CAS 74-98-6	Propane	2.5 - 10 %	Flammable Gas - Category 1. Compressed Gas.
CAS 75-28-5	Isobutane, pure	< 2.5 %	Flammable Gas - Category 1. Compressed Gas.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/6/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

## Crack Testing Agent Penetrant

Material number 116905

Page: 3 of 11

### 4. First aid measures

- General information: IF exposed or concerned: Get medical advice/attention. First aider: Pay attention to self-protection! In the event of persistent symptoms seek medical treatment.
- In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical attention.
- Following skin contact: After contact with skin, wash immediately with soap and plenty of water. Consult a doctor if skin irritation persists.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.
- After swallowing: Immediately get medical attention. Do not induce vomiting. Aspiration hazard: in case of swallowing or vomiting danger of penetration into the lungs. Never give anything by mouth to an unconscious person.

#### Most important symptoms/effects, acute and delayed

Causes serious eye irritation. May cause an allergic skin reaction. Inhalation causes narcotic effects/intoxication. Headache, Nausea. Inhaling can lead to irritations of the respiratory tract and mucous membrane.

#### Information to physician

Treat symptomatically.

### 5. Fire fighting measures

- Flash point/flash point range: not applicable
- Auto-ignition temperature: not self-igniting
- Suitable extinguishing media: Water fog, alcohol resistant foam, dry chemical powder, sand, carbon dioxide.
- Extinguishing media which must not be used for safety reasons: Full water jet

#### Specific hazards arising from the chemical

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May form dangerous gases and vapours in case of fire. Furthermore, there may develop: Carbon monoxide and carbon dioxide. Potentially explosive vapor/air mixtures may form.

#### Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing. In case of fire and/or explosion do not breathe fumes.

#### Additional information:

Heating will lead to pressure increase: Danger of bursting and explosion. Cool exposed containers with water spray.

Move undamaged containers from immediate hazard area if it can be done safely. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water. Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/6/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

## Crack Testing Agent Penetrant

Material number 116905

Page: 4 of 11

### 6. Accidental release measures

- Personal precautions:** Provide adequate ventilation. Do not breathe gas/vapor/spray. Avoid contact with skin and eyes. Eliminate all ignition sources if safe to do so. Wear appropriate protective equipment. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction. Take off immediately all contaminated clothing. Keep unprotected people away. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects. Cordon off downwind area at risk and warn inhabitants.
- Environmental precautions:** Do not allow to enter into ground-water, surface water or drains. In case of release, notify competent authorities. Danger of explosion!
- Methods for clean-up:** Allow small spillages to evaporate provided there is adequate ventilation. Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Beware of reignition. Thoroughly clean surrounding area.
- Additional information:** Use explosion-proof equipment and non-sparking tools/utensils. Leaking cans, cans with spillage, are to be segregated, sprayed to empty state and disposed of. Refer to section 13 (Waste removal)

### 7. Handling and storage

#### Handling

- Advices on safe handling:** Provide adequate ventilation, and local exhaust as needed. Do not breathe gas/vapor/spray. Avoid contact with skin and eyes. Wear appropriate protective equipment. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation. Take off immediately all contaminated clothing. When handling large quantities, supply emergency spray. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
- Precautions against fire and explosion:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.

#### Storage

- Requirements for storerooms and containers:** Keep container tightly closed and in a well-ventilated place. Keep container dry. Keep only in the original container. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. storage temperature: 41 °F up to 104 °F. Store containers in upright position.
- Hints on joint storage:** Keep away from oxidizing agents. Keep away from food, drink and animal feedingstuffs.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/6/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

## Crack Testing Agent Penetrant

Material number 116905

Page: 5 of 11

### 8. Exposure controls / personal protection

#### Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
112-34-5	2-(2-Butoxyethoxy) ethanol	USA: ACGIH: TWA	67.5 mg/m <sup>3</sup> ; 10 ppm inhalable fraction and vapor
106-97-8	Butane	USA: ACGIH: TWA USA: NIOSH: TWA	2370 mg/m <sup>3</sup> ; 1000 ppm 1900 mg/m <sup>3</sup> ; 800 ppm
74-98-6	Propane	USA: NIOSH: TWA USA: OSHA: TWA	1800 mg/m <sup>3</sup> ; 1000 ppm 1800 mg/m <sup>3</sup> ; 1000 ppm
75-28-5	Isobutane, pure	USA: ACGIH: TWA USA: NIOSH: TWA	2370 mg/m <sup>3</sup> ; 1000 ppm 1900 mg/m <sup>3</sup> ; 800 ppm

#### Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Use only explosion-proof equipment.  
See also information in chapter 7, section storage.

#### Personal protection equipment (PPE)

- Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
- Skin protection: Flame retardant, antistatic and chemical resistant protective clothing.  
Protective gloves according to OSHA Standard - 29 CFR: 1910.138 (Solvent resistant protective gloves).  
Glove material: Nitrile rubber - Layer thickness:  $\geq 0.4$  mm  
Breakthrough time:  $> 60$  min.  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.  
If higher concentrations occur: Wear self-contained breathing apparatus.  
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.
- General hygiene considerations:  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not pierce or burn, even after use.  
Do not breathe gas/vapor/spray. Do not get in eyes, on skin, or on clothing.  
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.  
Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.

### 9. Physical and chemical properties

#### Information on basic physical and chemical properties

- Appearance: Form: Aerosol  
Color: red



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/6/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

## Crack Testing Agent Penetrant

Material number 116905

Page: 6 of 11

Odor:	characteristic
Odor threshold:	not determined
pH value:	not determined
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	-47.2 °F
Flash point/flash point range:	not applicable
Evaporation rate:	not applicable
Flammability:	extremely flammable aerosol
Explosion limits:	LEL (Lower Explosion Limit): 0.70 Vol-% UEL (Upper Explosive Limit): 10.00 Vol-%
Vapor pressure:	at 68 °F: 2500 - 5000 hPa
Vapor density:	not determined
Density:	at 68 °F: 0.717 g/cm <sup>3</sup>
Solubility:	not determined
Water solubility:	slightly soluble
Partition coefficient: n-octanol/water:	not determined
Auto-ignition temperature:	not self-igniting
Thermal decomposition:	No decomposition when used properly.
Viscosity, dynamic:	not determined
Viscosity, kinematic:	not determined
Explosive properties:	Vapors may form explosive mixtures with air. Contains gas under pressure; may explode if heated.
Ignition temperature:	437 °F
Solvent content:	70.98 %

### 10. Stability and reactivity

Reactivity:	Extremely flammable aerosol. Vapors may form explosive mixtures with air.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Contains gas under pressure; may explode if heated.
Conditions to avoid:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Incompatible materials:	oxidizing agents
Hazardous decomposition products:	Carbon monoxide and carbon dioxide
Thermal decomposition:	No decomposition when used properly.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/6/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

## Crack Testing Agent Penetrant

Material number 116905

Page: 7 of 11

### 11. Toxicological information

#### Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.  
Acute toxicity (oral): Lack of data.  
Acute toxicity (dermal): Lack of data.  
Acute toxicity (inhalative): Lack of data.  
Skin corrosion/irritation: Based on available data, the classification criteria are not met.  
Eye damage/irritation: Eye Irritation - Category 2A = Causes serious eye irritation.  
Sensitisation to the respiratory tract: Lack of data.  
Skin sensitisation: Sensitization - skin - Category 1 = May cause an allergic skin reaction.  
Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.  
Reproductive toxicity: Based on available data, the classification criteria are not met.  
Effects on or via lactation: Lack of data.  
Specific target organ toxicity (single exposure): Lack of data.  
Specific target organ toxicity (repeated exposure): Lack of data.  
Aspiration hazard: Lack of data.

Other information: Information about 2-(2-Butoxyethoxy)ethanol:  
LD50 Rat, oral: 338420 mg/kg bw  
LD50 Rabbit, dermal: 2700 mg/kg

#### Symptoms

After contact with skin: Minor irritation effect - does not require labeling.

#### General remarks

Further hazardous properties cannot be excluded.

### 12. Ecological information

#### Ecotoxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

#### Mobility in soil

No data available

#### Persistence and degradability

Further details: No data available

#### Additional ecological information

Volatile organic compounds (VOC):

70.98 % by weight

General information: Do not allow to penetrate into soil, waterbodies or drains.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/6/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

## Crack Testing Agent Penetrant

Material number 116905

Page: 8 of 11

### 13. Disposal considerations

#### Product

Recommendation: Do not pierce or burn, even after use.  
Special waste. Dispose of waste according to applicable legislation.  
Do not dispose of with household waste.

#### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.  
Empty carefully and completely, if possible. Handle empty containers with care.  
Incineration may cause explosion.

### 14. Transport information

#### USA: Department of Transportation (DOT)

Identification number: UN1950  
Proper shipping name: UN 1950, AEROSOLS  
Hazard class or Division: 2.1  
Labels: 2.1  
Special provisions: N82  
Packaging – Exceptions: 306  
Packaging – Non-bulk: None  
Packaging – Bulk: None  
Quantity limitations – Passenger aircraft / rail:  
75 kg  
Quantity limitations – Cargo only: 150 kg  
Vessel stowage – Location: A  
Vessel stowage – Other: 25, 87, 126



#### Sea transport (IMDG)

UN number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS  
Class or division, Subsidiary risk: Class 2.1, Subrisk-  
Packing Group: -  
EmS: F-D, S-U  
Special provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantities: 1000 mL  
Excepted quantities: E0  
Contaminated packaging - Instructions: P207, LP200  
Contaminated packaging - Provisions: PP87, L2  
IBC - Instructions: -  
IBC - Provisions: -  
Tank instructions - IMO: -  
Tank instructions - UN: -  
Tank instructions - Provisions: -  
Stowage and handling: SW1 SW22  
Segregation: SG69  
Properties and observations: -  
Marine pollutant: no  
Segregation group: none





# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/6/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

## Crack Testing Agent Penetrant

Material number 116905

Page: 9 of 11

### Air transport (IATA)

UN/ID number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS, flammable  
Class or division, Subsidiary risk: Class 2.1  
Hazard label: Flamm. gas  
Excepted Quantity Code: E0  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G  
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg  
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg  
Special provisions: A145 A167 A802  
Emergency Response Guide-Code (ERG): 10L

## 15. Regulatory information

### National regulations - U.S. Federal Regulations

2-(2-Butoxyethoxy)ethanol: TSCA Inventory: listed  
TSCA HPVC: not listed  
Clean Air Act:  
Hazardous Air Pollutants: yes  
SOCMI Chemical: yes

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics: TSCA Inventory: listed; UVCB  
TSCA HPVC: not listed

Hydrocarbons, C10, aromatics, <1% naphthalene: TSCA Inventory: listed; UVCB  
TSCA HPVC: not listed

N-(2-ethylhexyl)-1-[[3-methyl-4-[(3-methylphenyl)azo]phenyl]azo]naphthalen-2-amine: TSCA Inventory: listed; EPA flags P  
TSCA HPVC: not listed

Butane: TSCA Inventory: listed  
TSCA HPVC: not listed  
Clean Air Act:  
Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f  
NIOSH Recommendations:  
Occupational Health Guideline: 0068\*

Propane: TSCA Inventory: listed  
TSCA HPVC: not listed  
Clean Air Act:  
Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f  
NIOSH Recommendations:  
Occupational Health Guideline: 0524

Isobutane, pure: TSCA Inventory: listed  
TSCA HPVC: not listed  
Clean Air Act:  
Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f  
NIOSH Recommendations:  
Occupational Health Guideline: 0350\*



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/6/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

## Crack Testing Agent Penetrant

Material number 116905

Page: 10 of 11

### National regulations - U.S. State Regulations

Butane:

Delaware Air Quality Management List:  
 DRQ: F 1000\*\* - RQ State: State requirements differs from Federal  
 Massachusetts Haz. Substance codes: 4,5,6  
 Minnesota Haz. Substance:  
 Codes: A - Ratings: - - Status: Title III  
 New Jersey RTK Hazardous Substance:  
 DOT: 1011 - Sub No.: 0273 - TPQ: -  
 Pennsylvania Haz. Substance code: -  
 Washington Air Contaminant:  
 TWA: 800 ppm - 1900 mg

Propane:

California Proposition 65 code: -  
 Delaware Air Quality Management List:  
 DRQ: F 1000\*\* - RQ State: State requirements differs from Federal  
 Massachusetts Haz. Substance codes: 2,4,5,6  
 Minnesota Haz. Substance:  
 Codes: AP - Ratings: - - Status: Title III  
 New Jersey RTK Hazardous Substance:  
 DOT: 1978 - Sub No.: 1594 - TPQ: -  
 Pennsylvania Haz. Substance code: -  
 Washington Air Contaminant:  
 TWA: 1000 ppm - 1800 mg

Isobutane, pure:

California Proposition 65 code: -  
 Delaware Air Quality Management List:  
 DRQ: F 1000\*\* - RQ State: State requirements differs from Federal  
 Massachusetts Haz. Substance codes: 6  
 New Jersey RTK Hazardous Substance:  
 DOT: 1969 - Sub No.: 1040 - TPQ: -  
 Pennsylvania Haz. Substance code: -

### National regulations - Great Britain

Hazchem-Code: -

## 16. Other information

Text for labeling:

Contains 10 - 25 % 2-(2-Butoxyethoxy)ethanol, 2.5 - 10 % Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics, 2.5 - 10 % Hydrocarbons, C10, aromatics, <1% naphthalene, 1 - 2.5 % N-(2-ethylhexyl)-1-[[3-methyl-4-[(3-methylphenyl)azo]phenyl]azo]naphthalen-2-amine, 10 - 25 % Butane, 2.5 - 10 % Propane, < 2.5 % Isobutane, pure. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:  
 Health: 2 (Moderate)  
 Fire: 4 (Severe)  
 Reactivity: 0 (Minimal)

HMIS Version III Rating:  
 Health: 2 (Moderate)  
 Flammability: 4 (Severe)  
 Physical Hazard: 0 (Minimal)  
 Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	0
	X

Date of first version: Apr/6/2017

### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/6/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

## Crack Testing Agent Penetrant

Material number 116905

Page: 11 of 11

---

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.