



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 29/Jan/2018

Version: 2

Language: en-CA,US

Date of print: 1/Feb/2018

## WEICON BR Resin

Material number 104201

Page: 1 of 9

### 1. Product and company identification

#### Product identifier

Trade name: WEICON BR Resin

#### Relevant identified uses of the substance or mixture and uses advised against

General use: Two-component epoxy resins, resin component.  
Reserved for industrial and professional use.

#### Details of the supplier of the safety data sheet

Company name: WEICON Inc.  
Street/POB-No.: 20 Steckle Place, Unit 20  
Postal Code, city: Kitchener, Ontario N2E 2C3, CA  
WWW: www.weicon.ca  
E-mail: info@weicon.ca  
Telephone: +1-519-896-5252  
Telefax: +1-519-896-5254  
Dept. responsible for information:  
Product-Safety-Department  
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

#### Emergency phone number

**EMERGENCY CONTACT – Canada (24h): Tel: ++1 866 928 0789 (Toll free)**

**Transport:**

**TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: ++1 866 928 0789 (Toll free)**

### 2. Hazards identification

#### Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: liquid  
Form: pasty  
Color: dark brown  
Odor: No data available  
Classification: Skin Irritation 2; Eye Irritation 2A; Sensitization - skin 1; Aquatic toxicity - chronic 2;

Hazard symbols:



Signal word:

**Warning**

Hazard statements:

Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## WEICON BR Resin

Material number 104201

Revision date: 29/Jan/2018

Version: 2

Language: en-CA,US

Date of print: 1/Feb/2018

Page: 2 of 9

Precautionary statements: Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wash hands and face thoroughly after handling.  
Contaminated work clothing should not be allowed out of the workplace.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection.  
IF ON SKIN: Wash with plenty of soap and water.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Specific treatment (see on this label).  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.  
Wash contaminated clothing before reuse.  
Collect spillage.  
Dispose of contents/container to hazardous or special waste collection point.

### Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

### Hazards not otherwise classified

see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterisation: Bisphenol A epoxy resin.

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 25068-38-6	Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700)	25 - 35 %	Skin Irritation 2. Eye Irritation 2A. Sensitization - skin 1. Aquatic toxicity - chronic 2.

## 4. First aid measures

General information: First aider: Pay attention to self-protection!  
If medical advice is needed, have product container or label at hand.  
Take off immediately all contaminated clothing and wash it before reuse.

In case of inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if problems persist.

Following skin contact: Immediately clean with water and soap followed by thorough rinsing. Take off immediately all contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.  
Subsequently consult an ophthalmologist.

After swallowing: Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Immediately get medical attention.

### Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Mucous membrane irritation.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## WEICON BR Resin

Material number 104201

Revision date: 29/Jan/2018

Version: 2

Language: en-CA,US

Date of print: 1/Feb/2018

Page: 3 of 9

### Information to physician

Treat symptomatically.

## 5. Fire fighting measures

Flash point/flash point range:

Not applicable

Auto-ignition temperature: Not determined

Suitable extinguishing media:

Extinguishing is to be in accordance with the surrounding fire.

Extinguishing media which must not be used for safety reasons:

Full water jet.

### Specific hazards arising from the chemical

Hazardous vapors may form during fires.

Furthermore, there may develop: Metal oxide smoke, nitrogen oxides (NO<sub>x</sub>), sulphur oxides, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Cool exposed containers with water spray.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow water used to extinguish fire to enter drains, ground or waterways.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

Do not inhale explosion and combustion gases. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention if problems persist.

## 6. Accidental release measures

Personal precautions:

Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with the substance.

If possible, eliminate leakage. Provide adequate ventilation.

Wear appropriate protective equipment. Keep unprotected people away.

Take off immediately all contaminated clothing and wash it before reuse.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.

If necessary notify appropriate authorities.

Methods for clean-up:

Soak up with absorbent materials such as sand, siliceous earth, acid- or universal binder. Store in special closed containers and dispose of according to ordinance.

Dispose of in accordance with the regulations. If necessary notify appropriate authorities.

Never return spills in original containers for re-use.

## 7. Handling and storage

### Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off immediately all contaminated clothing and wash it before reuse.

When handling large quantities, supply emergency spray.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## WEICON BR Resin

Material number 104201

Revision date: 29/Jan/2018

Version: 2

Language: en-CA,US

Date of print: 1/Feb/2018

Page: 4 of 9

### Storage

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place. Keep container dry. Protect from heat and direct sunlight. storage temperature: 5 °C up to 25 °C. Handle and open container with care. Store only in original container.

Hints on joint storage: Keep away from food, drink and animal feedingstuffs.

## 8. Exposure controls / personal protection

### Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

See also information in chapter 7, section storage.

### Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010

Skin protection: Wear suitable protective clothing.

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material: Natural latex

Layer thickness:  $\geq 0.6$  mm

Breakthrough time: 60 min

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. When vapors form, use respiratory protection.

The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.

If higher concentrations occur: Wear self-contained breathing apparatus.

General hygiene considerations:

Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

When handling large quantities, supply emergency spray.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Appearance: Physical state at 20 °C and 101.3 kPa: liquid

Form: pasty

Color: dark brown

Odor: No data available

Odor threshold: Not determined

pH value: Not applicable

Melting point/freezing point: Not determined

Initial boiling point and boiling range: Not determined

Flash point/flash point range: Not applicable

Evaporation rate: Not determined

Flammability: Not determined



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 29/Jan/2018

Version: 2

Language: en-CA,US

Date of print: 1/Feb/2018

## WEICON BR Resin

Material number 104201

Page: 5 of 9

Explosion limits:	LEL (Lower Explosion Limit): Not applicable UEL (Upper Explosive Limit): Not applicable
Vapor pressure:	Not determined
Vapor density:	No data available
Density:	at 20 °C: approx. 1.87 g/cm <sup>3</sup>
Solubility:	Not determined
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	Not determined
Auto-ignition temperature:	Not determined
Thermal decomposition:	No decomposition when used properly.
Viscosity, dynamic:	Not applicable
Explosive properties:	Not applicable
Ignition temperature:	> 200 °C (estimated)

## 10. Stability and reactivity

Reactivity:	Refer to subsection "Possibility of hazardous reactions".
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	No hazardous reaction when handled and stored according to provisions.
Conditions to avoid:	Keep away from heat sources, sparks and open flames. Protect against direct sunlight.
Incompatible materials:	No data available
Hazardous decomposition products:	Toxic gases/vapours. Metal oxide smoke, nitrogen oxides (NO <sub>x</sub> ), sulphur oxides, carbon monoxide and carbon dioxide.
Thermal decomposition:	No decomposition when used properly.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## WEICON BR Resin

Material number 104201

Revision date: 29/Jan/2018

Version: 2

Language: en-CA,US

Date of print: 1/Feb/2018

Page: 6 of 9

## 11. Toxicological information

### Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.  
Acute toxicity (oral): Lack of data.  
Acute toxicity (dermal): Lack of data.  
Acute toxicity (inhalative): Lack of data.  
Skin corrosion/irritation: Skin Irritation 2 = Causes skin irritation.  
Serious eye damage/irritation: Eye Irritation 2A = Causes serious eye irritation.  
Sensitisation to the respiratory tract: Lack of data.  
Skin sensitisation: Sensitization - skin 1 = May cause an allergic skin reaction.  
Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.  
Reproductive toxicity: Based on available data, the classification criteria are not met.  
Effects on or via lactation: Based on available data, the classification criteria are not met.  
Specific target organ toxicity (single exposure): Lack of data.  
Specific target organ toxicity (repeated exposure): Lack of data.  
Aspiration hazard: Lack of data.

Other information: Information about Reaction product with Bisphenol A-epichlorhydrin epoxy resin (molecular weight = 700):  
LD50, oral, Rat (OECD 401): 11400 mg/kg  
LD50, dermal, Rabbit (OECD 402): 20 mL/kg

### Symptoms

After contact with skin: Irritant, redness.  
After eye contact: Irritant, pain, redness, tear-producing.

### General remarks

Handle in accordance with good industrial hygiene and safety practice.  
Further hazardous properties cannot be excluded.

## 12. Ecological information

### Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.  
Information about Reaction product with Bisphenol A-epichlorhydrin epoxy resin (molecular weight = 700):  
Algae toxicity:  
EC50 *Desmodesmus subspicatus* (green algae): 9.4 mg/L/72h (EPA CFR).  
Daphnia toxicity:  
EC50 *Daphnia magna* (Big water flea): 1.7 mg/L/48h (OECD 202).  
Fish toxicity:  
LC50 *Oncorhynchus mykiss*: 1.2 mg/L/96h (OECD 203).  
Bacterial toxicity:  
IC50 Bacteria, Activated sludge: >100 mg/L/3 h.

### Mobility in soil

No data available



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 29/Jan/2018

Version: 2

Language: en-CA,US

Date of print: 1/Feb/2018

## WEICON BR Resin

Material number 104201

Page:

7 of 9

### Persistence and degradability

Further details: Information about Reaction product with Bisphenol A-epichlorhydrin epoxy resin (molecular weight = 700):  
Biodegradation: 5%/28d (OECD 301 F).  
Product is biodegradable with difficulty.  
Information about Bisphenol F Epoxy Resin: 0% /28d.  
Product is not biodegradable.

### Additional ecological information

Volatile organic compounds (VOC):  
< 35 % by weight = 645.5 g/L  
General information: Do not allow to enter into ground-water, surface water or drains.

## 13. Disposal considerations

### Product

Recommendation: Dispose of as hazardous waste in compliance with local and national regulations.  
Do not dispose of with household waste.

### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.

## 14. Transport information

### USA: Department of Transportation (DOT)

Identification number: UN3082  
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700).), mixture  
Hazard class or Division: 9  
Packing Group: III  
Labels: 9  
Symbols: G  
Special provisions: 8, 146, 173, 335, IB3, T4, TP1, TP29  
Packaging – Exceptions: 155  
Packaging – Non-bulk: 203  
Packaging – Bulk: 241  
Quantity limitations – Passenger aircraft / rail: No limit  
Quantity limitations – Cargo only: No limit  
Vessel stowage – Location: A



### Canada: Transportation of Dangerous Goods (TDG)

UN Number: UN3082  
Shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700).), mixture  
TDG class: 9  
Packing group: III  
Special provisions: 16, 99  
Explosive limit and limited quantity index: 5 L



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 29/Jan/2018

Version: 2

Language: en-CA,US

Date of print: 1/Feb/2018

## WEICON BR Resin

Material number 104201

Page:

8 of 9

### Sea transport (IMDG)

UN number: UN 3082  
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )), mixture  
Class or division, Subsidiary risk: Class 9, Subrisk -  
Packing Group: III  
EmS: F-A, S-F  
Special provisions: 274, 335, 969  
Limited quantities: 5 L  
Excepted quantities: E1  
Contaminated packaging - Instructions: P001, LP01  
Contaminated packaging - Provisions: PP1  
IBC - Instructions: IBC03  
IBC - Provisions: -  
Tank instructions - IMO: -  
Tank instructions - UN: T4  
Tank instructions - Provisions: TP2, TP29  
Stowage and handling: Category A.  
Properties and observations: -  
Marine pollutant: yes  
Segregation group: none

### Air transport (IATA)

UN/ID number: UN 3082  
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )), mixture  
Class or division, Subsidiary risk: Class 9  
Packing Group: III  
Hazard label: Miscellaneous  
Excepted Quantity Code: E1  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y964 - Max. Net Qty/Pkg. 30 kg G  
Passenger and Cargo Aircraft: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L  
Cargo Aircraft only: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L  
Special provisions: A97 A158 A197  
Emergency Response Guide-Code (ERG): 9L

## 15. Regulatory information

### National regulations - Canada

No data available

### National regulations - U.S. Federal Regulations

### National regulations - EC member states

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3

## 16. Other information

Text for labeling: Contains 25 - 35 % Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ ). Safety data sheet available on request.





# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010


Revision date: 29/Jan/2018  
Version: 2  
Language: en-CA,US  
Date of print: 1/Feb/2018

## WEICON BR Resin

Material number 104201

Page: 9 of 9

Hazard rating systems:



NFPA Hazard Rating:  
Health: 2 (Moderate)  
Fire: 0 (Minimal)  
Reactivity: 0 (Minimal)  
HMIS Version III Rating:  
Health: 2 (Moderate)  
Flammability: 0 (Minimal)  
Physical Hazard: 0 (Minimal)  
Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	0
PHYSICAL HAZARD	0
	X

Reason of change: Changes in section 2: Labeling  
General revision

Date of first version: 25/Apr/2017

### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.