



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

## Fast-Metal Minute Adhesive Resin

Material number 105511

Page: 1 of 9

### 1. Product and company identification

#### Product identifier

Trade name: Fast-Metal Minute Adhesive Resin

#### Relevant identified uses of the substance or mixture and uses advised against

General use: Two component epoxy adhesive.

#### Details of the supplier of the safety data sheet

Company name: WEICON Inc.  
Street/POB-No.: 20 Steckle Place, Unit 20  
Postal Code, city: Kitchener, Ontario N2E 2C3, CA  
WWW: www.weicon.ca  
E-mail: info@weicon.ca  
Telephone: +1-519-896-5252  
Telefax: +1-519-896-5254  
Dept. responsible for information:  
Product-Safety-Department  
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

#### Emergency phone number

**EMERGENCY CONTACT – USA (24h): Tel: ++1 202 464 2554**

**Transport:**

**TRANSPORT EMERGENCY CONTACT - USA (24h): Tel: ++1 202 464 2554**

### 2. Hazards identification

#### Emergency overview

Appearance: Form: pasty  
Color: black  
Odor: characteristic  
Classification: Skin Irritation - Category 2; Eye Irritation - Category 2A; Sensitization - skin - Category 1; Aquatic toxicity - chronic - Category 2;

Hazard symbols:



Signal word:

**Warning**

Hazard statements:

Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.

Precautionary statements:

Keep out of reach of children.  
Avoid breathing vapors.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection.  
IF ON SKIN: Wash with plenty of water/soap.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Collect spillage.  
Dispose of contents/container to hazardous or special waste collection point.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

## Fast-Metal Minute Adhesive Resin

Material number 105511

Page: 2 of 9

### Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

### Hazards not otherwise classified

Special danger of slipping by leaking/spilling product.  
see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterization: Epoxide resin-based adhesive.

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 25068-38-6	Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700)	30 - 50 %	Skin Irritation - Category 2. Eye Irritation - Category 2A. Sensitization - skin - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 28064-14-4	Bisphenol-F-epichlorhydrine resin	1 - 5 %	Skin Irritation - Category 2. Eye Irritation - Category 2A. Sensitization - skin - Category 1. Aquatic toxicity - chronic - Category 2.
CAS 100-51-6	Benzyl alcohol	1 - 5 %	Acute Toxicity - oral - Category 4. Acute Toxicity - inhalative - Category 4. Eye Irritation - Category 2A.
CAS 2425-79-8	1,4-bis(2,3-Epoxypropoxy) butane	1 - 5 %	Acute Toxicity - dermal - Category 4. Acute Toxicity - inhalative - Category 4. Skin Irritation - Category 2. Eye Irritation - Category 2A. Sensitization - skin - Category 1. Aquatic toxicity - chronic - Category 3.

Additional information: Contains Limestone, Barium sulfate, Magnesium carbonate and Talcum. The maximum workplace exposure limits are, where necessary, listed in section 8.

## 4. First aid measures

In case of inhalation: Provide fresh air. Move victim to fresh air; if necessary, provide artificial respiration or oxygen. If the casualty has difficulty breathing, call a doctor immediately.

Following skin contact: After contact with skin, wash immediately with soap and plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Seek medical treatment in case of troubles.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Seek the attention of an ophthalmologist immediately.

After swallowing: Rinse mouth with water. Do not induce vomiting without medical assistance. In case of vomiting, lay at least head on side. Immediately get medical attention.

### Most important symptoms/effects, acute and delayed

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

### Information to physician

Treat symptomatically.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

## Fast-Metal Minute Adhesive Resin

Material number 105511

Page: 3 of 9

### 5. Fire fighting measures

Flash point/flash point range:

not applicable

Auto-ignition temperature: not determined

Suitable extinguishing media:

Alcohol resistant foam, dry chemical powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

High power water jet.

#### Specific hazards arising from the chemical

This material is combustible, but will not ignite readily.

In case of fire may be liberated: Smoke, aldehydes, phenols, carbon monoxide and carbon dioxide

Protective equipment and precautions for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Cool endangered containers with water spray and, if possible, remove from danger zone. Use a water fog to control vapors. Do not breathe fumes. Do not allow fire water to penetrate into surface or ground water.

### 6. Accidental release measures

Personal precautions:

Eliminate all ignition sources if safe to do so. Avoid contact with skin, eyes, and clothing. Use suitable personal protective equipment to protect skin and eyes. Do not breathe vapor or spray. When vapors form, use respiratory protection. Ensure adequate ventilation, especially in confined areas. Keep unprotected people away.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains. In case of entry into waterways, soil or drains, inform the responsible authorities.

Methods for clean-up:

Plug leak if safely possible. Soak up with absorbent materials such as sand, siliceous earth, acid- or universal binder. Store in special closed containers and dispose of according to ordinance.

Additional information:

Special danger of slipping by leaking/spilling product.

### 7. Handling and storage

#### Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed. Handle and open container with care. Avoid contact with skin, eyes, and clothing. Take off contaminated clothing and wash it before reuse. Do not breathe vapor or spray. Wear appropriate protective equipment. When using do not eat, drink or smoke. Work place should be equipped with a shower and an eye rinsing apparatus.

Precautions against fire and explosion:

Usual measures for fire prevention.

#### Storage

Requirements for storerooms and containers:

Store in original container only. Keep container tightly closed in a cool, well-ventilated place. Keep container dry. Keep away from sources of ignition. Recommended storage temperature: 10 - 30 °C Protect from heat and direct sunlight.

Hints on joint storage:

Do not store together with strong bases, oxidizing agents, strong acids or amines. Keep away from food and drinks.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017  
Version: 3  
Language: en-US  
Date of print: Jan/10/2017

## Fast-Metal Minute Adhesive Resin

Material number 105511

Page: 4 of 9

### 8. Exposure controls / personal protection

#### Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
7727-43-7	Barium sulfate	USA: ACGIH: TWA	5 mg/m <sup>3</sup> (inhalable fraction)
		USA: NIOSH: TWA	10 mg/m <sup>3</sup> (inhalable fraction)
		USA: NIOSH: TWA	5 mg/m <sup>3</sup> (respirable fraction)
		USA: OSHA: TWA	15 mg/m <sup>3</sup> (inhalable fraction)
		USA: OSHA: TWA	5 mg/m <sup>3</sup> (respirable fraction)
1317-65-3	Limestone	USA: NIOSH: TWA	10 mg/m <sup>3</sup> inhalable fraction
		USA: NIOSH: TWA	5 mg/m <sup>3</sup> (respirable fraction)
		USA: OSHA: TWA	15 mg/m <sup>3</sup> inhalable fraction
		USA: OSHA: TWA	5 mg/m <sup>3</sup> (respirable fraction)
546-93-0	Magnesium carbonate	USA: NIOSH: TWA	10 mg/m <sup>3</sup> inhalable fraction
		USA: NIOSH: TWA	5 mg/m <sup>3</sup> (respirable fraction)
		USA: OSHA: TWA	15 mg/m <sup>3</sup> inhalable fraction
		USA: OSHA: TWA	5 mg/m <sup>3</sup> (respirable fraction)
14807-96-6	Talcum	USA: ACGIH: TWA	2 mg/m <sup>3</sup> respirable fraction
		USA: NIOSH: TWA	2 mg/m <sup>3</sup>
		USA: OSHA: TWA	20 mppcf
			Containing less than 1% quartz

#### Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

See also information in chapter 7, section storage.

#### Personal protection equipment (PPE)

Eye/face protection: Tightly sealed safety glasses

Skin protection: Wear suitable protective clothing.

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material: Nitrile rubber, Neoprene, PVC.

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

General hygiene considerations:

Avoid contact with skin, eyes, and clothing. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Eye wash facility must be provided. When using do not eat, drink or smoke. Wash hands before breaks and after work.

### 9. Physical and chemical properties

#### Information on basic physical and chemical properties

Appearance: Form: pasty  
Color: black  
Odor: characteristic  
Odor threshold: No data available



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

## Fast-Metal Minute Adhesive Resin

Material number 105511

Page: 5 of 9

pH value:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	not applicable
Flash point/flash point range:	not applicable
Evaporation rate:	No data available
Flammability:	not determined
Explosion limits:	LEL (Lower Explosion Limit): not determined UEL (Upper Explosive Limit): not determined
Vapor pressure:	at 68 °F: not determined <= 66.7 Pa
Vapor density:	not determined
Density:	approx. 1.9 g/mL
Water solubility:	soluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	not determined
Thermal decomposition:	No data available
Ignition temperature:	not determined

## 10. Stability and reactivity

Reactivity:	combustible
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Exothermic reactions with strong alkalis, strong acids, oxidizing agents and amines. Polymerization along with heat production.
Conditions to avoid:	Excessive heating, humidity. Avoid the formation of aerosol/vapors.
Incompatible materials:	Strong bases, strong oxidizing agents, strong acids, amines
Hazardous decomposition products:	In case of fire may be liberated: carbon black, Toxic gases/vapours, carbon monoxide and carbon dioxide.
Thermal decomposition:	No data available



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

## Fast-Metal Minute Adhesive Resin

Material number 105511

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

Page: 6 of 9

## 11. Toxicological information

### Toxicological tests

Toxicological effects: Acute toxicity (oral): Lack of data.  
Acute toxicity (dermal): Lack of data.  
Acute toxicity (inhalative): Lack of data.  
Skin corrosion/irritation: Skin Irritation - Category 2 = Causes skin irritation.  
Eye damage/irritation: Eye Irritation - Category 2A = Causes serious eye irritation.  
Sensitisation to the respiratory tract: Lack of data.  
Skin sensitisation: Sensitization - skin - Category 1 = May cause an allergic skin reaction.  
Germ cell mutagenicity/Genotoxicity: Lack of data.  
Carcinogenicity: Lack of data.  
Reproductive toxicity: Lack of data.  
Effects on or via lactation: Lack of data.  
Specific target organ toxicity (single exposure): Lack of data.  
Specific target organ toxicity (repeated exposure): Lack of data.  
Aspiration hazard: Lack of data.

Other information: Information about Bisphenol-A-(epichlorhydrin) epoxy resin (molecular weight <=700):  
LD50 Rat (oral): >2000 mg/kg  
LD50 Rabbit (dermal): >2000 mg/kg  
Information about Bisphenol-F-epichlorhydrine resin:  
LD50 Rat (oral): >2000 mg/kg  
LD50 Rabbit (dermal): >2000 mg/kg  
Information about 1,4-bis(2,3-Epoxypropoxy)butane:  
LD50 Rat (oral): 1134 mg/kg  
LD50 Rabbit (dermal): 1100 mg/kg

### General remarks

For carcinogenic effects:  
Information about Talcum:  
IARC Rating: Group 3  
OSHA Carcinogen: not listed  
NTP Rating: listed

## 12. Ecological information

### Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.

### Mobility in soil

No data available

### Persistence and degradability

Further details: Product is not readily biodegradable.

### Additional ecological information

General information: Do not allow to penetrate into soil, waterbodies or drains.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017  
Version: 3  
Language: en-US  
Date of print: Jan/10/2017

## Fast-Metal Minute Adhesive Resin

Material number 105511

Page: 7 of 9

### 13. Disposal considerations

#### Product

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.

#### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Do not remove label until container is thoroughly cleaned. Non-contaminated packages may be recycled.

### 14. Transport information

#### USA: Department of Transportation (DOT)

Identification number: UN3082  
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Reaction product with Bisphenol A-epichlorhydrin epoxy resin (molecular weight = 700), Bisphenol-F-epichlorhydrine resin)  
Hazard class or Division: 9  
Packing Group: III  
Labels: 9  
Symbols: G  
Special provisions: 8, 146, 173, 335, IB3, T4, TP1, TP29  
Packaging – Exceptions: 155  
Packaging – Non-bulk: 203  
Packaging – Bulk: 241  
Quantity limitations – Passenger aircraft / rail: No limit  
Quantity limitations – Cargo only: No limit  
Vessel stowage – Location: A



#### Sea transport (IMDG)

UN number: UN 3082  
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Reaction product with Bisphenol A-epichlorhydrin epoxy resin (molecular weight = 700), Bisphenol-F-epichlorhydrine resin)  
Class or division, Subsidiary risk: Class 9, Subrisk-  
Packing Group: III  
EmS: F-A, S-F  
Special provisions: 274, 335, 969  
Limited quantities: 5 L  
Excepted quantities: E1  
Contaminated packaging - Instructions: P001, LP01  
Contaminated packaging - Provisions: PP1  
IBC - Instructions: IBC03  
IBC - Provisions: -  
Tank instructions - IMO: -  
Tank instructions - UN: T4  
Tank instructions - Provisions: TP2, TP29  
Stowage and handling: Category A.  
Properties and observations: -  
Marine pollutant: yes  
Segregation group: none



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017  
Version: 3  
Language: en-US  
Date of print: Jan/10/2017

## Fast-Metal Minute Adhesive Resin

Material number 105511

Page: 8 of 9

### Air transport (IATA)

UN/ID number: UN 3082  
Proper shipping name: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Reaction product with Bisphenol A-epichlorhydrin epoxy resin (molecular weight = 700), Bisphenol-F-epichlorhydrine resin)  
Class or division, Subsidiary risk: Class 9  
Packing Group: III  
Hazard label: Miscellaneous  
Excepted Quantity Code: E1  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y964 - Max. Net Qty/Pkg. 30 kg G  
Passenger and Cargo Aircraft: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L  
Cargo Aircraft only: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L  
Special provisions: A97 A158 A197  
Emergency Response Guide-Code (ERG): 9L

## 15. Regulatory information

### National regulations - U.S. Federal Regulations

Reaction product: TSCA Inventory: listed; EPA flags XU  
Bisphenol-A-(epichlorhydrin) epoxy resin: TSCA HPVC: not listed  
(number average molecular weight <=700):  
Barium sulfate: TSCA Inventory: listed  
TSCA HPVC: not listed  
NIOSH Recommendations:  
Occupational Health Guideline: 0047  
Limestone: TSCA Inventory: listed; UVCB  
TSCA HPVC: not listed  
NIOSH Recommendations:  
Occupational Health Guideline: 0090\*  
Bisphenol-F-epichlorhydrine resin: TSCA Inventory: listed; UVCB; EPA flags XU  
TSCA HPVC: not listed  
Benzyl alcohol: TSCA Inventory: listed  
TSCA HPVC: not listed  
Clean Air Act:  
SOCMI Chemical: yes  
Other Environmental Laws:  
RCRA Groundwater Monitoring: Methods 8270 / PQL 20  
Magnesium carbonate: TSCA Inventory: listed  
TSCA HPVC: not listed  
NIOSH Recommendations:  
Occupational Health Guideline: 0373  
Talcum: TSCA Inventory: listed  
TSCA HPVC: not listed  
Carcinogen Status:  
IARC Rating: Group 3  
OSHA Carcinogen: not listed  
NTP Rating: not listed  
NIOSH Recommendations:  
Occupational Health Guideline: 0584  
1,4-bis(2,3-Epoxypropoxy)butane: TSCA Inventory: listed; EPA flags T  
TSCA HPVC: not listed  
TSCA: listed





# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

## Fast-Metal Minute Adhesive Resin

Material number 105511

Page: 9 of 9

### National regulations - U.S. State Regulations

Barium sulfate:

California Proposition 65 code: not listed  
Massachusetts Haz. Substance codes: 4  
Minnesota Haz. Substance:  
Codes: A - Ratings: --  
Pennsylvania Haz. Substance code: -  
Washington Air Contaminant:  
TWA: 10 mg

Benzyl alcohol:

Massachusetts Haz. Substance codes: 6  
Pennsylvania Haz. Substance code: -

Talcum:

California Proposition 65 code: not listed  
Massachusetts Haz. Substance codes: 2,4 F5  
Minnesota Haz. Substance:  
Codes: AO - Ratings: --  
Pennsylvania Haz. Substance code: -  
Washington Air Contaminant:  
TWA: 2mg  
Wisconsin Hazardous Air Contaminant List (Appears on Table): A

### National regulations - Great Britain


Hazchem-Code: •3Z

## 16. Other information

Text for labeling:

Contains 30 - 50 % Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700), 1 - 5 % Bisphenol-F-epichlorhydrine resin, 1 - 5 % Benzyl alcohol, 1 - 5 % 1,4-bis(2,3-Epoxypropoxy)butane. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:

Health: 2 (Moderate)

Fire: 1 (Slight)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 2 (Moderate)

Flammability: 1 (Slight)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0
X	

Reason of change:

ADR/RID 2017

Date of first version:

Oct/8/2015

### Department issuing data sheet

Contact person:

see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.