

# AL-W High Performance Grease



## special lubricant for underwater applications

AL-W high performance grease is a special lubricant and corrosion protection which can also be used for underwater applications. WEICON AL-W offers effective protection against aggressive liquids such as sea or wastewater, both in the maritime sector and in wet plants.

WEICON AL-W is suitable for rolling and sliding bearings even in mixed friction operation, for joints, levers, sliding guides, spindles, spline shafts, open gears, worm gears, chains and wire cables and at all sliding speeds permitted for grease lubrication.

## Technical Data

Abbreviation (DIN 51502)	KPL 1-2 E -25
Consistency assignment (DIN 51818)	NLGI-Class 1-2
Composition	Spec. calcium soap / mineral oil
Colour	beige
Density at +20°C (+68°F) (DIN 51757)	0,94 g/cm <sup>3</sup>
VKA-TEST (DIN 51350) welding load	3.400 N
VKA-TEST (DIN 51350) goods load	3.200 N
VKA-TEST (DIN 51350) Spherical cap value (1Min/1000N)	0,7 mm
Speed identifying value	350.000
Worked penetration (DIN ISO 2137)	285 -315 1/10 mm
Water resistance (DIN 51807)	0 - 40
Drop Point (IP 396)	>100 °C
Kinematic viscosity (DIN 51562) at +40°C	100 mm <sup>2</sup> /s
Kinematic viscosity (DIN 51562) at +100°C	9 mm <sup>2</sup> /s

## Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

Storage stability	no corrosion
Storage stability	0 / 0
Conforms to	Federal German Armed Forces TL 9150-0066, NATO specification G-460
Storage stability	24 months
Temperature resistance	-25 to +80 °C
ISSA-Code	53.052.10/11
IMPA-Code	45 04 37/38

## Surface pre-treatment

Clean surfaces.

## Processing

Apply AL-W evenly.

## Storage

Keep in closed original container. Do not store together with oxidizing agents. Keep container tightly closed and store at cool and aired place. Recommended storage temperature: room temperature.

## Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

## Available sizes:

26450040	AL-W High Performance Grease 400 g
26450100	AL-W High Performance Grease 1.0 kg
26450500	AL-W High Performance Grease 5.0 kg
26450925	AL-W High Performance Grease 25.0 kg

## Accessories:

10953001	Processing Spatula, short
10953003	Processing Spatula, long
11850200	Hand Protective Foam, 200 ml
15200005	WEICON Cleaner S, 5 L

WEICON GmbH & Co. KG  
(Headquarters)  
Germany  
phone +49 (0) 251 9322 0  
info@weicon.de

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
info@weicon.ae

WEICON Inc.  
Canada  
phone +1 877 620 8889  
info@weicon.ca  
www.weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Turkey  
phone +90 (0) 212 465 33 65  
info@weicon.com.tr  
www.weicon.com.tr

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
office@weicon.com

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
info@weicon.co.za

WEICON South East Asia Pte Ltd  
Singapore  
phone (+65) 6710 7671  
info@weicon.com.sg

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
info@weiconcz.cz

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
info@weicon.es