



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

Contact VA 100

Material number 120500

Page: 1 of 9

1. Product and company identification

Product identifier

Trade name: Contact VA 100

Relevant identified uses of the substance or mixture and uses advised against

General use: Adhesive.
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: WEICON Inc.
Street/POB-No.: 20 Steckle Place, Unit 20
Postal Code, city: Kitchener, Ontario N2E 2C3, CA
WWW: www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254
Dept. responsible for information:
Product-Safety-Department
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

Emergency phone number

EMERGENCY CONTACT – Canada (24h): Tel: ++1 866 928 0789 (Toll free)

Transport:

TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: ++1 866 928 0789 (Toll free)

2. Hazards identification

Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: liquid
Color: colorless
Odor: characteristic, stinging
Classification: Flammable Liquid 4; Skin Irritation 2; Eye Irritation 2A;
Specific Target Organ Toxicity (Single Exposure) 3;

Hazard symbols:



Signal word:

Warning

Hazard statements:

Combustible liquid.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017
Version: 5
Language: en-CA,US
Date of print: 10/Jan/2017

Contact VA 100

Material number 120500

Page: 2 of 9

Precautionary statements: Keep out of reach of children.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash hands and face thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
IF ON SKIN: Wash with plenty of water/soap.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a POISON CENTER/doctor if you feel unwell.
Specific treatment (see ' First aid ' on this label).
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing.
In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

Contains Ethyl 2-cyanoacrylate. Cyanacrylate - Danger - skin and eyelids will stick together in seconds. Keep out of the reach of children.
Potentially explosive mixtures may form if adequate ventilation is not provided.
Higher doses may have a narcotic effect.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterisation: Adhesive based on cyanoacrylic acid ester.

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 7085-85-0	Ethyl 2-cyanoacrylate	80 - 99.9 %	Flammable Liquid 4. Skin Irritation 2. Eye Irritation 2A. Specific Target Organ Toxicity (Single Exposure) 3.

4. First aid measures

General information: Cyanacrylate - Danger - skin and eyelids will stick together in seconds. Take off immediately all contaminated clothing.

In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing. If breathing has stopped, give artificial respiration immediately. Seek medical attention.

Following skin contact: Do not peel solidified product off the skin. Immediately clean with water and soap or cleanse with acetone followed by thorough rinsing. If product comes into contact with lips, hold mouth open. Do not allow lips to contact one another. Immediately get medical attention.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

Contact VA 100

Material number 120500

Page:

3 of 9

After eye contact: Keep eye wide open. Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.
Do not attempt to pull apart bonded eyelid. Subsequently seek the immediate attention of an ophthalmologist.

After swallowing: Do not induce vomiting. Keep airway open. Immediately get medical attention.

Most important symptoms and effects, both acute and delayed

May cause respiratory irritation. Causes skin irritation. Causes serious eye irritation.
Higher doses may have a narcotic effect.
Cough, shortage of breath, respiratory complaints.

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:

82.5 °C

Auto-ignition temperature: 480 °C

Suitable extinguishing media:

Water fog, extinguishing powder, alcohol resistant foam, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

High power water jet.

Specific hazards arising from the chemical

Combustible liquid. In case of fire may be liberated: Cyanide, nitrogen oxides (NO_x), carbon monoxide and carbon dioxide.

May form dangerous gases and vapours in case of fire.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Heating will lead to pressure increase: Danger of bursting and explosion. Cool exposed containers with water spray.

Move undamaged containers from immediate hazard area if it can be done safely.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

6. Accidental release measures

Personal precautions:

Cyanacrylate - Danger - skin and eyelids will stick together in seconds.

Avoid contact with skin, eyes, and clothing.

Provide adequate ventilation. Do not breathe vapor.

Wear appropriate protective equipment. Keep unprotected people away.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains. Danger of explosion!

In case of release, notify competent authorities.

Methods for clean-up:

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Beware of reignition. Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

Contact VA 100

Material number 120500

Page: 4 of 9

Additional information: Use explosion-proof equipment and non-sparking tools/utensils.

7. Handling and storage

Handling

Advices on safe handling: Provide good ventilation and/or an exhaust system in the work area.
Handle and open container with care. Avoid contact with skin, eyes, and clothing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water and soap/shower.
Do not breathe gas/fume/vapour/spray. Wear appropriate protective equipment. Wash hands before breaks and after work.
Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.

Precautions against fire and explosion:
Take care of general rules for industrial preventive fire protection.
Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.
Use only explosion-protected equipment/instruments. Do not weld.
In partially filled containers explosive mixtures may form.

Storage

Requirements for storerooms and containers:
Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from heat and direct sunlight.
Store containers in upright position. Explosion protection required. Protect from moisture contamination.

Hints on joint storage:
Do not store together with combustible or self-igniting materials or any highly flammable solids.
Do not store together with alkalis, oxidizing agents, amines or acids.
Keep away from food, drink and animal feedingstuffs.

Further details:
Before opening the container let the product reach room temperature as otherwise the formation of dew might be resulting.
Do not return unused portions of product to original container.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
7085-85-0	Ethyl 2-cyanoacrylate	Canada, Alberta: OEL 8 hour	1 mg/m ³ ; 0.2 ppm
		Canada, BC: OEL TWA	0.2 ppm
		USA: ACGIH: TWA	1 mg/m ³ ; 0.2 ppm

Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Explosion protection required.
See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Wear suitable protective clothing.
Recommendation: Flame retardant, antistatic and chemical resistant protective clothing.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

Contact VA 100

Material number 120500

Page:

5 of 9

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material: Nitrile rubber

Layer thickness: > 0.4 mm

Breakthrough time: > 60 min

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Provide adequate ventilation. If necessary: Respiratory protection mask. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

General hygiene considerations:

Cyanacrylate - Danger - skin and eyelids will stick together in seconds. Keep out of the reach of children.

Do not breathe gas/fume/vapour/spray. Avoid contact with skin, eyes, and clothing.

When using do not eat or drink. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water and soap/shower. Wash contaminated clothing before reuse.

Wash hands before breaks and after work. Use only non-sparking tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Work place should be equipped with a shower and an eye rinsing apparatus.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Color: colorless
Odor:	characteristic, stinging
Odor threshold:	No data available
pH value:	No data available
Melting point/freezing point:	-31 °C (1003 mbar)
Initial boiling point and boiling range:	> 214 °C
Flash point/flash point range:	82.5 °C
Evaporation rate:	No data available
Flammability:	Combustible liquid.
Explosion limits:	LEL (Lower Explosion Limit): not applicable UEL (Upper Explosive Limit): not applicable
Vapor pressure:	<= 21 Pa
Vapor density:	No data available
Density:	at 20 °C: 1.043 g/mL
Solubility:	91.8 mg/L (Acetone)
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	480 °C
Thermal decomposition:	No data available
Viscosity, dynamic:	2.6 mPa*s
Explosive properties:	Product is not explosive. Vapors may form explosive mixtures with air.
Oxidizing characteristics:	not oxidising



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

Contact VA 100

Material number 120500

Page:

6 of 9

10. Stability and reactivity

- Reactivity:** Combustible liquid.
Vapors may form explosive mixtures with air.
Explosive reaction with water.
- Chemical stability:** Stable under recommended storage conditions.
- Possibility of hazardous reactions**
Heating will lead to pressure increase: Danger of bursting and explosion.
At heat, humidity: Polymerization along with heat production.
May polymerize under the influence of light.
- Conditions to avoid:** Protect from moisture contamination. Keep away from heat sources, sparks and open flames.
Protect against direct sunlight.
- Incompatible materials:** Alkalis, oxidizing agents, amines, water, acids, strong bases.
- Hazardous decomposition products:**
In case of fire may be liberated: Cyanide, nitrogen oxides (NOx), carbon monoxide and carbon dioxide.
May form dangerous gases and vapours in case of fire.
- Thermal decomposition:** No data available

11. Toxicological information

Toxicological tests

- Toxicological effects:** The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
Acute toxicity (oral): Based on available data, the classification criteria are not met.
ATEmix (calculated): ATE > 5000 mg/kg.
Acute toxicity (dermal): Based on available data, the classification criteria are not met.
ATEmix (calculated): ATE > 2000 mg/kg.
Acute toxicity (inhalative): Lack of data.
Skin corrosion/irritation: Skin Irritation 2 = Causes skin irritation.
Eye damage/irritation: Eye Irritation 2A = Causes serious eye irritation.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Lack of data.
Information about Ethyl 2-cyanoacrylate: not sensitising.
Sensitization has been observed only in sensitive humans.
Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) 3 = May cause respiratory irritation.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.
- Other information:** Information about Ethyl 2-cyanoacrylate:
Acute oral toxicity: LD50, Rat: > 5000 mg/kg (OECD 401)
Acute dermal toxicity: LD50, Rabbit: > 2000 mg/kg (OECD 402)



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

Contact VA 100

Material number 120500

Page: 7 of 9

Symptoms

Cough, shortage of breath, respiratory complaints.

12. Ecological information

Ecotoxicity

Further details: No data available

Mobility in soil

No data available

Persistence and degradability

Further details: Due to the consistency along with the low water solubility of the product a bioavailability is unlikely.

Additional ecological information

AOX reference: Ecotoxicological effects: The product has not been tested.
The statement is derived from products of similar structure or composition.

Volatile organic compounds (VOC):
21.2 g/L = 2%

General information: Do not allow uncontrolled discharge of product into the environment.
Do not allow to penetrate into soil, waterbodies or drains.

13. Disposal considerations

Product

Recommendation: Dispose of waste according to applicable legislation. Do not allow to enter into ground-water, surface water or drains.

Contaminated packaging

Recommendation: Handle empty containers with care. Incineration may cause explosion.
Dispose of waste according to applicable legislation.
Handle contaminated packages in the same way as the substance itself.
Non-contaminated packages may be recycled.

14. Transport information

USA: Department of Transportation (DOT)

Identification number: UN1133
Proper shipping name: UN 1133, adhesives
Hazard class or Division: 3
Packing Group: III
Labels: 3
Special provisions: B1, B52, IB3, T2, TP1
Packaging – Exceptions: 150
Packaging – Non-bulk: 173
Packaging – Bulk: 242
Quantity limitations – Passenger aircraft / rail: 60 L
Quantity limitations – Cargo only: 220 L
Vessel stowage – Location: A
Vessel stowage – Other:





SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

Contact VA 100

Material number 120500

Page: 8 of 9

Canada: Transportation of Dangerous Goods (TDG)

UN Number: UN1133
 Shipping name: UN 1133, adhesives
 TDG class: 3
 Packing group: III
 Explosive limit and limited quantity index: 5L
 Passenger carrying road or rail index: 60L

Sea transport (IMDG)

Proper shipping name: Not restricted
 Marine pollutant: no

Air transport (IATA)

UN/ID number: UN 3334
 Proper shipping name: UN 3334, AVIATION REGULATED LIQUID, N.O.S. (Ethyl 2-cyanoacrylate)
 Class or division, Subsidiary risk: Class 9
 Packing Group: III
 Hazard label: Miscellaneous
 Excepted Quantity Code: E1
 Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y964 - Max. Net Qty/Pkg. 30 kg G
 Passenger and Cargo Aircraft: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
 Cargo Aircraft only: Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L
 Special provisions: A27
 Emergency Response Guide-Code (ERG): 9A

15. Regulatory information

National regulations - Canada

No data available

National regulations - U.S. Federal Regulations

Ethyl 2-cyanoacrylate: TSCA Inventory: listed
 TSCA HPVC: not listed


National regulations - U.S. State Regulations

Ethyl 2-cyanoacrylate: California Proposition 65: Not listed.

16. Other information

Text for labeling: Contains 80 - 99.9 % Ethyl 2-cyanoacrylate. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:

Health: 2 (Moderate)
 Fire: 2 (Moderate)
 Reactivity: 2 (Moderate)

HMIS Version III Rating:

Health: 2 (Moderate)
 Flammability: 2 (Moderate)
 Physical Hazard: 2 (Moderate)
 Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	2
	X

Reason of change: IATA-DGR 2017

Date of first version: 22/Oct/2015

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 5

Language: en-CA,US

Date of print: 10/Jan/2017

Contact VA 100

Material number 120500

Page: 9 of 9

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.