



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

Flex 310 M Liquid

Material number 133040

Page:

1 of 7

1. Product and company identification

Product identifier

Trade name: Flex 310 M Liquid

Relevant identified uses of the substance or mixture and uses advised against

General use: One-component adhesive and sealing agent, elastic
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: WEICON Inc.
Street/POB-No.: 20 Steckle Place, Unit 20
Postal Code, city: Kitchener, Ontario N2E 2C3, CA
WWW: www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254
Dept. responsible for information:
Product-Safety-Department
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

Emergency phone number

EMERGENCY CONTACT – USA (24h): Tel: ++1 202 464 2554

Transport:

TRANSPORT EMERGENCY CONTACT - USA (24h): Tel: ++1 202 464 2554

2. Hazards identification

Emergency overview

Appearance: Form: pasty
Color: white
Odor: characteristic
Classification: This material is classified as not hazardous.

Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

With exposure to Water, product will release Methanol.
Methanol: Toxic by inhalation, in contact with skin and if swallowed.
Special danger of slipping by leaking/spilling product.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterization: Mixture of the substance mentioned below with non-hazardous additions.

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 90622-57-4	Hydrocarbons, C11-C12, isoalkanes, aromatic contents: < 2%	< 10 %	Flammable Liquid - Category 3. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 4.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Flex 310 M Liquid

Material number 133040

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

Page: 2 of 7

Additional information: After contact with water: Formation of methanol.
The maximum workplace exposure limits are, where necessary, listed in section 8.

4. First aid measures

General information: Take off immediately all contaminated clothing.
In case of inhalation: Provide fresh air. Seek medical treatment in case of troubles.
Following skin contact: Remove mechanically (e.g. dab away using wadding or cellulose material) then thoroughly wash the affected skin with a mild cleansing agent and water. Seek medical attention if problems persist.
After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing: Do not induce vomiting. Immediately get medical attention.

Most important symptoms/effects, acute and delayed

After contact with skin:
Frequently or prolonged contact with skin may cause dermal irritation.

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range: not applicable
Auto-ignition temperature: not determined
Suitable extinguishing media: Water fog, alcohol resistant foam, dry chemical powder, carbon dioxide.
Extinguishing media which must not be used for safety reasons: Full water jet

Specific hazards arising from the chemical

May form dangerous gases and vapours in case of fire.
Nitrous fumes, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information: You have to dispose of contaminated extinguishing water according to the regulations of the authorities.

6. Accidental release measures

Personal precautions: Provide adequate ventilation. Do not breathe gas/vapor/spray.
Avoid contact with skin and eyes. Wear appropriate protective equipment.
Wear respiratory protection when in the presence of vapor, dust, and aerosols.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.

Methods for clean-up: Take up mechanically, placing in appropriate containers for disposal.

Additional information: During hydrolysis, a small amount of methanol is produced.
Special danger of slipping by leaking/spilling product.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

Flex 310 M Liquid

Material number 133040

Page:

3 of 7

7. Handling and storage

Handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.
Do not breathe gas/vapor/spray. Wear appropriate protective equipment.
Avoid contact with skin and eyes.
Keep away from sources of ignition - No smoking.
Take off immediately all contaminated clothing.

Precautions against fire and explosion:
Keep away from sources of ignition - No smoking.
Vapors may form explosive mixtures with air.
Take precautionary measures against static discharges.

Storage

Requirements for storerooms and containers:
Keep container tightly closed in a cool, well-ventilated place. Keep only in original packaging.
Protect from moisture contamination. Protect from frost, heat and sunlight.

Hints on joint storage: Do not store together with acids and strong oxidizing agents.
Keep away from food, drink and animal feedingstuffs.

Further details: During hydrolysis, a small amount of methanol is produced.
Do not allow the product to enter the ground.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
67-56-1	Methanol	USA: ACGIH: STEL	328 mg/m ³ ; 250 ppm (May be absorbed through the skin.)
		USA: ACGIH: TWA	262 mg/m ³ ; 200 ppm (May be absorbed through the skin.)
		USA: NIOSH: STEL	325 mg/m ³ ; 250 ppm (May be absorbed through the skin.)
		USA: NIOSH: TWA	260 mg/m ³ ; 200 ppm (May be absorbed through the skin.)
		USA: OSHA: TWA	260 mg/m ³ ; 200 ppm

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
67-56-1	Methanol	USA: ACGIH-BEI, urine	15 mg/L	Methanol	end of exposure or end of shift

Engineering controls

Provide adequate ventilation, and local exhaust as needed.
See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Wear suitable protective clothing.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

Flex 310 M Liquid

Material number 133040

Page:

4 of 7

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material: Nitrile rubber - Layer thickness: 0.8 mm

Breakthrough time: 480 min.

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.

Respiratory protection in case of aerosol or vapor formation.

The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.

General hygiene considerations:

Do not breathe vapor or spray. Avoid contact with skin and eyes.

Take off immediately all contaminated clothing. Keep away from sources of ignition - No smoking.

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Form: pasty Color: white
Odor:	characteristic
Odor threshold:	not determined
pH value:	not determined
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	not determined
Flash point/flash point range:	not applicable
Evaporation rate:	No data available
Flammability:	not applicable
Explosion limits:	LEL (Lower Explosion Limit): 0.10 Vol-% UEL (Upper Explosive Limit): 7.00 Vol-%
Vapor pressure:	at 68 °F: <= 100 hPa
Vapor density:	not determined
Density:	at 68 °F: approx. 1.48 g/cm ³
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	not determined
Auto-ignition temperature:	not determined
Thermal decomposition:	No data available
Viscosity, kinematic:	not determined
Explosive properties:	Product is not explosive. Vapors may form explosive mixtures with air.
Ignition temperature:	> 392 °F
Solvent content:	5 %

10. Stability and reactivity

Reactivity: Vapors may form explosive mixtures with air.

Chemical stability: Stable under recommended storage conditions.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

Flex 310 M Liquid

Material number 133040

Page:

5 of 7

Possibility of hazardous reactions

Reacts with: Acids, strong oxidizing agents.
Contact with water liberates methanol.

Conditions to avoid:

Protect from moisture contamination.
Protect from frost, heat and sunlight.

Incompatible materials:

Strong oxidizing agents, acids, water.

Hazardous decomposition products:

In case of fire may be liberated: Nitrous fumes, carbon monoxide and carbon dioxide.
During hydrolysis, a small amount of methanol is produced.

Thermal decomposition:

No data available

11. Toxicological information

Toxicological tests

Toxicological effects:

The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Minor irritation effect - does not require labeling.

Eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

Other information:

Further hazardous properties cannot be excluded.

Symptoms

After contact with skin:

Frequently or prolonged contact with skin may cause dermal irritation.

General remarks

Handle in accordance with good industrial hygiene and safety practice.

12. Ecological information

Ecotoxicity

Further details:

No data available

Mobility in soil

No data available

Persistence and degradability

Further details:

No data available



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

Flex 310 M Liquid

Material number 133040

Page: 6 of 7

Additional ecological information

Volatile organic compounds (VOC):

5.02 % by weight = 74.3 g/L

General information:

Do not allow to enter into ground-water, surface water or drains. No ecotoxic effects are known for this product.

13. Disposal considerations

Product

Recommendation: Dispose of as hazardous waste. Dispose of waste according to applicable legislation.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.
Handle contaminated packages in the same way as the substance itself.
Non-contaminated packages may be recycled.

14. Transport information

USA: Department of Transportation (DOT)

Proper shipping name: Not restricted

Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant: no

Air transport (IATA)

Proper shipping name: Not restricted

Further information

No dangerous good in sense of these transport regulations.

15. Regulatory information

National regulations - U.S. Federal Regulations

Product: TSCA Inventory: not listed

Methanol: Clean Air Act:

Hazardous Air Pollutants: Code XO V

SOCMI Chemical: yes

Other Environmental Laws:

CERCLA: RQ 5000 lbs.

RCRA Hazardous Wastes: Code U154

SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard

NIOSH Recommendations:

Occupational Health Guideline: 0397



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Flex 310 M Liquid

Material number 133040

Revision date: Aug/5/2016

Version: 2

Language: en-US

Date of print: Aug/11/2016

Page: 7 of 7

National regulations - U.S. State Regulations

Methanol:


California Proposition 65 code: -
 Delaware Air Quality Management List:
 DRQ: 5000 - RQ State: Federal Regulations Apply
 Idaho Air Pollutant List:
 Title 585: AAC: 13 - EL: 17,3 - OEL: 260 - Title 586: -
 Main Hazardous Air Pollutants:
 Me 2005: HAP - Hap Rpt: 2000
 Massachusetts Haz. Substance codes: 2,4,5,6 F8 F9
 Minnesota Haz. Substance:
 Codes: ANO - Ratings: 7,5 - Status: Air Pollutant Title III. TRI.
 New Jersey RTK Hazardous Substance:
 DOT: 1230 - Sub No.: 1222 - TPQ: -
 New York List of Hazardous Substances:
 RQ-Air: 5000 - RQ-Land: 1 - Note: No Note Associated with this chemical.
 Pennsylvania Haz. Substance code: E
 Washington Air Contaminant:
 TWA: 200 ppm - 260 mg - STEL: 250 ppm - 325 mg
 Skin: Protective measures should be taken to prevent or reduce skin absorption.
 California Proposition 65: developmental
 Rhode Island HSL: listed

National regulations - Great Britain

Hazchem-Code: -

16. Other information

Hazard rating systems:



NFPA Hazard Rating:
 Health: 1 (Slight)
 Fire: 1 (Slight)
 Reactivity: 1 (Slight)

HMIS Version III Rating:
 Health: 1 (Slight)
 Flammability: 1 (Slight)
 Physical Hazard: 1 (Slight)
 Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	1
	X

Reason of change: Changes in section 1: General revision

Date of first version: Mar/15/2016

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.