



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 5/Aug/2016

Version: 2

Language: en-CA,US

Date of print: 11/Aug/2016

Repair Stick Copper

Material number 105300

Page: 1 of 9

1. Product and company identification

Product identifier

Trade name: Repair Stick Copper

Relevant identified uses of the substance or mixture and uses advised against

General use: Two-component epoxy resins.
Reserved for industrial and professional use.

Details of the supplier of the safety data sheet

Company name: WEICON Inc.
Street/POB-No.: 20 Steckle Place, Unit 20
Postal Code, city: Kitchener, Ontario N2E 2C3, CA
WWW: www.weicon.ca
E-mail: info@weicon.ca
Telephone: +1-519-896-5252
Telefax: +1-519-896-5254
Dept. responsible for information:
Product-Safety-Department
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

Emergency phone number

EMERGENCY CONTACT – Canada (24h): Tel: ++1 866 928 0789 (Toll free)

Transport:

TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: ++1 866 928 0789 (Toll free)

2. Hazards identification

Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: solid
Form: pasty
Color: copper-coloured
Odor: slightly perceptible
Classification: Skin Irritation 2; Eye Irritation 2A; Sensitization - skin 1; Aquatic toxicity - chronic 3;

Hazard symbols:



Signal word:

Warning

Hazard statements:

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful to aquatic life with long lasting effects.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Repair Stick Copper

Material number 105300

Revision date: 5/Aug/2016
Version: 2
Language: en-CA,US
Date of print: 11/Aug/2016

Page: 2 of 9

Precautionary statements: Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash hands and face thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection.
IF ON SKIN: Wash with plenty of water/soap.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see 'First aid' on this label).
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing.
Wash contaminated clothing before reuse.
Dispose of contents/container to hazardous or special waste collection point.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterisation: Two-component epoxy resins

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 14807-96-6	Talcum	20 - 50 %	not applicable
CAS 25068-38-6	Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700)	10 - 20 %	Skin Irritation 2. Eye Irritation 2A. Sensitization - skin 1. Aquatic toxicity - chronic 2.
CAS 90-72-2	2,4,6-tris (Dimethylaminomethyl) phenol	< 5 %	Acute Toxicity 4 (oral). Skin Irritation 2. Eye Irritation 2A.
CAS 7440-50-8	Copper	1 - 5 %	Aquatic toxicity - acute 1. Aquatic toxicity - chronic 3.

Additional information: Information about Copper: M-factor =1

4. First aid measures

General information: Remove all contaminated clothes and footwear immediately unless stuck to skin.
Wash contaminated clothing before reuse.

In case of inhalation: Provide fresh air. Seek medical treatment in case of troubles.

Following skin contact: After contact with skin, wash immediately with soap and plenty of water. In case of skin reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.
Subsequently seek the immediate attention of an ophthalmologist.

After swallowing: Do not induce vomiting. Rinse mouth with water. Immediately get medical attention.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 5/Aug/2016

Version: 2

Language: en-CA,US

Date of print: 11/Aug/2016

Repair Stick Copper

Material number 105300

Page: 3 of 9

Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
Vomiting

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:

> 100 °C

Auto-ignition temperature: not determined

Suitable extinguishing media:

Alcohol resistant foam, dry extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Water

Specific hazards arising from the chemical

Hazardous vapors may form during fires. In case of fire may be liberated: nitrogen oxides (NO_x), carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing. In case of fire and/or explosion do not breathe fumes.

Additional information:

You have to dispose of contaminated extinguishing water according to the regulations of the authorities.

6. Accidental release measures

Personal precautions:

Provide adequate ventilation. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.
Keep unprotected people away. Avoid contact with skin and eyes.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains.
If necessary notify appropriate authorities.

Methods for clean-up:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal.

7. Handling and storage

Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed. Avoid contact with skin and eyes.

Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Wash hands before breaks and after work.

Precautions against fire and explosion:

Take care of general rules for industrial preventive fire protection.

Storage

Requirements for storerooms and containers:

Keep only in the original container. Protect from heat and direct sunlight.

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry.

Hints on joint storage:

Avoid contact with strong oxidizing agents, acids and amines.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Repair Stick Copper

Material number 105300

Revision date: 5/Aug/2016

Version: 2

Language: en-CA,US

Date of print: 11/Aug/2016

Page:

4 of 9

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
14807-96-6	Talcum	Canada, Alberta: OEL 8 hour	2 mg/m ³ (respirable fraction)
		Canada, BC: OEL TWA	0.1 fibers/cm ³ (Containing asbestos fibres)
		Canada, BC: OEL TWA	2 mg/m ³ respirable fraction (Containing no asbestos fibres)
		Canada, Ontario: OEL TWA	2 fibers/cm ³
		Canada, Ontario: OEL TWA	2 mg/m ³ respirable fraction
		Canada, Québec: VEMP	3 mg/m ³ (respirable fraction)
		USA: ACGIH: TWA	2 mg/m ³ respirable fraction
		USA: NIOSH: TWA	2 mg/m ³
		USA: OSHA: TWA	20 mppcf Containing less than 1% quartz
		7440-50-8	Copper
Canada, Alberta: OEL 8 hour	1 mg/m ³ Dusts and mist		
Canada, BC: OEL TWA	0.2 mg/m ³ Smoke		
Canada, BC: OEL TWA	1 mg/m ³		
Canada, Québec: VEMP	0.2 mg/m ³ (Smoke, calculated as Cu)		
Canada, Québec: VEMP	1 mg/m ³ (Dusts and mist, calculated as Cu)		
USA: ACGIH: TWA	0.2 mg/m ³ Smoke		
USA: ACGIH: TWA	1 mg/m ³ Dusts and mist calculated as Cu		
USA: NIOSH: TWA	1 mg/m ³		
USA: OSHA: TWA	0.1 mg/m ³ (Smoke; calculated as Cu)		
USA: OSHA: TWA	1 mg/m ³ Dusts and mist calculated as Cu		

Engineering controls

Provide good ventilation and/or an exhaust system in the work area.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Wear suitable protective clothing.

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material: Nitrile rubber - Layer thickness: 0.4 mm.

Breakthrough time: > 480 min.

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.

General hygiene considerations:

Avoid contact with skin and eyes. Eye wash facility must be provided.

Take off immediately all contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Wash hands before breaks and after work.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Repair Stick Copper

Material number 105300

Revision date: 5/Aug/2016

Version: 2

Language: en-CA,US

Date of print: 11/Aug/2016

Page: 5 of 9

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: solid Form: pasty Color: copper-coloured
Odor:	slightly perceptible
Odor threshold:	not determined
pH value:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	> 35 °C (approx. 1010 hPa)
Flash point/flash point range:	> 100 °C
Evaporation rate:	not applicable
Flammability:	not determined
Explosion limits:	LEL (Lower Explosion Limit): not determined UEL (Upper Explosive Limit): not determined
Vapor pressure:	at 20 °C: <= 5 hPa
Vapor density:	No data available
Density:	at 20 °C: approx. 2.0 g/cm ³
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	(estimated) 3.242 log P(o/w) (Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700)) Based on the n-octanol/water partition coefficient significant accumulation in organisms is not expected.
Auto-ignition temperature:	not determined
Thermal decomposition:	No decomposition when used properly.
Viscosity, dynamic:	not applicable
Explosive properties:	not applicable

10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Reactions with acids and strong oxidizing agents.
Conditions to avoid:	Protect from heat and direct sunlight. Protect from moisture contamination.
Incompatible materials:	Avoid contact with strong oxidizing agents, acids and amines.
Hazardous decomposition products:	In case of fire may be liberated: nitrogen oxides (NO _x), carbon monoxide and carbon dioxide.
Thermal decomposition:	No decomposition when used properly.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Repair Stick Copper

Material number 105300

Revision date: 5/Aug/2016

Version: 2

Language: en-CA,US

Date of print: 11/Aug/2016

Page: 6 of 9

11. Toxicological information

Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
Acute toxicity (oral): Based on available data, the classification criteria are not met.
ATEmix calculated: > 5000 mg/kg.
Acute toxicity (dermal): Lack of data..
Acute toxicity (inhalative): Lack of data.
Skin corrosion/irritation: Skin Irritation 2 = Causes skin irritation.
Eye damage/irritation: Eye Irritation 2A = Causes serious eye irritation.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Sensitization - skin 1 = May cause an allergic skin reaction.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Lack of data.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

Other information: Information about 2,4,6-tris(Dimethylaminomethyl)phenol:
LD50 Rat, oral: 1670 mg/kg
LD50 Rat, dermal: > 1 mg/kg
Information about Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700):
LD50, oral, Rat (OECD 420): >2000 mg/kg
LD50, dermal, Rabbit (OECD 402): >2000 mg/kg
Information about Talkum:
For carcinogenic effects:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed

Symptoms

Vomiting

12. Ecological information

Ecotoxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.
Information about Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700):
Fish toxicity:
LC50 Oncorhynchus mykiss: 2 mg/L/96h.
Daphnia toxicity:
EC50 Daphnia magna (Big water flea): 1.8 mg/L/48h (OECD 202).
NOEC Daphnia magna (Big water flea): 0.3 mg/L/21d (OECD 211).
Algae toxicity:
EC50 Scenedesmus capricornutum: 220 mg/L/72h.

Mobility in soil

The product is insoluble in water and is deposited on the water surface.



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Repair Stick Copper

Material number 105300

Revision date: 5/Aug/2016

Version: 2

Language: en-CA,US

Date of print: 11/Aug/2016

Page: 7 of 9

Persistence and degradability

Further details: Product is not biodegradable.

Additional ecological information

Volatile organic compounds (VOC):

0 % by weight = 0 g/L

General information:

Do not allow to enter into ground-water, surface water or drains.

Do not allow uncontrolled discharge of product into the environment.

13. Disposal considerations

Product

Recommendation: Dispose of waste according to applicable legislation.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Uncontaminated packaging may be treated as household waste.

14. Transport information

USA: Department of Transportation (DOT)

Proper shipping name: No dangerous good in sense of this transport regulation.

Canada: Transportation of Dangerous Goods (TDG)

Shipping name: No dangerous good in sense of this transport regulation.

Sea transport (IMDG)

Proper shipping name: No dangerous good in sense of this transport regulation.

Marine pollutant: no

Air transport (IATA)

Proper shipping name: No dangerous good in sense of this transport regulation.

Further information

No dangerous good in sense of these transport regulations.

15. Regulatory information

National regulations - Canada

No data available



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 5/Aug/2016

Version: 2

Language: en-CA,US

Date of print: 11/Aug/2016

Repair Stick Copper

Material number 105300

Page: 8 of 9

National regulations - U.S. Federal Regulations

Talcum:

TSCA Inventory: listed
TSCA HPVC: not listed
Carcinogen Status:
IARC Rating: Group 3
OSHA Carcinogen: not listed
NTP Rating: not listed
NIOSH Recommendations:
Occupational Health Guideline: 0584

Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700):

TSCA Inventory: listed; EPA flags XU
TSCA HPVC: not listed

2,4,6-tris(Dimethylaminomethyl)phenol:

TSCA Inventory: listed
TSCA HPVC: not listed

Copper:

TSCA Inventory: listed
TSCA HPVC: not listed
Clean Water Act:
Priority Pollutant: yes
Other Environmental Laws:
CERCLA: RQ 5000* lbs.
Marine Pollutant: listed as severe pollutant.
RCRA Groundwater Monitoring: Methods 6010, 7210 / PQL 60, 200
SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard
NIOSH Recommendations:
Occupational Health Guideline: 0150*

National regulations - U.S. State Regulations

Talcum:


California Proposition 65 code: not listed
Massachusetts Haz. Substance codes: 2,4 F5
Minnesota Haz. Substance:
Codes: AO - Ratings: --
Pennsylvania Haz. Substance code: -
Washington Air Contaminant:
TWA: 2mg
Wisconsin Hazardous Air Contaminant List (Appears on Table): A

16. Other information

Text for labeling:

Contains 20 - 50 % Talcum, 10 - 20 % Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700), < 5 % 2,4,6-tris(Dimethylaminomethyl)phenol, 1 - 5 % Copper. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:
Health: 2 (Moderate)
Fire: 1 (Slight)
Reactivity: 1 (Slight)
HMIS Version III Rating:
Health: 2 (Moderate)
Flammability: 1 (Slight)
Physical Hazard: 1 (Slight)
Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	1
	X

Reason of change:

Changes in section 1: General revision

Date of first version:

24/Feb/2016



SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Repair Stick Copper

Material number 105300

Revision date: 5/Aug/2016

Version: 2

Language: en-CA,US

Date of print: 11/Aug/2016

Page: 9 of 9

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.