



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 21/Feb/2018

Version: 1

Language: en-CA,US

Date of print: 13/Mar/2018

## Gasket Maker black

Material number 301010

Page:

1 of 6

### 1. Product and company identification

#### Product identifier

Trade name: Gasket Maker black

#### Relevant identified uses of the substance or mixture and uses advised against

General use: One-component adhesive and sealing agent, permanently elastic.  
Reserved for industrial and professional use.

#### Details of the supplier of the safety data sheet

Company name: WEICON Inc.  
Street/POB-No.: 20 Steckle Place, Unit 20  
Postal Code, city: Kitchener, Ontario N2E 2C3, CA  
WWW: www.weicon.ca  
E-mail: info@weicon.ca  
Telephone: +1-519-896-5252  
Telefax: +1-519-896-5254  
Dept. responsible for information:  
Product-Safety-Department  
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

#### Emergency phone number

**EMERGENCY CONTACT – Canada (24h): Tel: +1 866 928 0789 (Toll free)**  
**Transport:**  
**TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: +1 866 928 0789 (Toll free)**

### 2. Hazards identification

#### Emergency overview

Appearance: Form: pasty  
Color: black  
Odor: like acetic acidic  
Classification: This material is classified as not hazardous.

#### Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

#### Hazards not otherwise classified

see section 11: Toxicological information

### 3. Composition / Information on ingredients

Chemical characterisation: Silicone rubber

### 4. First aid measures

In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing.  
Seek medical attention.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 21/Feb/2018

Version: 1

Language: en-CA,US

Date of print: 13/Mar/2018

## Gasket Maker black

Material number 301010

Page:

2 of 6

- Following skin contact: Immediately clean with water and soap followed by thorough rinsing. Take off contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Keep eye wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Do not attempt to pull apart bonded eyelid. Subsequently seek the immediate attention of an ophthalmologist.
- After swallowing: Rinse mouth with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Seek medical aid in case of troubles.

### Most important symptoms and effects, both acute and delayed

No data available

### Information to physician

Treat symptomatically.

## 5. Fire fighting measures

Flash point/flash point range:

> 100 °C

Auto-ignition temperature: not self-igniting

Suitable extinguishing media:

Alcohol resistant foam, extinguishing powder, carbon dioxide, water spray jet.

Extinguishing media which must not be used for safety reasons:

Full water jet

### Specific hazards arising from the chemical

May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information: You have to dispose of contaminated extinguishing water according to the regulations of the authorities.

## 6. Accidental release measures

Personal precautions: Avoid contact with skin, eyes, and clothing. Do not breathe vapors/dust/ aerosols. Provide adequate ventilation. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.

Environmental precautions: Do not allow to penetrate into soil, waterbodies or drains.

Methods for clean-up: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal.

## 7. Handling and storage

### Handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Wear appropriate protective equipment. Do not breathe vapors/dust/ aerosols. Avoid contact with skin, eyes, and clothing. Take off contaminated clothing and wash it before reuse.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 21/Feb/2018

Version: 1

Language: en-CA,US

Date of print: 13/Mar/2018

## Gasket Maker black

Material number 301010

Page:

3 of 6

### Storage

Requirements for storerooms and containers:

Keep container tightly closed in a cool, well-ventilated place.  
Protect from moisture contamination. Protect from frost, heat and sunlight. Keep only in the original container.  
recommended storage temperature: room temperature

Hints on joint storage:

Do not store together with oxidizing agents.  
Keep away from food, drink and animal feedingstuffs.

Further details:

Do not allow the product to enter the ground.

## 8. Exposure controls / personal protection

### Exposure guidelines

Occupational exposure limit values:

Type	Limit value
Canada, Alberta: OEL 15 min	10 mg/m <sup>3</sup> Oil mist mineral
Canada, Alberta: OEL 8 hour	5 mg/m <sup>3</sup> Oil mist mineral
Canada, BC: OEL TWA	0.2 mg/m <sup>3</sup> Oil mist mineral
Canada, BC: OEL TWA	1 mg/m <sup>3</sup> Oil mist mineral, (mineral, severely refined)
Canada, Ontario: OEL TWA	5 mg/m <sup>3</sup> Oil mist mineral
Canada, Québec: VECD	10 mg/m <sup>3</sup> Oil mist mineral
Canada, Québec: VEMP	5 mg/m <sup>3</sup> Oil mist mineral
USA: NIOSH: STEL	10 mg/m <sup>3</sup> Oil mist mineral
USA: NIOSH: TWA	5 mg/m <sup>3</sup> Oil mist mineral
USA: OSHA: TWA	5 mg/m <sup>3</sup> Oil mist mineral

### Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

See also information in chapter 7, section storage.

### Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Wear suitable protective clothing.  
Protective gloves according to OSHA Standard - 29 CFR: 1910.138.  
Glove material: Nitrile rubber  
Layer thickness: > 0.4 mm  
Breakthrough time: > 480 min  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.  
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

General hygiene considerations:

Take off contaminated clothing and wash it before reuse. Avoid contact with the substance.

Wash hands before breaks and after work.

When using do not eat, drink or smoke.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 21/Feb/2018

Version: 1

Language: en-CA,US

Date of print: 13/Mar/2018

## Gasket Maker black

Material number 301010

Page:

4 of 6

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Appearance:	Form: pasty Color: black
Odor:	like acetic acidic
Odor threshold:	not determined
pH value:	No data available
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	not determined
Flash point/flash point range:	> 100 °C
Evaporation rate:	No data available
Flammability:	Not readily combustible.
Explosion limits:	LEL (Lower Explosion Limit): not determined UEL (Upper Explosive Limit): not determined
Vapor pressure:	No data available
Vapor density:	No data available
Density:	at 20 °C: 1.0 g/cm <sup>3</sup>
Solubility:	organic solvents
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	not self-igniting
Thermal decomposition:	No data available
Explosive properties:	not explosive
Ignition temperature:	not determined
Additional information:	not oxidising

## 10. Stability and reactivity

Reactivity:	Refer to subsection "Possibility of hazardous reactions".
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	No hazardous reaction when handled and stored according to provisions.
Conditions to avoid:	Protect from moisture contamination. Protect from frost, heat and sunlight.
Incompatible materials:	Oxidizing agents.
Hazardous decomposition products:	Carbon monoxide and carbon dioxide.
Thermal decomposition:	No data available



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 21/Feb/2018

Version: 1

Language: en-CA,US

Date of print: 13/Mar/2018

## Gasket Maker black

Material number 301010

Page:

5 of 6

## 11. Toxicological information

### Toxicological tests

Toxicological effects: Acute toxicity (oral): Lack of data.  
Acute toxicity (dermal): Lack of data.  
Acute toxicity (inhalative): Lack of data.  
Skin corrosion/irritation: Lack of data.  
Serious eye damage/irritation: Lack of data.  
Sensitisation to the respiratory tract: Lack of data.  
Skin sensitisation: Lack of data.  
Germ cell mutagenicity/Genotoxicity: Lack of data.  
Carcinogenicity: Lack of data.  
Reproductive toxicity: Lack of data.  
Effects on or via lactation: Lack of data.  
Specific target organ toxicity (single exposure): Lack of data.  
Specific target organ toxicity (repeated exposure): Lack of data.  
Aspiration hazard: Lack of data.

## 12. Ecological information

### Ecotoxicity

Further details: No data available

### Mobility in soil

No data available

### Persistence and degradability

Further details: No data available

### Additional ecological information

Volatile organic compounds (VOC):

approx. 2 % by weight = 21.2 g/L

General information: Do not allow to enter into ground-water, surface water or drains.

## 13. Disposal considerations

### Product

Recommendation: Dispose of waste according to applicable legislation.

### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.  
Non-contaminated packages may be recycled.

## 14. Transport information

### USA: Department of Transportation (DOT)

Proper shipping name: Not restricted



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 21/Feb/2018

Version: 1

Language: en-CA,US

Date of print: 13/Mar/2018

## Gasket Maker black

Material number 301010

Page: 6 of 6

### Canada: Transportation of Dangerous Goods (TDG)

Shipping name: Not restricted

### Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant: no

### Air transport (IATA)

Proper shipping name: Not restricted

### Further information

No dangerous good in sense of these transport regulations.


## 15. Regulatory information

### National regulations - Canada

No data available

## 16. Other information

Hazard rating systems:



NFPA Hazard Rating:

Health: 0 (Minimal)

Fire: 1 (Slight)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 0 (Minimal)

Flammability: 1 (Slight)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Date of first version: 21/Feb/2018

### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.