



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Gold Spray

Material number 111050

Page: 1 of 13

1. Product and company identification

Product identifier

Trade name: Gold Spray

Relevant identified uses of the substance or mixture and uses advised against

General use: Technical aerosol

Details of the supplier of the safety data sheet

Company name: WEICON Inc.

Street/POB-No.: 20 Steckle Place, Unit 20

Postal Code, city: Kitchener, Ontario N2E 2C3, CA

WWW: www.weicon.ca

E-mail: info@weicon.ca

Telephone: +1-519-896-5252

Telefax: +1-519-896-5254

Dept. responsible for information:

Product-Safety-Department

Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

Emergency phone number

EMERGENCY CONTACT – USA (24h): Tel: ++1 202 464 2554

Transport:

TRANSPORT EMERGENCY CONTACT - USA (24h): Tel: ++1 202 464 2554

2. Hazards identification

Emergency overview

Appearance: Physical state at 68 °F and 101.3 kPa: liquid

Form: Aerosol

Odor: No data available

Classification: Flammable Aerosol - Category 1; Compressed Gas; Eye Irritation - Category 2A; Specific Target Organ Toxicity (Single Exposure) - Category 3; Aquatic toxicity - acute - Category 1; Aquatic toxicity - chronic - Category 2;

Hazard symbols:



Signal word: **Danger**

Hazard statements: Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Very toxic to aquatic life.
Toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Gold Spray

Material number 111050

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Page: 2 of 13

Precautionary statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash hands and face thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
Call a POISON CENTER/doctor if you feel unwell.
If eye irritation persists: Get medical advice/attention.
Collect spillage.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Dispose of contents/container to hazardous or special waste collection point.

Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.
Repeated exposure may cause skin dryness or cracking.
see section 11: Toxicological information

3. Composition / Information on ingredients

Relevant ingredients:

| CAS No. | Designation | Content | Classification |
|----------------|---|------------|--|
| CAS 67-64-1 | Acetone | 20 - 25 % | Flammable Liquid - Category 2. Eye Irritation - Category 2A. Specific Target Organ Toxicity (Single Exposure) - Category 3. |
| CAS 141-78-6 | Ethyl acetate | 15 - 20 % | Flammable Liquid - Category 2. Eye Irritation - Category 2A. Specific Target Organ Toxicity (Single Exposure) - Category 3. |
| CAS 64742-95-6 | Solvent naphtha (petroleum), light arom | 2.5 - 10 % | Flammable Liquid - Category 3. Specific Target Organ Toxicity (Single Exposure) - Category 3. Aspiration Toxicity - Category 1. Aquatic toxicity - chronic - Category 2. |
| CAS 7440-50-8 | Copper | 2.5 - 10 % | Acute Toxicity - oral - Category 4. Aquatic toxicity - acute - Category 1. Aquatic toxicity - chronic - Category 2. |
| CAS 7440-66-6 | Zinc powder-zinc dust | < 2.5 % | Aquatic toxicity - acute - Category 1. Aquatic toxicity - chronic - Category 1. |
| CAS 106-97-8 | Butane | 10 - 20 % | Flammable Gas - Category 1. Compressed Gas. |
| CAS 74-98-6 | Propane | 10 - 20 % | Flammable Gas - Category 1. Compressed Gas. |



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Gold Spray

Material number 111050

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Page: 3 of 13

Additional information: Solvent naphtha (petroleum), light arom: < 0,1% benzene

4. First aid measures

General information: IF exposed or concerned: Get medical advice/attention. First aider: Pay attention to self-protection! Take off immediately all contaminated clothing.

In case of inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of irregular breathing or respiratory arrest provide artificial respiration. Seek medical attention.

Following skin contact: Wash with generous amount of water and soap. Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently seek the immediate attention of an ophthalmologist.

After swallowing: Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

Most important symptoms/effects, acute and delayed

Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range: not applicable

Auto-ignition temperature: No data available

Suitable extinguishing media: Alcohol resistant foam, dry chemical powder, sand, carbon dioxide

Extinguishing media which must not be used for safety reasons: Water

Specific hazards arising from the chemical

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May form dangerous gases and vapours in case of fire. Furthermore, there may develop: Metal oxide smoke, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters: Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing. Do not breathe fumes.

Additional information: Heating will lead to pressure increase: Danger of bursting and explosion. Cool exposed containers with water spray. Move undamaged containers from immediate hazard area if it can be done safely. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not allow fire water to penetrate into surface or ground water. Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Gold Spray

Material number 111050

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Page: 4 of 13

6. Accidental release measures

- Personal precautions:** Eliminate all ignition sources if safe to do so.
Provide adequate ventilation. Do not breathe vapor or spray.
Wear appropriate protective equipment. Avoid contact with skin and eyes.
Cordon off downwind area at risk and warn inhabitants.
- Environmental precautions:** Do not allow to penetrate into soil, waterbodies or drains. In case of release, notify competent authorities.
- Methods for clean-up:** Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).
Thoroughly clean surrounding area.
In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

7. Handling and storage

Handling

- Advices on safe handling:** Provide adequate ventilation, and local exhaust as needed.
Use only in well-ventilated areas. Do not breathe vapor or spray.
Wear appropriate protective equipment. Avoid contact with skin and eyes. Work place should be equipped with a shower and an eye rinsing apparatus.
Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.
- Precautions against fire and explosion:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.

Storage

- Requirements for storerooms and containers:** Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Store containers in upright position. storage temperature: 41 °F up to 77 °F.
- Hints on joint storage:** Keep away from food, drink and animal feedingstuffs.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Gold Spray
Material number 111050

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Page: 5 of 13

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

| CAS No. | Designation | Type | Limit value |
|-----------|---------------|------------------|---|
| 67-64-1 | Acetone | USA: ACGIH: STEL | 500 ppm |
| | | USA: ACGIH: TWA | 250 ppm |
| | | USA: NIOSH: TWA | 590 mg/m ³ ; 250 ppm |
| | | USA: OSHA: TWA | 2400 mg/m ³ ; 1000 ppm |
| 141-78-6 | Ethyl acetate | USA: ACGIH: TWA | 1440 mg/m ³ ; 400 ppm |
| | | USA: NIOSH: TWA | 1400 mg/m ³ ; 400 ppm |
| | | USA: OSHA: TWA | 1400 mg/m ³ ; 400 ppm |
| 7440-50-8 | Copper | USA: ACGIH: TWA | 0.2 mg/m ³ Smoke |
| | | USA: ACGIH: TWA | 1 mg/m ³ Dusts and mist calculated as Cu |
| | | USA: NIOSH: TWA | 1 mg/m ³ |
| | | USA: OSHA: TWA | 0.1 mg/m ³ (Smoke; calculated as Cu) |
| | | USA: OSHA: TWA | 1 mg/m ³ Dusts and mist calculated as Cu |
| 106-97-8 | Butane | USA: ACGIH: TWA | 2370 mg/m ³ ; 1000 ppm |
| | | USA: NIOSH: TWA | 1900 mg/m ³ ; 800 ppm |
| 74-98-6 | Propane | USA: NIOSH: TWA | 1800 mg/m ³ ; 1000 ppm |
| | | USA: OSHA: TWA | 1800 mg/m ³ ; 1000 ppm |

Biological limit values:

| CAS No. | Designation | Type | Limit value | Parameter | Sampling |
|---------|-------------|-----------------------|-------------|-----------|---------------------------------|
| 67-64-1 | Acetone | USA: ACGIH-BEI, urine | 25 mg/L | acetone | end of exposure or end of shift |

Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection Wear suitable protective clothing.

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material: Butyl caoutchouc (butyl rubber) - Layer thickness: >= 0.7 mm

Breakthrough time: >= 480 min

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Gold Spray

Material number 111050

Page: 6 of 13

General hygiene considerations:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not pierce or burn, even after use.
Do not breathe vapor or spray. Use only in well-ventilated areas.
Change contaminated clothing. Avoid contact with skin and eyes.
When using do not eat, drink or smoke.
Wash hands before breaks and after work.
Work place should be equipped with a shower and an eye rinsing apparatus.
Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.

9. Physical and chemical properties

Information on basic physical and chemical properties

| | |
|--|--|
| Appearance: | Physical state at 68 °F and 101.3 kPa: liquid Form: Aerosol |
| Odor: | No data available |
| Odor threshold: | No data available |
| pH value: | No data available |
| Melting point/freezing point: | No data available |
| Initial boiling point and boiling range: | not applicable |
| Flash point/flash point range: | not applicable |
| Evaporation rate: | No data available |
| Flammability: | Extremely flammable aerosol. |
| Explosion limits: | No data available |
| Vapor pressure: | No data available |
| Vapor density: | No data available |
| Density: | No data available |
| Water solubility: | slightly miscible |
| Partition coefficient: n-octanol/water: | No data available |
| Auto-ignition temperature: | No data available |
| Thermal decomposition: | No data available |
| Explosive properties: | Vapors may form explosive mixtures with air. Contains gas under pressure; may explode if heated. |
| Ignition temperature: | > 392 °F (estimated) |

10. Stability and reactivity

| | |
|------------------------------------|--|
| Reactivity: | Extremely flammable aerosol. Vapors may form explosive mixtures with air. |
| Chemical stability: | Stable under recommended storage conditions. |
| Possibility of hazardous reactions | Contains gas under pressure; may explode if heated. |
| Conditions to avoid: | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |
| Incompatible materials: | Water |



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Gold Spray

Material number 111050

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Page: 7 of 13

Hazardous decomposition products:

Toxic gases/vapours.
Carbon monoxide and carbon dioxide.

Thermal decomposition: No data available

11. Toxicological information

Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.
ATEmix (calculated): $2000 < ATE \leq 5000$ mg/kg.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.
Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
Skin corrosion/irritation: Based on available data, the classification criteria are not met.
Eye damage/irritation: Eye Irritation - Category 2A = Causes serious eye irritation.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Based on available data, the classification criteria are not met.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) - Category 3 = May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

Other information: Information about Acetone:
LD50 Rat, oral: 5800 mg/kg
LD50 Rat, dermal: 7800 mg/kg
LD50 Rat, inhalative: > 20 mg/L/4h

Symptoms

After contact with skin: Minor irritation effect - does not require labeling.
After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

General remarks

Further hazardous properties cannot be excluded.

12. Ecological information

Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.

Mobility in soil

No data available

Persistence and degradability

Further details: No data available



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Gold Spray

Material number 111050

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Page: 8 of 13

Additional ecological information

Volatile organic compounds (VOC):

85.3 % by weight = 738.2 g/L

General information:

Do not allow to enter into ground-water, surface water or drains.

Avoid spills and leaks. Very small amounts contaminates drinking water.

13. Disposal considerations

Product

Recommendation:

Do not pierce or burn, even after use.

Special waste. Dispose of waste according to applicable legislation.

Do not dispose of with household waste.

Contaminated packaging

Recommendation:

Dispose of waste according to applicable legislation.

Empty carefully and completely, if possible. Handle empty containers with care.

Incineration may cause explosion.

14. Transport information

USA: Department of Transportation (DOT)

Identification number: UN1950
Proper shipping name: UN 1950, AEROSOLS
Hazard class or Division: 2.1
Labels: 2.1
Special provisions: N82
Packaging – Exceptions: 306
Packaging – Non-bulk: None
Packaging – Bulk: None
Quantity limitations – Passenger aircraft / rail: 75 kg
Quantity limitations – Cargo only: 150 kg
Vessel stowage – Location: A
Vessel stowage – Other: 25, 87, 126





SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Gold Spray

Material number 111050

Page: 9 of 13

Sea transport (IMDG)

UN number: UN 1950
Proper shipping name: UN 1950, AEROSOLS
Class or division, Subsidiary risk: Class 2, Subrisk-, see SP63
Packing Group: -
EmS: F-D, S-U
Special provisions: 63, 190, 277, 327, 344, 381, 959
Limited quantities: See SP277
Excepted quantities: E0
Contaminated packaging - Instructions: P207, LP200
Contaminated packaging - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Marine pollutant: yes
Segregation group: none

Air transport (IATA)

UN/ID number: UN 1950
Proper shipping name: UN 1950, AEROSOLS, flammable
Class or division, Subsidiary risk: Class 2.1
Hazard label: Flamm. gas
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special provisions: A145 A167 A802
Emergency Response Guide-Code (ERG): 10L



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Gold Spray

Material number 111050

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Page: 10 of 13

15. Regulatory information

National regulations - U.S. Federal Regulations

| | |
|--|--|
| Acetone: | TSCA Inventory: listed TSCA HPVC: not listed Clean Air Act: SOCMI Chemical: yes Other Environmental Laws: CERCLA: RQ 5000 lbs. RCRA Hazardous Wastes: Code U002 RCRA Groundwater Monitoring: Methods 8240 / PQL 100 NIOSH Recommendations: Occupational Health Guideline: 0004* |
| Ethyl acetate: | TSCA Inventory: listed; EPA flags T TSCA HPVC: not listed Other Environmental Laws: CERCLA: RQ 5000 lbs. RCRA Hazardous Wastes: Code U112 NIOSH Recommendations: Occupational Health Guideline: 0260 |
| Solvent naphtha (petroleum), light arom: | TSCA Inventory: listed TSCA HPVC: not listed |
| Copper: | TSCA Inventory: listed TSCA HPVC: not listed Clean Water Act: Priority Pollutant: yes Other Environmental Laws: CERCLA: RQ 5000* lbs. Marine Pollutant: listed as severe pollutant. RCRA Groundwater Monitoring: Methods 6010, 7210 / PQL 60, 200 SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard NIOSH Recommendations: Occupational Health Guideline: 0150* |
| Zinc powder-zinc dust: | TSCA Inventory: listed TSCA HPVC: not listed Clean Water Act: Priority Pollutant: yes Other Environmental Laws: CERCLA: RQ 1000* lbs. RCRA Groundwater Monitoring: Methods 6010, 7950 / PQL 20, 50 SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard |
| Butane: | TSCA Inventory: listed TSCA HPVC: not listed Clean Air Act: Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f NIOSH Recommendations: Occupational Health Guideline: 0068* |



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Gold Spray

Material number 111050

Page: 11 of 13

Propane:

TSCA Inventory: listed

TSCA HPVC: not listed

Clean Air Act:

Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f

NIOSH Recommendations:

Occupational Health Guideline: 0524



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Gold Spray

Material number 111050

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Page: 12 of 13

National regulations - U.S. State Regulations

| | |
|----------------|---|
| Acetone: | California Prop 65 List: None Delaware Air Quality Management List: DRQ: 5000 - RQ State: Federal Regulations Apply Idaho Air Pollutant List: Title 585: AAC: 89 - EL: 119 - OEL: 1780 Massachusetts Haz. Substance codes: 2,4,5,6 F8 F9 Minnesota Haz. Substance: Codes: AON - Ratings: 7.16 - Status: Title III New York List of Hazardous Substances: RQ-Air: 5000 - RQ-Land: 1 - Note: No Note Associated with this chemical. Pennsylvania Haz. Substance code: E Washington Air Contaminant: TWA: 750 ppm - 1800 mg - STEL: 1000 ppm - 2400 mg |
| Ethyl acetate: | Delaware Air Quality Management List: DRQ: 5000 - RQ State: Federal Regulations Apply Idaho Air Pollutant List: Title 585: AAC: 70 - EL: 93,3 - OEL: 1400 - Title 586: - Main Hazardous Air Pollutants: Me 2005: HAP - Hap Rpt: 20000 Massachusetts Haz. Substance codes: 2,4,5,6 F8 Minnesota Haz. Substance: Codes: AO - Ratings: 6.83 - Status: Title III. New York List of Hazardous Substances: RQ-Air: 5000 - RQ-Land: 1 - Note: No Note Associated with this chemical. Pennsylvania Haz. Substance code: E Washington Air Contaminant: TWA: 400 ppm - 1400 mg |
| Butane: | Delaware Air Quality Management List: DRQ: F 1000** - RQ State: State requirements differs from Federal Massachusetts Haz. Substance codes: 4,5,6 Minnesota Haz. Substance: Codes: A - Ratings: - - Status: Title III New Jersey RTK Hazardous Substance: DOT: 1011 - Sub No.: 0273 - TPQ: - Pennsylvania Haz. Substance code: - Washington Air Contaminant: TWA: 800 ppm - 1900 mg |
| Propane: | California Proposition 65 code: - Delaware Air Quality Management List: DRQ: F 1000** - RQ State: State requirements differs from Federal Massachusetts Haz. Substance codes: 2,4,5,6 Minnesota Haz. Substance: Codes: AP - Ratings: - - Status: Title III New Jersey RTK Hazardous Substance: DOT: 1978 - Sub No.: 1594 - TPQ: - Pennsylvania Haz. Substance code: - Washington Air Contaminant: TWA: 1000 ppm - 1800 mg |

National regulations - Great Britain

Hazchem-Code: -



SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Gold Spray

Material number 111050

Revision date: Apr/4/2017

Version: 1

Language: en-US

Date of print: Apr/10/2017

Page: 13 of 13

16. Other information

Text for labeling:

Contains 20 - 25 % Acetone, 15 - 20 % Ethyl acetate, 2.5 - 10 % Solvent naphtha (petroleum), light arom, 2.5 - 10 % Copper, < 2.5 % Zinc powder-zinc dust, 10 - 20 % Butane, 10 - 20 % Propane. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:

Health: 2 (Moderate)

Fire: 4 (Severe)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 2 (Moderate) - Chronic effects

Flammability: 4 (Severe)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

| | | |
|-----------------|---|---|
| HEALTH | * | 2 |
| FLAMMABILITY | | 4 |
| PHYSICAL HAZARD | | 0 |
| | | X |

Date of first version:

Apr/4/2017

Department issuing data sheet

Contact person:

see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.