



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 4

Language: en-CA,US

Date of print: 10/Jan/2017

## Silicone-Spray

Material number 113500

Page: 1 of 12

### 1. Product and company identification

#### Product identifier

Trade name: Silicone-Spray

#### Relevant identified uses of the substance or mixture and uses advised against

General use: Technical aerosol.  
Reserved for industrial and professional use.

#### Details of the supplier of the safety data sheet

Company name: WEICON Inc.  
Street/POB-No.: 20 Steckle Place, Unit 20  
Postal Code, city: Kitchener, Ontario N2E 2C3, CA  
WWW: www.weicon.ca  
E-mail: info@weicon.ca  
Telephone: +1-519-896-5252  
Telefax: +1-519-896-5254  
Dept. responsible for information:  
Product-Safety-Department  
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

#### Emergency phone number

**EMERGENCY CONTACT – Canada (24h): Tel: ++1 866 928 0789 (Toll free)**

**Transport:**

**TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: ++1 866 928 0789 (Toll free)**

### 2. Hazards identification

#### Emergency overview

Appearance: Physical state at 20 °C and 101.3 kPa: liquid  
Form: Aerosol  
Color: colorless  
Odor: characteristic  
Classification: Flammable Aerosol 1; Compressed Gas; Skin Irritation 2; Reproductive toxicity 2; Specific Target Organ Toxicity (Single Exposure) 3; Specific Target Organ Toxicity (Repeated Exposure) 2; Aspiration Toxicity 1; Aquatic toxicity - chronic 2;

Hazard symbols:



Signal word:

**Danger**

Hazard statements:

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging fertility.  
May cause damage to organs through prolonged or repeated exposure.  
Toxic to aquatic life with long lasting effects.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 4

Language: en-CA,US

Date of print: 10/Jan/2017

## Silicone-Spray

Material number 113500

Page: 2 of 12

Precautionary statements: Keep out of reach of children.  
Obtain special instructions before use.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Do not breathe fume/gas/mist/vapors/spray.  
Avoid breathing vapors/spray.  
Wash hands and face thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection.  
IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
IF ON SKIN: Wash with plenty of water/soap.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed or concerned: Get medical advice/attention.  
Call a POISON CENTER/doctor if you feel unwell.  
Specific treatment (see ' First aid ' on this label).  
Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.  
Collect spillage.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Protect from sunlight. Store in a well-ventilated place.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container to hazardous or special waste collection point.

### Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

### Hazards not otherwise classified

Potentially explosive mixtures may form if adequate ventilation is not provided.  
Inhaling can lead to irritations of the respiratory tract and mucous membrane.  
Higher doses may lead to a narcotic effect.  
see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterisation: Silicone spray, solvent-based



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 4

Language: en-CA,US

Date of print: 10/Jan/2017

## Silicone-Spray

Material number 113500

Page:

3 of 12

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 64742-49-0	Naphtha (petroleum), hydrotreated light: < 0,1% benzene	20 - 40 %	Flammable Liquid 2. Skin Irritation 2. Specific Target Organ Toxicity (Single Exposure) 3. Aspiration Toxicity 1. Aquatic toxicity - chronic 2.
CAS 64-17-5	Ethanol	10 - 20 %	Flammable Liquid 2.
CAS 63148-62-9	Dimethylpolysiloxane	5 - 20 %	Flammable Liquid 3. Aquatic toxicity - chronic 4.
CAS 110-54-3	n-Hexane	< 2 %	Flammable Liquid 2. Skin Irritation 2. Reproductive toxicity 2. Specific Target Organ Toxicity (Single Exposure) 3. Specific Target Organ Toxicity (Repeated Exposure) 2. Aspiration Toxicity 1. Aquatic toxicity - chronic 2.
CAS 110-82-7	Cyclohexane	< 2 %	Flammable Liquid 2. Skin Irritation 2. Specific Target Organ Toxicity (Single Exposure) 3. Aspiration Toxicity 1. Aquatic toxicity - acute 1. Aquatic toxicity - chronic 1.
CAS 106-97-8	Butane	20 - 30 %	Flammable Gas 1. Compressed Gas.
CAS 74-98-6	Propane	20 - 30 %	Flammable Gas 1. Compressed Gas.

## 4. First aid measures

General information:	Take off immediately all contaminated clothing and wash it before reuse.
In case of inhalation:	Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical attention.
Following skin contact:	After contact with skin, wash immediately with soap and plenty of water. Consult a doctor if skin irritation persists.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.
After swallowing:	Immediately get medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

### Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Inhalation causes narcotic effects/intoxication. Dizziness, fatigue, headache. May cause respiratory irritation.

### Information to physician

Treat symptomatically.

## 5. Fire fighting measures

Flash point/flash point range:

-60 °C (c.c.)

Auto-ignition temperature: not self-igniting

Suitable extinguishing media::

Alcohol resistant foam, extinguishing powder, carbon dioxide, water fog.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Silicone-Spray

Material number 113500

Revision date: 2/Jan/2017

Version: 4

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 4 of 12

Extinguishing media which must not be used for safety reasons:

High power water jet

### Specific hazards arising from the chemical

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Heating will lead to pressure increase: Danger of bursting and explosion. Cool exposed containers with water spray.

May form dangerous gases and vapours in case of fire. Carbon monoxide and carbon dioxide.

Potentially explosive vapor/air mixtures may form.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Cool endangered containers with water jetspray. Do not allow fire water to penetrate into surface or ground water.

## 6. Accidental release measures

Personal precautions:

Provide adequate ventilation. Do not breathe gas/vapor/spray. Avoid contact with the substance. Eliminate all ignition sources if safe to do so. Wear appropriate protective equipment. Keep unprotected people away. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains. In case of release, notify competent authorities. Danger of explosion!

Methods for clean-up:

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Beware of reignition. Thoroughly clean surrounding area.

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

## 7. Handling and storage

### Handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed. Do not breathe gas/vapor/spray. Avoid contact with skin and eyes. Wear appropriate protective equipment. Keep unprotected people away. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation. Take off immediately all contaminated clothing and wash it before reuse.

Precautions against fire and explosion:

Container under pressure. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Use only explosion-protected equipment/instruments. Do not weld. In partially filled containers explosive mixtures may form. Vapors may form explosive mixtures with air.

### Storage

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place. Keep container dry. Keep only in the original container. Protect from heat and direct sunlight. Keep at temperature not exceeding 50 °C. Store containers in upright position. Explosion protection required. Store locked up.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Silicone-Spray

Material number 113500

Revision date: 2/Jan/2017

Version: 4

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 5 of 12

Hints on joint storage: Do not store together with combustible or self-igniting materials or any highly flammable solids. Keep away from food, drink and animal feedingstuffs. Do not store with oxidizing agents.

### 8. Exposure controls / personal protection

#### Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
64-17-5	Ethanol	Canada, Alberta: OEL 8 hour	1880 mg/m <sup>3</sup> ; 1000 ppm
		Canada, BC: OEL STEL	1000 ppm
		Canada, Québec: VEMP	1880 mg/m <sup>3</sup> ; 1000 ppm
		USA: ACGIH: STEL	1000 ppm (A3)
		USA: NIOSH: TWA	1900 mg/m <sup>3</sup> ; 1000 ppm
110-54-3	n-Hexane	USA: OSHA: TWA	1900 mg/m <sup>3</sup> ; 1000 ppm
		Canada, Alberta: OEL 8 hour	176 mg/m <sup>3</sup> ; 50 ppm
		Canada, BC: OEL TWA	20 ppm
			(May be absorbed through the skin.)
		Canada, Québec: VEMP	176 mg/m <sup>3</sup> ; 50 ppm
110-82-7	Cyclohexane	USA: ACGIH: TWA	176 mg/m <sup>3</sup> ; 50 ppm
			(May be absorbed through the skin.)
		USA: NIOSH: TWA	180 mg/m <sup>3</sup> ; 50 ppm
		USA: OSHA: TWA	1800 mg/m <sup>3</sup> ; 500 ppm
		Canada, Alberta: OEL 8 hour	344 mg/m <sup>3</sup> ; 100 ppm
106-97-8	Butane	Canada, BC: OEL TWA	100 ppm
		Canada, Québec: VEMP	1030 mg/m <sup>3</sup> ; 300 ppm
		USA: ACGIH: TWA	344 mg/m <sup>3</sup> ; 100 ppm
		USA: NIOSH: TWA	1050 mg/m <sup>3</sup> ; 300 ppm
		USA: OSHA: TWA	1050 mg/m <sup>3</sup> ; 300 ppm
74-98-6	Propane	Canada, Ontario: OEL TWA	800 ppm
		Canada, Québec: VEMP	1900 mg/m <sup>3</sup> ; 800 ppm
		USA: ACGIH: TWA	2370 mg/m <sup>3</sup> ; 1000 ppm
		USA: NIOSH: TWA	1900 mg/m <sup>3</sup> ; 800 ppm
		Canada, Alberta: OEL 8 hour	1000 ppm
		Canada, Québec: VEMP	1800 mg/m <sup>3</sup> ; 1000 ppm
		USA: NIOSH: TWA	1800 mg/m <sup>3</sup> ; 1000 ppm
		USA: OSHA: TWA	1800 mg/m <sup>3</sup> ; 1000 ppm
			1800 mg/m <sup>3</sup> ; 1000 ppm

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
110-54-3	n-Hexane	USA: ACGIH-BEI, urine	0.4 mg/L	2,5-Hexanedion in urine	end of shift at end of workweek

#### Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Use only explosion-proof equipment.

See also information in chapter 7, section storage.

#### Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 4

Language: en-CA,US

Date of print: 10/Jan/2017

## Silicone-Spray

Material number 113500

Page: 6 of 12

Skin protection	Flame retardant, antistatic and chemical resistant protective clothing. Protective gloves according to OSHA Standard - 29 CFR: 1910.138 (Solvent resistant protective gloves). Glove material: Butyl caoutchouc (butyl rubber) - Layer thickness: 0.7 mm Breakthrough time: > 480 min. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Respiratory protection:	Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If higher concentrations occur: Wear self-contained breathing apparatus.
General hygiene considerations:	Use only non-sparking tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Do not breathe gas/vapor/spray. Avoid contact with skin and eyes. Take off contaminated clothing and wash it before reuse. When using do not eat, drink or smoke. Wash hands before breaks and after work.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Form: Aerosol Color: colorless
Odor:	characteristic
Odor threshold:	No data available
pH value:	No data available
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	not applicable
Flash point/flash point range:	-60 °C (c.c.)
Evaporation rate:	No data available
Flammability:	extremely flammable aerosol
Explosion limits:	LEL (Lower Explosion Limit): 0.60 Vol-% UEL (Upper Explosive Limit): not determined
Vapor pressure:	at 20 °C: 3500 hPa
Vapor density:	not determined
Density:	at 20 °C: 0.67 g/mL
Solubility:	Soluble in hydrocarbons
Water solubility:	slightly soluble
Partition coefficient: n-octanol/water:	not determined
Auto-ignition temperature:	not self-igniting
Thermal decomposition:	No decomposition when used properly.
Viscosity, dynamic:	not determined
Viscosity, kinematic:	not determined
Explosive properties:	Product is not explosive. Potentially explosive vapor/air mixtures may form.
Ignition temperature:	> 250 °C
Solvent content:	>= 40 %



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Silicone-Spray

Material number 113500

Revision date: 2/Jan/2017

Version: 4

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 7 of 12

## 10. Stability and reactivity

- Reactivity: Contains gas under pressure; may explode if heated.  
Vapors may form explosive mixtures with air.
- Chemical stability: Stable under recommended storage conditions.
- Possibility of hazardous reactions  
Container under pressure.  
Heating will lead to pressure increase: Danger of bursting and explosion.
- Conditions to avoid: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- Incompatible materials: Do not store together with combustible or self-igniting materials or any highly flammable solids. Do not store with oxidizing agents..
- Hazardous decomposition products:  
May form dangerous gases and vapours in case of fire.  
Carbon monoxide and carbon dioxide.
- Thermal decomposition: No decomposition when used properly.

## 11. Toxicological information

### Toxicological tests

- Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
- Acute toxicity (oral): Based on available data, the classification criteria are not met.  
ATEmix (calculated): > 5000 mg/kg.
- Acute toxicity (dermal): Based on available data, the classification criteria are not met.  
ATEmix (calculated): > 2000 mg/kg.
- Acute toxicity (inhalative): Based on available data, the classification criteria are not met.  
ATEmix (calculated): > 20 ml/L.
- Skin corrosion/irritation: Skin Irritation 2 = Causes skin irritation.  
Information about Naphtha (petroleum), hydrotreated light  
Specific symptoms in animal studies (Rabbit): Irritant
- Eye damage/irritation: Lack of data.
- Sensitisation to the respiratory tract: Lack of data.
- Skin sensitisation: Lack of data.
- Germ cell mutagenicity/Genotoxicity: Lack of data.
- Carcinogenicity: Lack of data.
- Reproductive toxicity: Reproductive toxicity 2 = Suspected of damaging fertility.
- Effects on or via lactation: Lack of data.
- Specific target organ toxicity (single exposure): Specific Target Organ Toxicity (Single Exposure) 3 = May cause drowsiness or dizziness.  
Specific target organ toxicity: depression of central nervous system
- Specific target organ toxicity (repeated exposure): Specific Target Organ Toxicity (Repeated Exposure) 2 = May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard: Aspiration Toxicity 1 = May be fatal if swallowed and enters airways.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 4

Language: en-CA,US

Date of print: 10/Jan/2017

## Silicone-Spray

Material number 113500

Page: 8 of 12

Other information: Information about Naphtha (petroleum), hydrotreated light:  
LD50 Rat, oral: > 5000 mg/kg (OECD 401)  
LD50, Rabbit, dermal: > 2000 mg/kg (OECD 402)  
LC50, Rat, inhalative (Dampf): > 5,61 mg/L (OECD 403)

### Symptoms

After contact with skin:  
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

## 12. Ecological information

### Ecotoxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.  
Information about Naphtha (petroleum), hydrotreated light  
Algae toxicity:  
EL50 Pseudokirchneriella subcapitata (green algae): 56 mg/L/72h (OECD 201)  
Daphnia toxicity:  
EL50 Daphnia magna (Big water flea): 4.5 mg/L/48h (OECD 202)  
Fish toxicity:  
LL50 Leuciscus idus: 4.5 mg/L/96h (OECD 203)

Further details: Information about Naphtha (petroleum), hydrotreated light:  
Biodegradation: 77.05 % /28 d (OECD 301 F).  
Easily bio-degradable.

### Mobility in soil

No data available

### Persistence and degradability

Further details: No data available

### Additional ecological information

Volatile organic compounds (VOC):  
90 % by weight = 584.3 g/L

General information: Do not allow to penetrate into soil, waterbodies or drains.

## 13. Disposal considerations

### Product

Recommendation: Dispose of waste according to applicable legislation.

### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle empty containers with care. Incineration may cause explosion. Spray can must be completely empty for proper waste disposal.



## Silicone-Spray

Material number 113500

Page:

9 of 12

**14. Transport information****USA: Department of Transportation (DOT)**

Identification number: UN1950  
Proper shipping name: UN 1950, AEROSOLS  
Hazard class or Division: 2.1  
Labels: 2.1  
Special provisions: N82  
Packaging – Exceptions: 306  
Packaging – Non-bulk: None  
Packaging – Bulk: None  
Quantity limitations – Passenger aircraft / rail:  
75 kg  
Quantity limitations – Cargo only: 150 kg  
Vessel stowage – Location: A  
Vessel stowage – Other: 25, 87, 126

**Canada: Transportation of Dangerous Goods (TDG)**

UN Number: UN1950  
Shipping name: UN 1950, AEROSOLS  
TDG class: 2.1  
Special provisions: 80, 107  
Explosive limit and limited quantity index: 1 L  
Passenger carrying road or rail index: 75 L

**Sea transport (IMDG)**

UN number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS  
Class or division, Subsidiary risk: Class 2.1, Subrisk-  
Packing Group: -  
EmS: F-D, S-U  
Special provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantities: 1000 mL  
Excepted quantities: E0  
Contaminated packaging - Instructions: P207, LP200  
Contaminated packaging - Provisions: PP87, L2  
IBC - Instructions: -  
IBC - Provisions: -  
Tank instructions - IMO: -  
Tank instructions - UN: -  
Tank instructions - Provisions: -  
Stowage and handling: SW1 SW22  
Segregation: SG69  
Properties and observations: -  
Marine pollutant: yes  
Segregation group: none

**Air transport (IATA)**

UN/ID number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS, flammable  
Class or division, Subsidiary risk: Class 2.1  
Hazard label: Flamm. gas  
Excepted Quantity Code: E0  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G  
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg  
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg  
Special provisions: A145 A167 A802  
Emergency Response Guide-Code (ERG): 10L



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 4

Language: en-CA,US

Date of print: 10/Jan/2017

## Silicone-Spray

Material number 113500

Page: 10 of 12

### 15. Regulatory information

#### National regulations - Canada

No data available

#### National regulations - U.S. Federal Regulations

Naphtha (petroleum), hydrotreated  
light: < 0,1% benzene:

TSCA Inventory: listed; UVCB  
TSCA HPVC: not listed  
TSCA: listed - UVCB

Ethanol:

TSCA Inventory: listed  
TSCA HPVC: not listed  
TSCA: listed  
NIOSH Recommendations:  
Occupational Health Guideline: 0262

n-Hexane:

TSCA Inventory: listed  
TSCA HPVC: not listed  
Clean Air Act:  
Hazardous Air Pollutants: Code XO  
SOCMI Chemical: yes  
Other Environmental Laws:  
CERCLA: RQ 5000 lbs.  
SARA Title III Section 313, Toxic Release: Conc. 1.0% /  
Threshold Standard  
NIOSH Recommendations:  
Occupational Health Guideline: 0322

Cyclohexane:

TSCA Inventory: listed  
TSCA HPVC: not listed  
Clean Air Act:  
SOCMI Chemical: yes  
Clean Water Act:  
Hazardous Substances: RQ 1000 lbs.  
Other Environmental Laws:  
CERCLA: RQ 1000 lbs.  
RCRA Hazardous Wastes: Code U056  
SARA Title III Section 313, Toxic Release: Conc. 1.0% /  
Threshold Standard  
NIOSH Recommendations:  
Occupational Health Guideline: 0163

Butane:

TSCA Inventory: listed  
TSCA HPVC: not listed  
Clean Air Act:  
Accidental Release Prevention: Threshold 10000 lbs. / Basis for  
listing = f  
NIOSH Recommendations:  
Occupational Health Guideline: 0068\*

Propane:

TSCA Inventory: listed  
TSCA HPVC: not listed  
Clean Air Act:  
Accidental Release Prevention: Threshold 10000 lbs. / Basis for  
listing = f  
NIOSH Recommendations:  
Occupational Health Guideline: 0524



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Silicone-Spray

Material number 113500

Revision date: 2/Jan/2017

Version: 4

Language: en-CA,US

Date of print: 10/Jan/2017

Page: 11 of 12

### National regulations - U.S. State Regulations

Ethanol:

California Proposition 65 code: -  
Idaho Air Pollutant List:  
Title 585: AAC: 94 - EL: 125 - OEL: 1880 - Title 586: -  
Massachusetts Haz. Substance codes: 2,4,5,6 \*T1\*  
Minnesota Haz. Substance:  
Codes: AO - Ratings: 7.74  
Pennsylvania Haz. Substance code: -  
Washington Air Contaminant:  
TWA: 1000 ppm - 1900 mg

n-Hexane:

California Proposition 65 code: -  
Delaware Air Quality Management List:  
DRQ: 5000 - RQ State: Federal Regulations Apply  
Idaho Air Pollutant List:  
Title 585: AAC: 9 - EL: 12 - OEL: 180 - Title 586: -  
Maine Hazardous Air Pollutants:  
Me 2005: HAP - Hap Rpt: 2000  
Massachusetts Haz. Substance codes: 2,4,5,6  
Minnesota Haz. Substance:  
Codes: ANO - Ratings: 9.57 - Status: Air Pollutant Title III. TRI.  
New Jersey RTK Hazardous Substance:  
DOT: 1208 - Sub No.: 1340 - TPQ: -  
New York List of Hazardous Substances:  
RQ-Air: 1 - RQ-Land: 1 - Note: No Note Associated with this chemical.  
Pennsylvania Haz. Substance code: -  
Washington Air Contaminant:  
TWA: 50 ppm - 180 mg

Cyclohexane:

California Proposition 65 code: -  
Delaware Air Quality Management List:  
DRQ: 1000 - RQ State: Federal Regulations Apply  
Idaho Air Pollutant List:  
Title 585: AAC: 52,5 - EL: 70 - OEL: 1050 - Title 586: -  
Maine Hazardous Air Pollutants:  
Me 2005: HAP - Hap Rpt: 20000  
Massachusetts Haz. Substance codes: 2,4,5,6 F8 F9  
Minnesota Haz. Substance:  
Codes: AO - Ratings: 7.94 - Status: Title III. TRI.  
New Jersey RTK Hazardous Substance:  
DOT: 1145 - Sub No.: 0565 - TPQ: -  
New York List of Hazardous Substances:  
RQ-Air: 1000 - RQ-Land: 1 - Note: No Note Associated with this chemical.  
Pennsylvania Haz. Substance code: E  
Washington Air Contaminant:  
TWA: 300 ppm - 1050 mg

Butane:

Delaware Air Quality Management List:  
DRQ: F 1000\*\* - RQ State: State requirements differs from Federal  
Massachusetts Haz. Substance codes: 4,5,6  
Minnesota Haz. Substance:  
Codes: A - Ratings: - - Status: Title III  
New Jersey RTK Hazardous Substance:  
DOT: 1011 - Sub No.: 0273 - TPQ: -  
Pennsylvania Haz. Substance code: -  
Washington Air Contaminant:  
TWA: 800 ppm - 1900 mg



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 2/Jan/2017

Version: 4

Language: en-CA,US

Date of print: 10/Jan/2017

## Silicone-Spray

Material number 113500

Page: 12 of 12

Propane:

California Proposition 65 code: -  
 Delaware Air Quality Management List:  
 DRQ: F 1000\*\* - RQ State: State requirements differs from Federal  
 Massachusetts Haz. Substance codes: 2,4,5,6  
 Minnesota Haz. Substance:  
 Codes: AP - Ratings: - - Status: Title III  
 New Jersey RTK Hazardous Substance:  
 DOT: 1978 - Sub No.: 1594 - TPQ: -  
 Pennsylvania Haz. Substance code: -  
 Washington Air Contaminant:  
 TWA: 1000 ppm - 1800 mg

### 16. Other information

Text for labeling: Contains 20 - 40 % Naphtha (petroleum), hydrotreated light: < 0,1% benzene, 10 - 20 % Ethanol, 5 - 20 % Dimethylpolysiloxane, < 2 % n-Hexane, < 2 % Cyclohexane, 20 - 30 % Butane, 20 - 30 % Propane. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:  
 Health: 2 (Moderate)  
 Fire: 4 (Severe)  
 Reactivity: 0 (Minimal)  
 HMIS Version III Rating:  
 Health: 2 (Moderate) - Chronic effects  
 Flammability: 4 (Severe)  
 Physical Hazard: 0 (Minimal)  
 Personal Protection: X = Consult your supervisor

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL HAZARD		0
		X

Reason of change: ADR/RID 2017, IMDG 2017

Date of first version: 30/Oct/2015

#### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.