



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 28/Feb/2017

Version: 1

Language: en-CA,US

Date of print: 28/Feb/2017

## Adhering-Grease-Spray

Material number 115400

Page: 1 of 11

### 1. Product and company identification

#### Product identifier

Trade name: Adhering-Grease-Spray

#### Relevant identified uses of the substance or mixture and uses advised against

General use: Technical aerosol.  
Reserved for industrial and professional use.

#### Details of the supplier of the safety data sheet

Company name: WEICON Inc.  
Street/POB-No.: 20 Steckle Place, Unit 20  
Postal Code, city: Kitchener, Ontario N2E 2C3, CA  
WWW: www.weicon.ca  
E-mail: info@weicon.ca  
Telephone: +1-519-896-5252  
Telefax: +1-519-896-5254  
Dept. responsible for information:  
Product-Safety-Department  
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

#### Emergency phone number

**EMERGENCY CONTACT – Canada (24h): Tel: ++1 866 928 0789 (Toll free)**

**Transport:**

**TRANSPORT EMERGENCY CONTACT - Canada (24h): Tel: ++1 866 928 0789 (Toll free)**

### 2. Hazards identification

#### Emergency overview

Appearance: Form: Aerosol  
Color: beige  
Odor: like mineral oil  
Classification: Flammable Aerosol 1; Compressed Gas; Sensitization - skin 1;  
Hazard symbols:



Signal word: **Danger**  
Hazard statements: Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
May cause an allergic skin reaction.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Adhering-Grease-Spray

Material number 115400

Revision date: 28/Feb/2017

Version: 1

Language: en-CA,US

Date of print: 28/Feb/2017

Page: 2 of 11

Precautionary statements: Keep out of reach of children.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Avoid breathing vapors/spray.  
Contaminated work clothing should not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection.  
IF ON SKIN: Wash with plenty of water/soap.  
Specific treatment (see 'First aid' on this label).  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
Protect from sunlight. Store in a well-ventilated place.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container to hazardous or special waste collection point.

### Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

### Hazards not otherwise classified

Product has an anesthetic effect.  
Exposure to temperatures exceeding 50 °C will increase pressure: resulting in danger of bursting or explosion.  
Potentially explosive mixtures may form if adequate ventilation is not provided.  
see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterisation: Preparation of metallic soap in mineral oil with additives  
Preparation of active ingredients with propellant: Propane/Butane.

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 67-63-0	Isopropyl alcohol	< 10 %	Flammable Liquid 2. Eye Irritation 2A. Specific Target Organ Toxicity (Single Exposure) 3.
CAS 3115-49-9	(4-nonylphenoxy) acetic acid	< 1 %	Acute Toxicity 4 (oral). Skin Corrosion 1B. Sensitization - skin 1. Aquatic toxicity - acute 1. Aquatic toxicity - chronic 1.
CAS 74-98-6	Propane	20 - 25 %	Flammable Gas 1. Compressed Gas.
CAS 106-97-8	Butane	20 - 25 %	Flammable Gas 1. Compressed Gas.

## 4. First aid measures

General information: Take off immediately all contaminated clothing and wash it before reuse.  
In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical treatment in case of troubles.  
Following skin contact: After contact with skin, wash immediately with soap and plenty of water. Consult a doctor if skin irritation persists.  
After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Adhering-Grease-Spray

Material number 115400

Revision date: 28/Feb/2017

Version: 1

Language: en-CA,US

Date of print: 28/Feb/2017

Page: 3 of 11

After swallowing: Immediately get medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

### Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

### Information to physician

Treat symptomatically.

## 5. Fire fighting measures

Flash point/flash point range:

not applicable

Auto-ignition temperature: not determined

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

### Specific hazards arising from the chemical

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: Sulphur dioxide (SO<sub>2</sub>), carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Heating will lead to pressure increase: Danger of bursting and explosion. Cool exposed containers with water spray.

Move undamaged containers from immediate hazard area if it can be done safely.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

## 6. Accidental release measures

Personal precautions:

Do not breathe spray. Avoid contact with the substance.

Eliminate all ignition sources if safe to do so. Provide adequate ventilation.

Take off immediately all contaminated clothing and wash it before reuse.

Wear appropriate protective equipment. Keep unprotected people away.

Cordon off downwind area at risk and warn inhabitants.

Environmental precautions:

Do not allow to enter into ground-water, surface water or drains.

In case of release, notify competent authorities. Danger of explosion!

Methods for clean-up:

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Adhering-Grease-Spray

Material number 115400

Revision date: 28/Feb/2017

Version: 1

Language: en-CA,US

Date of print: 28/Feb/2017

Page:

4 of 11

## 7. Handling and storage

### Handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Provide room air exhaust at ground level. Do not breathe spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.

Take off immediately all contaminated clothing and wash it before reuse.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.

### Storage

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.

Keep container dry. Keep only in the original container.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Store containers in upright position.

Hints on joint storage:

Keep away from food, drink and animal feedingstuffs.

## 8. Exposure controls / personal protection

### Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
67-63-0	Isopropyl alcohol	Canada, Alberta: OEL 15 min	984 mg/m <sup>3</sup> ; 400 ppm
		Canada, Alberta: OEL 8 hour	492 mg/m <sup>3</sup> ; 200 ppm
		Canada, BC: OEL STEL	400 ppm
		Canada, BC: OEL TWA	200 ppm
		Canada, Québec: VECD	1230 mg/m <sup>3</sup> ; 500 ppm
		Canada, Québec: VEMP	985 mg/m <sup>3</sup> ; 400 ppm
		USA: ACGIH: STEL	984 mg/m <sup>3</sup> ; 400 ppm
		USA: ACGIH: TWA	492 mg/m <sup>3</sup> ; 200 ppm
		USA: NIOSH: STEL	1225 mg/m <sup>3</sup> ; 500 ppm
		USA: NIOSH: TWA	980 mg/m <sup>3</sup> ; 400 ppm
74-98-6	Propane	USA: OSHA: TWA	980 mg/m <sup>3</sup> ; 400 ppm
		Canada, Alberta: OEL 8 hour	1000 ppm
		Canada, Québec: VEMP	1800 mg/m <sup>3</sup> ; 1000 ppm
		USA: NIOSH: TWA	1800 mg/m <sup>3</sup> ; 1000 ppm
106-97-8	Butane	USA: OSHA: TWA	1800 mg/m <sup>3</sup> ; 1000 ppm
		Canada, Alberta: OEL 8 hour	1000 ppm
		Canada, BC: OEL STEL	750 ppm
		Canada, BC: OEL TWA	600 ppm
		Canada, Ontario: OEL TWA	800 ppm
		Canada, Québec: VEMP	1900 mg/m <sup>3</sup> ; 800 ppm
		USA: ACGIH: TWA	2370 mg/m <sup>3</sup> ; 1000 ppm
		USA: NIOSH: TWA	1900 mg/m <sup>3</sup> ; 800 ppm



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Adhering-Grease-Spray

Material number 115400

Revision date: 28/Feb/2017

Version: 1

Language: en-CA,US

Date of print: 28/Feb/2017

Page: 5 of 11

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
67-63-0	Isopropyl alcohol	USA: ACGIH-BEI, urine	40 mg/L	Acetone in urine	end of shift at end of workweek

### Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

See also information in chapter 7, section storage.

### Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Flame retardant, antistatic and chemical resistant protective clothing.  
Protective gloves according to OSHA Standard - 29 CFR: 1910.138 (Solvent resistant protective gloves).  
Glove material: Nitrile rubber - Layer thickness: 0.4 mm  
Breakthrough time: 60 min.  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.  
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

General hygiene considerations:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not pierce or burn, even after use.

Provide adequate ventilation, and local exhaust as needed. Do not breathe spray. Do not get in eyes, on skin, or on clothing.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Appearance:	Form: Aerosol Color: beige
Odor:	like mineral oil
Odor threshold:	not determined
pH value:	not determined
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	not applicable
Flash point/flash point range:	not applicable
Evaporation rate:	not determined
Flammability:	extremely flammable aerosol
Explosion limits:	LEL (Lower Explosion Limit): 0.60 Vol-% UEL (Upper Explosive Limit): 3.20 Vol-%
Vapor pressure:	at 20 °C: 3500 hPa (Internal pressure of can)
Vapor density:	not determined



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 28/Feb/2017

Version: 1

Language: en-CA,US

Date of print: 28/Feb/2017

## Adhering-Grease-Spray

Material number 115400

Page:

6 of 11

Density:	at 20 °C: 0.72 g/cm <sup>3</sup>
Solubility:	not determined
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	not determined
Auto-ignition temperature:	not determined
Thermal decomposition:	No decomposition when used properly.
Viscosity, dynamic:	not determined
Viscosity, kinematic:	not determined
Explosive properties:	Vapors may form explosive mixtures with air. Contains gas under pressure; may explode if heated.
Ignition temperature:	> 250 °C
Solid content:	29.1 %

## 10. Stability and reactivity

Reactivity:	Extremely flammable aerosol. Vapors may form explosive mixtures with air.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Contains gas under pressure; may explode if heated. Reactions with oxygen.
Conditions to avoid:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Incompatible materials:	oxygen
Hazardous decomposition products:	Sulphur dioxide (SO <sub>2</sub> )
Thermal decomposition:	No decomposition when used properly.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Adhering-Grease-Spray

Material number 115400

Revision date: 28/Feb/2017

Version: 1

Language: en-CA,US

Date of print: 28/Feb/2017

Page: 7 of 11

## 11. Toxicological information

### Toxicological tests

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.  
Acute toxicity (oral): Lack of data.  
Acute toxicity (dermal): Lack of data.  
Acute toxicity (inhalative): Lack of data.  
Skin corrosion/irritation: Based on available data, the classification criteria are not met.  
Eye damage/irritation: Based on available data, the classification criteria are not met.  
Sensitisation to the respiratory tract: Lack of data.  
Skin sensitisation: Sensitization - skin 1 = May cause an allergic skin reaction.  
Germ cell mutagenicity/Genotoxicity: Lack of data.  
Carcinogenicity: Lack of data.  
Reproductive toxicity: Lack of data.  
Effects on or via lactation: Lack of data.  
Specific target organ toxicity (single exposure): Lack of data.  
Specific target organ toxicity (repeated exposure): Lack of data.  
Aspiration hazard: Lack of data.

Other information: Further hazardous properties cannot be excluded.

### Symptoms

When vapors form: Dizziness, Headache and fatigue.  
After contact with skin:  
Minor irritation effect - does not require labeling.  
After eye contact:  
Minor irritation effect - does not require labeling.

### General remarks

Handle in accordance with good industrial hygiene and safety practice.

## 12. Ecological information

### Ecotoxicity

Further details: No data available

### Mobility in soil

No data available

### Persistence and degradability

Further details: Product is biodegradable with difficulty.

### Additional ecological information

Volatile organic compounds (VOC):

62.8 % by weight = 410.9 g/L

General information: Do not allow to enter into ground-water, surface water or drains.



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Adhering-Grease-Spray

Material number 115400

Revision date: 28/Feb/2017

Version: 1

Language: en-CA,US

Date of print: 28/Feb/2017

Page:

8 of 11

### 13. Disposal considerations

#### Product

Recommendation: Do not pierce or burn, even after use.  
Special waste. Dispose of waste according to applicable legislation.  
Do not dispose of with household waste.

#### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.  
Empty carefully and completely, if possible. Handle empty containers with care.  
Incineration may cause explosion.

### 14. Transport information

#### USA: Department of Transportation (DOT)

Identification number: UN1950  
Proper shipping name: UN 1950, AEROSOLS  
Hazard class or Division: 2.1  
Labels: 2.1  
Special provisions: N82  
Packaging – Exceptions: 306  
Packaging – Non-bulk: None  
Packaging – Bulk: None  
Quantity limitations – Passenger aircraft / rail: 75 kg  
Quantity limitations – Cargo only: 150 kg  
Vessel stowage – Location: A  
Vessel stowage – Other: 25, 87, 126



#### Canada: Transportation of Dangerous Goods (TDG)

UN Number: UN1950  
Shipping name: UN 1950, AEROSOLS  
TDG class: 2.1  
Special provisions: 80, 107  
Explosive limit and limited quantity index: 1 L  
Passenger carrying road or rail index: 75 L





# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 28/Feb/2017

Version: 1

Language: en-CA,US

Date of print: 28/Feb/2017

## Adhering-Grease-Spray

Material number 115400

Page: 9 of 11

### Sea transport (IMDG)

UN number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS  
Class or division, Subsidiary risk: Class 2.1, Subrisk-  
Packing Group: -  
EmS: F-D, S-U  
Special provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantities: 1000 mL  
Excepted quantities: E0  
Contaminated packaging - Instructions: P207, LP200  
Contaminated packaging - Provisions: PP87, L2  
IBC - Instructions: -  
IBC - Provisions: -  
Tank instructions - IMO: -  
Tank instructions - UN: -  
Tank instructions - Provisions: -  
Stowage and handling: SW1 SW22  
Segregation: SG69  
Properties and observations: -  
Marine pollutant: no  
Segregation group: none

### Air transport (IATA)

UN/ID number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS, flammable  
Class or division, Subsidiary risk: Class 2.1  
Hazard label: Flamm. gas  
Excepted Quantity Code: E0  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G  
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg  
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg  
Special provisions: A145 A167 A802  
Emergency Response Guide-Code (ERG): 10L

## 15. Regulatory information

### National regulations - Canada

No data available



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

## Adhering-Grease-Spray

Material number 115400

Revision date: 28/Feb/2017

Version: 1

Language: en-CA,US

Date of print: 28/Feb/2017

Page: 10 of 11

### National regulations - U.S. Federal Regulations

Isopropyl alcohol:	TSCA Inventory: listed TSCA HPVC: not listed Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0359
(4-nonylphenoxy)acetic acid:	TSCA Inventory: listed TSCA HPVC: not listed
Propane:	TSCA Inventory: listed TSCA HPVC: not listed Clean Air Act: Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f NIOSH Recommendations: Occupational Health Guideline: 0524
Butane:	TSCA Inventory: listed TSCA HPVC: not listed Clean Air Act: Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f NIOSH Recommendations: Occupational Health Guideline: 0068*

### National regulations - U.S. State Regulations

Isopropyl alcohol:	Idaho Air Pollutant List: Title 585: AAC: 49 -- EL: 65.3 -- WEL: 980 -Title 586: - Massachusetts Haz. Substance codes: 2,4,5,6 F9 Minnesota Haz. Substance: Codes: ANO -- Ratings: 7.84 -- Status: Title III. TRI. New Jersey RTK Hazardous Substance: DOT: 1219 - Sub No.: 1076 - TPQ: - Pennsylvania Haz. Substance code: E Washington Air Contaminant: TWA: 400 ppm - 980 mg -- STEL: 500 ppm - 1225 mg
Propane:	California Proposition 65 code: - Delaware Air Quality Management List: DRQ: F 1000** - RQ State: State requirements differs from Federal Massachusetts Haz. Substance codes: 2,4,5,6 Minnesota Haz. Substance: Codes: AP - Ratings: - - Status: Title III New Jersey RTK Hazardous Substance: DOT: 1978 - Sub No.: 1594 - TPQ: - Pennsylvania Haz. Substance code: - Washington Air Contaminant: TWA: 1000 ppm - 1800 mg
Butane:	Delaware Air Quality Management List: DRQ: F 1000** - RQ State: State requirements differs from Federal Massachusetts Haz. Substance codes: 4,5,6 Minnesota Haz. Substance: Codes: A - Ratings: - - Status: Title III New Jersey RTK Hazardous Substance: DOT: 1011 - Sub No.: 0273 - TPQ: - Pennsylvania Haz. Substance code: - Washington Air Contaminant: TWA: 800 ppm - 1900 mg



# SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 28/Feb/2017  
Version: 1  
Language: en-CA,US  
Date of print: 28/Feb/2017

## Adhering-Grease-Spray


Material number 115400

Page: 11 of 11

### 16. Other information

Text for labeling: Contains < 10 % Isopropyl alcohol, < 1 % (4-nonylphenoxy)acetic acid, 20 - 25 % Propane, 20 - 25 % Butane. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:

Health: 2 (Moderate)

Fire: 4 (Severe)

Reactivity: 1 (Slight)

HMIS Version III Rating:

Health: 2 (Moderate)

Flammability: 4 (Severe)

Physical Hazard: 1 (Slight)

Personal Protection: X = Consult your supervisor

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	1
	X

Date of first version: 28/Feb/2017

#### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.