



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

## Fitting-Spray

Material number 115600

Page: 1 of 9

## 1. Product and company identification

### Product identifier

Trade name: Fitting-Spray

### Relevant identified uses of the substance or mixture and uses advised against

General use: Technical aerosol.  
Reserved for industrial and professional use.

### Details of the supplier of the safety data sheet

Company name: WEICON Inc.  
Street/POB-No.: 20 Steckle Place, Unit 20  
Postal Code, city: Kitchener, Ontario N2E 2C3, CA  
WWW: www.weicon.ca  
E-mail: info@weicon.ca  
Telephone: +1-519-896-5252  
Telefax: +1-519-896-5254  
Dept. responsible for information:  
Product-Safety-Department  
Telephone: +49(0)251 / 9322 - 0, Email: msds@weicon.de

### Emergency phone number

**EMERGENCY CONTACT – USA (24h): Tel: ++1 202 464 2554**

**Transport:**

**TRANSPORT EMERGENCY CONTACT - USA (24h): Tel: ++1 202 464 2554**

## 2. Hazards identification

### Emergency overview

Appearance: Form: Aerosol  
Color: colorless, clear  
Odor: characteristic  
Classification: Flammable Aerosol - Category 1; Compressed Gas;  
Hazard symbols:



Signal word:

**Danger**

Hazard statements:

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.

Precautionary statements:

Keep out of reach of children.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Protect from sunlight. Store in a well-ventilated place.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### Regulatory status

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

## Fitting-Spray

Material number 115600

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

Page: 2 of 9

### Hazards not otherwise classified

Potentially explosive mixtures may form if adequate ventilation is not provided.  
Inhaling can lead to irritations of the respiratory tract and mucous membrane.  
Higher doses may have a narcotic effect.

see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterization: White mineral oil (petroleum), Preparation of active ingredients with propellant

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 106-97-8	Butane	< 25 %	Flammable Gas - Category 1. Compressed Gas.
CAS 74-98-6	Propane	< 25 %	Flammable Gas - Category 1. Compressed Gas.

## 4. First aid measures

General information: Take off immediately all contaminated clothing.

In case of inhalation: Move victim to fresh air, put at rest and loosen restrictive clothing.  
Seek medical attention.

Following skin contact: After contact with skin, wash immediately with soap and plenty of water. Consult a doctor if skin irritation persists.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

After swallowing: Immediately get medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth.

### Most important symptoms/effects, acute and delayed

Inhalation causes narcotic effects/intoxication. Dizziness.

### Information to physician

Treat symptomatically.

## 5. Fire fighting measures

Flash point/flash point range:

not applicable

Auto-ignition temperature: not determined

Suitable extinguishing media:

Alcohol resistant foam, dry chemical powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

High power water jet

### Specific hazards arising from the chemical

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.  
May form dangerous gases and vapours in case of fire. In case of fire may be liberated: Carbon monoxide and carbon dioxide.  
Potentially explosive vapor/air mixtures may form.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017  
Version: 3  
Language: en-US  
Date of print: Jan/10/2017

## Fitting-Spray

Material number 115600

Page: 3 of 9

Additional information: Heating will lead to pressure increase: Danger of bursting and explosion. Cool exposed containers with water spray.  
Move undamaged containers from immediate hazard area if it can be done safely.  
In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.  
Do not allow fire water to penetrate into surface or ground water.  
Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

## 6. Accidental release measures

Personal precautions: Provide adequate ventilation. Do not breathe gas/vapor/spray. Avoid contact with the substance. Eliminate all ignition sources if safe to do so. Wear appropriate protective equipment. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction. Keep unprotected people away. Cordon off downwind area at risk and warn inhabitants.

Environmental precautions: Do not allow to enter into ground-water, surface water or drains.  
In case of release, notify competent authorities. Danger of explosion!

Methods for clean-up: Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).  
Beware of reignition. Thoroughly clean surrounding area.

Additional information: Use explosion-proof equipment and non-sparking tools/utensils.  
Leaking cans, cans with spillage, are to be segregated, sprayed to empty state and disposed of. Refer to section 13 (Waste removal)

## 7. Handling and storage

### Handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe gas/vapor/spray.  
Avoid contact with skin and eyes. Wear appropriate protective equipment.  
Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation. Take off immediately all contaminated clothing.

Precautions against fire and explosion: Container under pressure. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects. Keep away from sources of ignition - No smoking.  
Take precautionary measures against static discharges.  
Use only explosion-protected equipment/instruments. Do not weld.  
In partially filled containers explosive mixtures may form. Vapors may form explosive mixtures with air.

### Storage

Requirements for storerooms and containers: Keep container tightly closed and in a well-ventilated place.  
Keep container dry. Keep only in the original container.  
Protect from heat and direct sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Store containers in upright position. Explosion protection required. Store locked up.

Hints on joint storage: Do not store together with combustible or self-igniting materials or any highly flammable solids. Keep away from food, drink and animal feedingstuffs.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

## Fitting-Spray

Material number 115600

Page:

4 of 9

## 8. Exposure controls / personal protection

### Exposure guidelines

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
106-97-8	Butane	USA: ACGIH: TWA USA: NIOSH: TWA	2370 mg/m <sup>3</sup> ; 1000 ppm 1900 mg/m <sup>3</sup> ; 800 ppm
74-98-6	Propane	USA: NIOSH: TWA USA: OSHA: TWA	1800 mg/m <sup>3</sup> ; 1000 ppm 1800 mg/m <sup>3</sup> ; 1000 ppm

### Engineering controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment. Use only explosion-proof equipment.  
See also information in chapter 7, section storage.

### Personal protection equipment (PPE)

Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: Flame retardant, antistatic and chemical resistant protective clothing.  
Protective gloves according to OSHA Standard - 29 CFR: 1910.138 (Solvent resistant protective gloves).  
Glove material: Nitrile rubber - Layer thickness: 0.4 mm  
Breakthrough time: 480 min.  
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.  
The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product.  
If higher concentrations occur: Wear self-contained breathing apparatus.

General hygiene considerations:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not pierce or burn, even after use.  
Do not spray on an open flame or other ignition source.  
Do not breathe vapor or spray. Avoid contact with skin and eyes.  
Take off immediately all contaminated clothing.  
When using do not eat, drink or smoke.  
Wash hands before breaks and after work.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

Appearance: Form: Aerosol  
Color: colorless, clear

Odor: characteristic

Odor threshold: not determined

pH value: not determined

Melting point/freezing point: not determined

Initial boiling point and boiling range: not applicable

Flash point/flash point range: not applicable

Evaporation rate: not determined



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

## Fitting-Spray

Material number 115600

Page: 5 of 9

Flammability:	Extremely flammable aerosol.
Explosion limits:	No data available
Vapor pressure:	at 68 °F: 3.5 hPa (Internal pressure of can)
Vapor density:	not determined
Density:	not determined
Water solubility:	slightly soluble
Partition coefficient: n-octanol/water:	not determined
Auto-ignition temperature:	not determined
Thermal decomposition:	No decomposition when used properly.
Viscosity, dynamic:	not determined
Viscosity, kinematic:	not determined
Explosive properties:	Product is not explosive. Potentially explosive vapor/air mixtures may form.
Ignition temperature:	not determined

## 10. Stability and reactivity

Reactivity:	Extremely flammable aerosol. Vapors may form explosive mixtures with air.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions	Contains gas under pressure; may explode if heated.
Conditions to avoid:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Incompatible materials:	Do not store together with combustible or self-igniting materials or any highly flammable solids.
Hazardous decomposition products:	May form dangerous gases and vapours in case of fire. In case of fire may be liberated: Carbon monoxide and carbon dioxide
Thermal decomposition:	No decomposition when used properly.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

## Fitting-Spray

Material number 115600

Page: 6 of 9

## 11. Toxicological information

### Toxicological tests

Toxicological effects: Acute toxicity (oral): Lack of data.  
Acute toxicity (dermal): Lack of data.  
Acute toxicity (inhalative): Lack of data.  
Skin corrosion/irritation: Lack of data.  
Eye damage/irritation: Lack of data.  
Sensitisation to the respiratory tract: Lack of data.  
Skin sensitisation: Lack of data.  
Germ cell mutagenicity/Genotoxicity: Lack of data.  
Carcinogenicity: Lack of data.  
Reproductive toxicity: Lack of data.  
Effects on or via lactation: Lack of data.  
Specific target organ toxicity (single exposure): Lack of data.  
Specific target organ toxicity (repeated exposure): Lack of data.  
Aspiration hazard: Lack of data.

### Symptoms

After contact with skin:  
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

## 12. Ecological information

### Ecotoxicity

Further details: ''

### Mobility in soil

No data available

### Persistence and degradability

Further details: No data available

### Additional ecological information

Volatile organic compounds (VOC):

44 % by weight = 301 g/L

General information: Do not allow to penetrate into soil, waterbodies or drains.

## 13. Disposal considerations

### Product

Recommendation: Do not pierce or burn, even after use.  
Special waste. Dispose of waste according to applicable legislation.  
Do not dispose of with household waste.

### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.  
Empty carefully and completely, if possible. Handle empty containers with care.  
Incineration may cause explosion.



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

## Fitting-Spray

Material number 115600

Page: 7 of 9

### 14. Transport information

#### USA: Department of Transportation (DOT)

Identification number: UN1950  
Proper shipping name: UN 1950, AEROSOLS  
Hazard class or Division: 2.1  
Labels: 2.1  
Special provisions: N82  
Packaging – Exceptions: 306  
Packaging – Non-bulk: None  
Packaging – Bulk: None  
Quantity limitations – Passenger aircraft / rail:  
75 kg  
Quantity limitations – Cargo only: 150 kg  
Vessel stowage – Location: A  
Vessel stowage – Other: 25, 87, 126



#### Sea transport (IMDG)

UN number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS  
Class or division, Subsidiary risk: Class 2.1, Subrisk-  
Packing Group: -  
EmS: F-D, S-U  
Special provisions: 63, 190, 277, 327, 344, 381,959  
Limited quantities: 1000 mL  
Excepted quantities: E0  
Contaminated packaging - Instructions: P207, LP200  
Contaminated packaging - Provisions: PP87, L2  
IBC - Instructions: -  
IBC - Provisions: -  
Tank instructions - IMO: -  
Tank instructions - UN: -  
Tank instructions - Provisions: -  
Stowage and handling: SW1 SW22  
Segregation: SG69  
Properties and observations: -  
Marine pollutant: no  
Segregation group: none

#### Air transport (IATA)

UN/ID number: UN 1950  
Proper shipping name: UN 1950, AEROSOLS, flammable  
Class or division, Subsidiary risk: Class 2.1  
Hazard label: Flamm. gas  
Excepted Quantity Code: E0  
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G  
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg  
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg  
Special provisions: A145 A167 A802  
Emergency Response Guide-Code (ERG): 10L



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

## Fitting-Spray

Material number 115600

Page: 8 of 9

### 15. Regulatory information

#### National regulations - U.S. Federal Regulations

**Butane:** TSCA Inventory: listed  
 TSCA HPVC: not listed  
 Clean Air Act:  
 Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f  
 NIOSH Recommendations:  
 Occupational Health Guideline: 0068\*

**Propane:** TSCA Inventory: listed  
 TSCA HPVC: not listed  
 Clean Air Act:  
 Accidental Release Prevention: Threshold 10000 lbs. / Basis for listing = f  
 NIOSH Recommendations:  
 Occupational Health Guideline: 0524

#### National regulations - U.S. State Regulations

**Butane:** Delaware Air Quality Management List:  
 DRQ: F 1000\*\* - RQ State: State requirements differs from Federal  
 Massachusetts Haz. Substance codes: 4,5,6  
 Minnesota Haz. Substance:  
 Codes: A - Ratings: - - Status: Title III  
 New Jersey RTK Hazardous Substance:  
 DOT: 1011 - Sub No.: 0273 - TPQ: -  
 Pennsylvania Haz. Substance code: -  
 Washington Air Contaminant:  
 TWA: 800 ppm - 1900 mg

**Propane:** California Proposition 65 code: -  
 Delaware Air Quality Management List:  
 DRQ: F 1000\*\* - RQ State: State requirements differs from Federal  
 Massachusetts Haz. Substance codes: 2,4,5,6  
 Minnesota Haz. Substance:  
 Codes: AP - Ratings: - - Status: Title III  
 New Jersey RTK Hazardous Substance:  
 DOT: 1978 - Sub No.: 1594 - TPQ: -  
 Pennsylvania Haz. Substance code: -  
 Washington Air Contaminant:  
 TWA: 1000 ppm - 1800 mg


#### National regulations - Great Britain

Hazchem-Code: -

### 16. Other information

Text for labeling: Contains < 25 % Butane, < 25 % Propane. Safety data sheet available on request.

Hazard rating systems:



NFPA Hazard Rating:

Health: 1 (Slight)  
 Fire: 4 (Severe)  
 Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 1 (Slight)  
 Flammability: 4 (Severe)  
 Physical Hazard: 0 (Minimal)  
 Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	4
PHYSICAL HAZARD	0
	X

Reason of change: ADR/RID 2017, IMDG 2017

Date of first version: Apr/27/2016





# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

## Fitting-Spray

Material number 115600

Revision date: Jan/2/2017

Version: 3

Language: en-US

Date of print: Jan/10/2017

Page: 9 of 9

### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.